

# RMV<sup>®</sup> Compound, Kleated Profile, Multi-Plied Spun Polyester

At the top of the list in rugged durability

- Special kleated profile features:
  - transverse molded cleats built into the belt
  - extra traction on inclines
- Goodyear's RMV compound is FDA/USDA compliant and offers:
  - superior resistance to animal fats, vegetable and mineral oils
  - high resin content offers state-of-the-art Melt-Weld fabrications
- Multi-Plied Spun Polyester carcass with HPC<sup>™</sup> technology increases strength and durability:
  - superior tracking in both directions
  - resistance to edge wicking and curling
  - flexibility over small pulleys
  - excellent adhesions provide improved belt wear
  - Thermo-Flo<sup>™</sup> splicing capabilities

Description	Plies	Working Tension		Approx. OAG		Weight		COF (approx.)	Pulley Dia.		Temp.	
		PIW*	KN/m	in.	mm	Lbs./Sq.ft.	Kg/Sq.m		In.	mm	°F	°C
RMV 150H2 KFw	2	150	26	0.250	6.4	1.07	5.2	0.30	2.5	64	20 - 180	-7 - 82

\*Elongation less than 2% at specified PIW

Description	Splicing Methods	Recommended Fasteners**		
		Clipper	Alligator	Staple
RMV 150H2 KFw	Finger-over-finger, Finger, Bias Stepped, Skived Bias, Mechanical Fasteners	36 or UCM36	7	62

\*\* Fastener manufacturer should be consulted to review specific belt and application information