

RMH™ Compound, Quadgrip Profile, HPC Carcass

Above average product release characteristics

- Hard durometer RMH compound is a version of Goodyear's RMV® compound:
 - good food release characteristics
FDA/USDA compliant
 - superior resistance to animal fats, vegetable and mineral oils
 - high resin content offers state-of-the-art Melt-Weld fabrications
- Quadgrip bottom cover profile:
 - protects the carcass
 - lowers the coefficient of friction over slider beds
- Multi-Plied Spun Polyester carcass with HPC™ technology increases strength and durability:
 - superior tracking in both directions
 - resistance to edge wicking and curling
 - flexibility over small pulleys
 - excellent adhesions provide improved belt wear
 - Thermo-Flo™ splicing capabilities

Description	Plies	Working Tension		Approx. OAG		Weight		COF (approx.)	Pulley Dia.		Temp.	
		PIW*	KN/m	in.	mm	Lbs./Sq.ft.	Kg/Sq.m		In.	mm	°F°	C
RMH 220S2 NQw	2	220	39	0.230	5.8	1.38	6.7	0.50	6.0	152	20-180	-7-82

*Elongation less than 2% at specified PIW

Description	Splicing Methods	Recommended Fasteners**		
		Clipper	Alligator	Staple
RMH 220S2 NQw	Finger-over-finger, Finger, Bias Stepped, Skived Bias, Mechanical Fasteners	3 or U3	25	187

** Fastener manufacturer should be consulted to review specific belt and application information