

PVG™ Compound, Interwoven Carcass

For value that lasts
season after season

- PVG Compound is specially designed for agricultural use:
 - moderate oil resistance
 - excellent slider abrasion resistance
 - low temperature to -20°F, intermittent
 - good wear characteristics
- Interwoven carcass is ideal for general conveying:
 - fusion and high impregnation provides superior fastener retention, tear resistance and low stretch qualities

Description	Plies	Working Tension		Approx. OAG		Weight		COF (approx.)	Pulley Dia.		Temp.	
		PIW*	KN/m	in.	mm	Lbs./Sq.ft.	Kg/Sq.m		In.	mm	°F	°C
PVG 100S1 CBb	1	100	18	0.110	2.8	0.64	3.1	0.25	1.5	38	-20 – 180	-29 – 82
PVG 120S1 CBb	1	120	21	0.135	3.4	0.80	3.9	0.25	2.0	51	-20 – 180	-29 – 82
PVG 150S1 CBb	1	150	26	0.165	4.2	0.96	4.6	0.25	2.5	64	-20 – 180	-29 – 82
PVG 150S1 CNb	1	150	26	0.180	4.6	1.11	5.4	0.50	2.5	64	-20 – 180	-29 – 82

*Elongation less than 2% at specified PIW

Description	Splicing Methods	Recommended Fasteners**		
		Clipper	Alligator	Staple
PVG 100S1 CBb	Finger, Skived Bias, Mechanical Fasteners	1SP or UX1SP	7	62
PVG 120S1 CBb	Finger, Skived Bias, Mechanical Fasteners	1 or UX1	7	125
PVG 150S1 CBb	Finger, Skived Bias, Mechanical Fasteners	2 or U2	20	125
PVG 150S1 CNb	Finger, Skived Bias, Mechanical Fasteners	2 or U2	20	125

** Fastener manufacturer should be consulted to review specific belt and application information