



FLAT BELTING (TRULY ENDLESS)

COMPASS CORD BELT

Compass Number	Type of Service	Construction	Width Limits	Length Limits
L	Light	Endless	1"-36"	20.5"-120"
M	Medium	Endless	2"-36"	20.5"-135"
C	Heavy	Endless	4"-36"	49"-135"
H	Extra Heavy	Endless	4"-36"	49"-135"

*Special sizes available on request. Contact your local GTM or Goodyear Distributor.

COMPASS 250 & 350 STEEL CABLE BELT

Sizes:	
<p>DRUM CURED</p> <ul style="list-style-type: none"> Widths from 1" up to 28" available in lengths from 25" to 170". <p><i>Note: All belts produced in endless construction only.</i></p>	<p>PRESS CURED</p> <ul style="list-style-type: none"> Widths from 1" up to 36" available in lengths from 120" to 135'.

*Special sizes available on request. Contact your local GTM or Goodyear Distributor.

TRULY ENDLESS MULTIPLE PLY BELT

Sizes:	
<ul style="list-style-type: none"> Available in widths of 1" to 48" (drum cured) and 1" to 36" (press cured). Product availability in truly endless or roll lot construction. 	<p>Contact your local GTM or Goodyear Distributor for manufacturing capability.</p>

*Special sizes available on request. Contact your local GTM or Goodyear Distributor.

REGULATOR™ POWER STRAP BELTING

Construction	Overall Thickness	Working Strength	Ultimate Strength	Minimum Pulley Diameter
<p>3/4" Regulator</p> <p>Flexten® Cable Cord Rubber Friction Fabric Both Sides</p>	.10"	1% Stretch at 500#	2,400#	1-1/2"
<p>1" Regulator</p> <p>Flexten® Cable Cord Rubber Friction Fabric Both Sides</p>	.10"	1% Stretch at 625#	3,000#	1-1/2"
<p>1-1/2" Regulator</p> <p>Flexten® Cable Cord Rubber Friction Fabric Both Sides</p>	.10"	1% Stretch at 850#	4,000#	1-1/2"

*Special sizes available on request. Contact your local GTM or Goodyear Distributor.

SPECIALTY