

VPR® Hand-Wind

Designed for general and industrial use. Ideal for production areas, maintenance and service areas, washdown equipment and service vehicles. Reels do not include hose.

- Heavy steel construction
- Corrosion resistant epoxy powder-coat finish
- Spring tension brake
- Brass swivel
- Simple mounting for floor, wall or work bench
- Nitrile seals

For dimensions, see page 23



Reels do not include hose.

CL & CH



Low Pressure (300 PSI)

Model	Inlet hose fitting (NPT)	Hose Inner Diameter	Hose Outer Diameter	Capacity	
				feet	m
CL102	1/4"	1/4"	5/8"	100	30.4
CL202	1/4"	1/4"	5/8"	200	60.8
CL103	3/8"	3/8"	3/4"	50	15.2
CL203	3/8"	3/8"	3/4"	100	30.4

High Pressure (3,000 PSI)

Model	Inlet hose fitting (NPT)	Hose Inner Diameter	Hose Outer Diameter	Capacity	
				feet	m
CH102	1/4"	1/4"	5/8"	100	30.4
CH202	1/4"	1/4"	5/8"	200	60.8
CH103	3/8"	3/8"	3/4"	50	15.2
CH203	3/8"	3/8"	3/4"	100	30.4
CH303	3/8"	3/8"	3/4"	350	106.4
CH304	1/2"	1/2"	7/8"	270	82.0

Maximum capacity dimensions listed.