NCLOSED REELS

Enclosed VPR® Standard

Enclosed VPR® hose reels include a brass and stainless steel fluid path, durable steel finish, and ratchet lock. The reels are designed to handle lowpressure hose (300 PSI).

- Durable steel construction
- Containerized mainspring for easy maintenance
- Brass and stainless steel fluid path
- Durable epoxy powder-coat finish
- Ratchet lock

For dimensions, see page 22



EΝ

| Inlet Hose Fitting (NPT) | Hose Inner Diameter | | | Pressure PSI | |
|-----------------------------|------------------------|--|--|---|---|
| 3/8" | 3/8" | 25 | 7.6 | 300 | |
| 3/8" | 3/8" | 50 | 15.2 | 300 | |
| 1/2" | 1/2" | 50 | 15.2 | 300 | |
| | 3/8" 3/8" | Fitting (NPT) Diameter 3/8" 3/8" 3/8" 3/8" | Fitting (NPT) Diameter ft. 3/8" 3/8" 25 3/8" 3/8" 50 | Fitting (NPT) Diameter ft. m 3/8" 3/8" 25 7.6 3/8" 3/8" 50 15.2 | Fitting (NPT) Diameter ft. m PSI 3/8" 3/8" 25 7.6 300 3/8" 3/8" 50 15.2 300 |

Hose Specs

Type: EPDM/SBR tube Red SBR cover Max Temp: 176° F (80°C)

Shop Reel

This plastic enclosed shop duty reel is designed for general shop use.

- Integrated wall/ceiling bracket
- Enclosure made of high-quality impact-resistant polypropylene
- Includes 36" lead-in hose
- Ratchet lock

For dimensions, see page 21

PL

| Model | Inlet Hose | Hose Inner | Length | Pressure |
|-------|---------------|------------|---------|----------|
| | Fitting (NPT) | Diameter | ft. m | PSI |
| PL450 | 1/2" | 1/2" | 50 15.2 | 300 |



Hose Specs Type: PVC tube Blue PVC cover

Max Temp: 176' F (80'C)