

Stainless Steel Aero-Motive® Premium Industrial Grade

Designed for general and industrial use. Ideal for production lines, material handling equipment, service areas, maintenance applications and service vehicles.

- Steel construction for long life in industrial applications
- Containerized main spring for safe, easy maintenance
- Adjustable guide arm - 8 positions
- Six-roller guide to protect hose
- Brass and stainless steel fluid path
- Ratchet lock and easy tension adjustment
- Hose stop included with all models
- Nitrile seals

Accessories on pages 16

For dimensions, see page 19



PWS, PAS, PBS

Model	Inlet hose fitting (NPT)	Hose Inner Diameter	Capacity feet	m	Pressure PSI	Housing Material
PWL300S	3/8"	3/8"	25	7.6	300	Composite
PAL300S	3/8"	3/8"	30	9.1	300	Stainless Steel
PBL400S	1/2"	1/2"	50	15.2	300	Stainless Steel

Hose Specs

Type: PVC tube
 Black PVC cover
 Max Temp: 176° F (80°C)

Enclosed Stainless Steel Aero-Motive® Premium Industrial Grade

Enclosed hose reels include a stainless steel fluid path, durable steel finish, and ratchet lock. The reels are designed to handle low-pressure hose (300 PSI).

- Durable stainless steel construction
- Containerized mainspring for easy maintenance
- Brass and stainless steel fluid path
- Ratchet lock

For dimensions, see page 21



ES

Model	Inlet Hose Fitting (NPT)	Hose Inner Diameter	Length ft. m	Pressure PSI
PAL200ES	1/4"	1/4"	w/o hose	300
PAL300ES	3/8"	3/8"	w/o hose	300
PBL450ES	1/2"	1/2"	50 15.2	300
PBL400ES	1/2"	1/2"	w/o hose	300

Hose Specs

Type: PVC tube
 Black PVC cover
 Max Temp: 176° F (80°C)