

Accessories

HOSE ASSEMBLIES*

*Hose assemblies for all reels except DC & T series.

General Purpose Oil Resistant

Model	ID (inches)	Length (feet)	Max Pressure (PSI)	Tube Type	Cover Type
HOSL001	1/4"	30	300	EPDM/SBR	Red SBR
HOSL035	3/8"	25	300	EPDM/SBR	Red SBR
HOSL002	3/8"	30	300	EPDM/SBR	Red SBR
HOSL004	3/8"	50	300	EPDM/SBR	Red SBR
HOSL005	1/2"	30	300	EPDM/SBR	Red SBR
HOSL006	1/2"	50	300	EPDM/SBR	Red SBR

PVC

Model	ID (inches)	Length (feet)	Max Pressure (PSI)	Tube Type	Cover Type
HOSL047	1/4"	30	300	PVC	Black PVC
HOSL049	3/8"	25	300	PVC	Black PVC
HOSL050	3/8"	30	300	PVC	Black PVC
HOSL052	3/8"	50	300	PVC	Black PVC
HOSL054	1/2"	30	300	PVC	Black PVC
HOSL056	1/2"	50	300	PVC	Black PVC

Medium Pressure Oil Resistant

Model	ID (inches)	Length (feet)	Max Pressure (PSI)	Tube Type	Cover Type
HOSM020	1/4"	30	2750	Synthetic	Black Synthetic
HOSM011	3/8"	30	2250	Synthetic	Black Synthetic
HOSM059	3/8"	35	2250	Synthetic	Black Synthetic
HOSM012	3/8"	50	2250	Synthetic	Black Synthetic
HOSM060	1/2"	30	2000	Synthetic	Black Synthetic
HOSM024	1/2"	50	2000	Synthetic	Black Synthetic

High Pressure Oil Resistant

Model	ID (inches)	Length (feet)	Max Pressure (PSI)	Tube Type	Cover Type
HOSH015	1/4"	30	5000	Synthetic	Black Synthetic
HOSH016	1/4"	50	5000	Synthetic	Black Synthetic
HOSH061	3/8"	35	4000	Synthetic	Black Synthetic
HOSH018	3/8"	50	4000	Synthetic	Black Synthetic

HOSE STOP KIT

For use with standard hoses

Model	ID	Reel Type/Family
STPV006	1/4"	Std.
STPV007	3/8"	Std.
STPV008	1/2"	Std.
STPV044	1/4"	Stainless
STPV045	3/8"	Stainless
STPV046	1/2"	Stainless

SINGLE EYE HOSE GRIPS

Commonly referred to as "Chinese Fingers" or "Basket Grips."

Designed to relieve concentrated strain on hose termination.




Model	Hose Diameter	Dim. A In.	Dim. A mm	Dim. B In.	Dim. B mm	Approx. Break Strength
36567	0.53 - 0.73"	6.5	165	7.0	178	1000 lbs.
36569	0.70 - 0.85"	7.25	184	7.0	178	1100
36574	0.96 - 1.25"	9.0	299	9.0	229	1500
35034	1.25 - 1.49"	15.0	381	15.0	381	2000

Snap hook (No. 01146P0015) must be ordered separately if desired.

PB201 PIVOT BASE


For use with hose reels when less than 330° rotation is required. Fits all D*, M*, H*, S*, PA* and PB* reels.



SWING MOUNT

The additional range of motion provided by the swing mount helps extend hose life and operation efficiency. Can be ceiling or wall mounted.

Model	Used with Reel Series	Dim. A in.	Dim. A mm	Dim. B in.	Dim. B mm
SR105	D*/M*/H*/S*/PA*/PB*	3.55	90.2	5.60	142.2
SB103	TL/TH/TB	3.55	90.2	5.60	142.2



SWIVELS

Model	ID	Max PSI	Reel Type/Family
SVLV025	1/4"	3000	DA2, MA2, PBL2, PBM2
SVLV024	3/8"	3000	DA3, MA3, PBL3, PBM3
SVLV035	3/8"	3000	DB3, MB3
SVLV036	1/2"	3000	DB4, MB4, PBL4, PBM4
SVLV037	1/4"	5000	HA2, HB2, PBH2
SVLV028	3/8"	5000	HA3, HB3, PBH3

RATCHET REPLACEMENT KIT

Model	Reel Type/Family
RTVCV010	AM Stainless, except PW
RTVCV008	AM, all PW
RTVCV002	VPR A size, Stainless
RTVCV005	VPR B size, Stainless

LEAD-IN HOSE (HOSE WHIPS)

Single hose - EPDM/SRB, max 300 PSI.
Welding hose - rubber core, rubber cover, max 200 PSI.

Model	Hose Inner diameter	Length ft.	Length mm	Description
5383800002	1/4"	4	1.2	Single hose
5382100029	3/8"	4	1.2	Single hose
5372600025	1/2"	4	1.2	Single hose
4437800414	3/4"	4	1.2	Single hose
4437800511	1"	4	1.2	Single hose
5503800000	1/4"	5	1.5	Dual welding reel