



Series A1307 — Standard duty reinforced PVC water hose

Series A1317 — Heavy duty reinforced PVC water hose

An all-purpose PVC hose for light duty industrial watering applications.

Construction:

- Tube — Smooth black PVC compound
- Reinforcement — High tensile strength yarn
- Cover — Smooth opaque green PVC compound

Features:

- Economical
- Lightweight and easy to handle
- Good resistance to weather aging, ozone and ultraviolet light
- Available in assemblies on special order
- Silicone-free
- One-piece lengths

Applications:

- Light duty industrial watering
- Lawn and garden watering
- Nursery water supply lines
- Light duty commercial washdown

An all-purpose heavy duty PVC hose that's ideal for golf courses, parks and construction projects.

Construction:

- Tube — Smooth black PVC compound
- Reinforcement — High tensile strength yarn
- Cover — Smooth transparent green PVC compound

Features:

- Higher working and burst pressures
- Abrasion-resistant cover
- Good resistance to weather aging
- Available in assemblies on special order
- Silicone-free
- One-piece lengths

Applications:

- Golf course water lines
- Heavy duty commercial and construction use
- Municipal maintenance and park departments
- Irrigation supply lines
- Heavy duty washdown

Service Temperature Range: +25°F (-4°C) to 150°F (+65°C)

Series A1307 — Standard duty reinforced PVC water hose — solid green cover

Series No.	Size Code	Nominal ID		Nominal OD		Max. Working† Pressure (PSI)		Standard Length Coils	Approx. Wt. per Pkg.
		(In)	(mm)	(In)	(mm)	@ 70°F (20°C)	@ 122°F (50°C)		
A1307	08	1/2	12.7	.692	17.6	125	50	300 ft.	34 lbs.
A1307	10	5/8	15.9	.817	20.8	125	50	300 ft.	40 lbs.
A1307	12	3/4	19.1	.972	24.7	100	40	300 ft.	53 lbs.
A1307	16	1	25.4	1.297	32.9	100	40	200 ft./300 ft.	69 lbs./104 lbs.

Series A1317 — Heavy duty reinforced PVC water hose — green tint cover

Series No.	Size Code	Nominal ID		Nominal OD		Max. Working† Pressure (PSI)		Standard Length Coils	Approx. Wt. per Pkg.
		(In)	(mm)	(In)	(mm)	@ 70°F (20°C)	@ 122°F (50°C)		
A1317	12	3/4	19.1	1.025	26.0	125	50	300 ft.	65 lbs.
A1317	16	1	25.4	1.297	32.9	125	50	200 ft./300 ft.	60 lbs./90 lbs.

† Note: Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.