

Surface Protection and Rust Prevention

- Stabilize existing rust
- Guard against corrosion
- Prevent electro-chemical corrosion
- Increase belt friction



SURFACE PROTECTION AND RUST PREVENTION

Solution	Belt Dressing	Rust Treatment	Corrosion Protection			
			General Purpose			
			Cathodic Protection	Undercoating	Non-Drying	Color Coding
	Loctite® Belt Dressing & Conditioner	Loctite® Extend® Rust Treatment	Loctite® Cold Galvanizing Compound	Loctite® Heavy-Duty Rubberized Undercoating	Loctite® Maxi-Coat™	Loctite® Color Guard®
Description	Liquid Spray	Rust Converter	Zinc Spray	Rubberized Spray	Waxy Film	Rubber Coating
Color	Colorless	Matte black	Grey	Black	Brown	Red, Yellow, Blue, Black
Temperature Range	Up to 200°F (93°C)	Up to 250°F (121°C)	Up to 400°F (204°C)	Up to 200°F (93°C)	Up to 200°F (93°C)	Up to 200 °F (93°C)
Dry Time	N.A.	30 min.	15 min.	20 min.	N.A.	4 hrs.
Common Sizes / Part Number	12 oz. aerosol – 30527	10.25 oz. aerosol – 30539 1 qt. bottle – 75430 1 gallon bottle – 75448 5 gallon pail – 75465	15 oz. aerosol – 82039	16 oz. aerosol – 30538	12 oz. aerosol – 51211 1 gallon can – 51213	11 oz. aerosol* 14.5 fl. oz. can* 1 gallon can*

* Available in Black, Blue, Red and Yellow. See index for Part Numbers.

Additional Products		
Name	Part #	Pkg. Size
Loctite® Primer for Color Guard®	34994	1 gallon pail
Loctite® Thinner for Color Guard®	34995	1 gallon pail
Loctite® Nordbak® Chemical Resistant Coating	96092	12 lb. kit




Loctite® Belt Dressing & Conditioner
Recommended to prevent slipping and increase friction for all types of belts. Extends belt life. Penetrates the cord fibers of "V" belts to restore pliability and flexibility. Eliminates squeaking and glazing.



Loctite® Extend® Rust Treatment
Converts existing rust into a stable base. Cured product acts as a primer ready for painting. Protects surfaces from corrosion. Use on metal pipes, valves, fittings, storage tanks, fences, guard rails, conveyors, construction and agricultural equipment. ABS Approved.



Loctite® Cold Galvanizing Compound
Sprays on metal surfaces to prevent corrosion even when the surface is scratched. Ideal touch-up for welded seams. Highly resistant to salt corrosion and water. Not resistant to acid or alkaline solutions. Contains no ozone-depleting compounds.



Loctite® Heavy-Duty Rubberized Undercoating
This heavy-duty undercoating seals, protects, and insulates. Rubberized for maximum durability.



Loctite® Maxi-Coat™, Heavy Duty Rustproofing
Heavy-duty coating provides long-term protection for metal parts, equipment, and machinery. Forms a protective, waxy film which seals out moisture, air, acid, and other corrosive elements. Great for protecting parts in storage. Removable.



Loctite® Color Guard®, Tough Rubber Coating
Inhibits rust and corrosion. Seals, insulates, and identifies almost any material in minutes. Creates a non-slip gripping surface. Rubber coating won't crack or chip. Acid and alkali resistant. Dip, spray, or brush to apply. Suggested applications: tools, metal, electrical connections, masonry, wood, conveyors, glass, rope, fabric.

GOODYEAR
RUBBER PRODUCTS INC.

Call Toll Free: **1-866-711-4673**
WebSales@GoodyearRubberProducts.com

**We Ship
World Wide**