

BRASS AIR COCKS


BRASS FITTINGS

BRASS

- For use on low pressure air systems.
- Designed for working pressure of 80 PSI at moderate temperatures.
- Spring-key type cocks of all brass construction with stainless steel springs.
- Machine finish is standard. Polished or plated finish available at extra cost.

MIP X BIBB


- tee handle
- no hex



Part #	MIP x BIBB	Ind. #	A	B	Approx. Wt. Lbs.	List Price
46-300	1/8"	6	1.53	1.55	0.12	15.37
46-301	1/4"	7	1.61	1.54	0.14	14.96

MIP X BIBB


- lever handle
- no hex



Part #	MIP x BIBB	Ind. #	A	B	Approx. Wt. Lbs.	List Price
46-305	1/8"	12	2.01	1.71	0.14	15.79
46-306	1/4"	13	2.09	1.66	0.14	16.21

MIP X BIBB


- tee handle
- hex



Part #	MIP x BIBB	Ind. #	A	B	Hex	Approx. Wt. Lbs.	List Price
46-310	1/8"	63	1.64	1.51	0.56	0.14	14.28
46-311	1/4"	64	1.69	1.54	0.62	0.14	16.33
46-312	3/8"	8	1.75	1.48	0.75	0.17	15.46

MIP X BIBB

- lever handle
- hex



Part #	MIP x BIBB	Ind. #	A	B	Hex	Approx. Wt. Lbs.	List Price
46-315	1/8"	65	2.11	1.71	0.62	0.14	15.30
46-316	1/4"	66	2.16	1.71	0.62	0.16	16.62
46-317	3/8"	14	2.26	1.71	0.75	0.18	18.70
46-318	1/2"	15	2.32	1.46	0.87	0.26	16.38

Dimension data can change without notice.
Please call us when dimensions are critical.

**MIDLAND
METAL**

GOODYEAR
RUBBER PRODUCTS INC.

Call Toll Free: **1-866-711-4673**
WebSales@GoodyearRubberProducts.com

**We Ship
World Wide**