

MANIFOLDS

PNEUMATIC ACCESSORIES

Materials:


Aluminum with black anodizing for corrosion resistance.

Specifications:

Max Operating Pressure: 1000PSI

Temperature: -10° to 200°F

Media: Air and liquids compatible with materials of construction.



THREADED PORTS

Part #	Ports	List Price	A NPT	B NPT	C	D	E	F	G	H	J	K	M	R
28-448	2	37.19						N/A		1.75				
28-449	3	41.64						0.75		2.50				
28-450	4	55.78						1.50		3.25				
28-451	5	49.00						2.25		4.00				
28-452	6	51.96	1/8	1/4	1.00	0.50	0.75	3.00	0.17	4.75	0.70	0.50	0.88	0.15
28-453	7	54.72						3.75		5.50				
28-454	8	57.55						4.50		6.25				
28-455	9	59.67						5.25		7.00				
28-456	10	82.52						6.00		7.75				
28-457	2	42.14						N/A		2.13				
28-458	3	55.36						0.88		3.00				
28-459	4	59.35						1.75		3.88				
28-460	5	63.84						2.63		4.75				
28-461	6	67.94	1/4	3/8	1.25	0.63	0.88	3.50	0.20	5.63	0.89	0.63	1.06	0.18
28-462	7	59.32						4.38		6.50				
28-463	8	76.00						5.25		7.38				
28-464	9	65.04						6.13		8.25				
28-465	10	67.38						7.00		9.13				
28-466	2	64.97						N/A		3.13				
28-467	3	83.36						1.13		4.25				
28-468	4	87.80						2.25		5.38				
28-469	5	91.84						3.38		6.50				
28-470	6	96.93	3/8	3/8	1.25	1.00	1.13	4.50	0.20	7.63	0.89	0.63	1.56	0.18
28-471	7	113.90						5.63		8.75				
28-472	8	107.25						6.75		9.88				
28-473	9	109.66						7.88						
28-474	10	136.85						9.00						

RIGHT ANGLE MANIFOLD

Part #	List Price
28-448R	37.19
28-449R	42.14
28-450R	57.27
28-451R	41.64
28-452R	45.67
28-453R	68.86
28-454R	46.03
28-455R	49.21
28-456R	82.72
28-457R	49.00
28-458R	52.67
28-459R	61.61
28-460R	51.96
28-461R	56.07
28-462R	79.61
28-463R	54.72
28-464R	59.32
28-465R	89.44
28-466R	57.55
28-467R	62.64
28-468R	107.25
28-469R	59.67
28-470R	65.04
28-471R	109.66
28-472R	61.65
28-473R	67.38
28-474R	112.13

3 IN 1 ALUMINUM AIR MANIFOLD

No need to connect and disconnect every time you want to change tools. Supply 3 air tools from one outlet. These manifolds have one inlet with three outlets.



- S685-4 D3406
- S685-6 D3408
- S685-8 3104
- D3404 3106

Part #	Size	List Price
320-120	1/4" Inlet	14.28
three 1/4" Outlets		

SAFETY BLOW GUN

- N/P steel handle with plastic sleeve 20430AD
- Brass Valve S148
- Zinc body D204-30
- Aluminum nozzle 5114 6475
- 51-124
- 401



Part #	Size	List Price
320-050	1/4" Inlet	6.67
1/8" Outlet		

RUBBER TIPPED NOZZLE



- 51-521
- 2058
- D201RT
- 411R

Makes positive seal between gun and fuel line or other openings. Use only on air line regulated to 30 PSI or less

Part #	List Price
320-070	12.86

HIGH FLOW SAFETY NOZZLE



- 51-338
- SST10
- 411BT
- 2056

Meets OSHA regulations of 30 PSI maximum outlet pressure when line pressure is 150 PSI or less. Has an air pressure bypass which prevent build up of tip pressure even if nozzle is blocked. Adapts to any blow gun with a 1/8" NPT nozzle port

Part #	List Price
320-075	3.00

AIR ADJUSTING VALVE

(NOT A SHUT-OFF VALVE)

- Permits accurate flow control in either direction
- Set knob to desired flow rate
- Spring-loaded ratchet permits positive flow adjustment without drift



AIR ADJUSTING VALVE

Part #	Size	List Price
28-599	1/4"	11.64

MULTI-PURPOSE AIR VENT

705



Part #	Size	List Price
46-048	1/8	3.15

ACCESSORIES