


- **Sales Tip:** Rubber top resists exposure to sparks from welding. Easy to clean nondirectional top surface.
- **Where to Specify:** Welding locations.

- Pebble-embossed top surface of resilient SBR rubber is combined with dense closed cell foam base utilizing NOTRAX® exclusive UniFusion™ technology.
- UniFusion™ bond guaranteed for the life of the mat – See warranty for details
- Overall mat thickness is 1/2 inch.
- Sloped beveled foam on all 4 undersides affords easy access onto and off of mat.
- Custom widths available



RESULTS from INDEPENDENT TEST LABS & PRESENTED as COMPARISONS to OTHER NOTRAX® INDUSTRIAL MATS



#480 PEBBLE TRAX®

Stock Sizes	2' x 3'	3' x 5'	3' x 12'	Custom Widths		
List Price	\$57.72	\$144.30	\$346.32	\$11.54/sq.ft.		
Weight (lbs.)	9	20	50	1.17/sq.ft.		
Roll Sizes & Custom Sizes	2' x 75'	3' x 75'	4' x 75'	2' Widths	3' Widths	4' Widths
List Price	\$1443.00	\$2164.50	\$2886.00	\$9.62/sq.ft.	\$9.62/sq.ft.	\$9.62/sq.ft.
Weight (lbs.)	176	264	351	1.17/sq.ft.	1.17/sq.ft.	1.17/sq.ft.

Shipping Location: Superior Manufacturing Group - Moselle, MS 39459

* For applications on carpeted, finished or polished surfaces, Mat Hold (090 - pg.59) is recommended to minimize mat movement

