



SPIRALITE® 111

PVC SPECIAL GRAY STANDARD SUCTION HOSE

NOMINAL SIZE	inch	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	5"	6"
APPROX. O.D.	inch	1.01	1.27	1.53	1.82	2.36	2.90	3.44	4.52	5.65	6.80
RECOMMENDED W.P. AT 68°F	psi	100	90	90	90	70	65	55	50	45	45
VACUUM RATING AT 68°F	in/HG	28	28	28	28	28	28	28	28	28	28
RECOM. MIN. BEND RADIUS AT 68°F*	inch	2	3	4	5	6	8	9	13	21	24
APPROX. B.P. AT 68°F	psi	300	270	270	270	210	195	165	150	135	135
APPROX. WT.	lbs./ft.	.20	.27	.36	.47	.66	.92	1.20	1.87	3.00	4.56

* BEND RADIUS FOR CONTINUOUS SERVICE.

• **APPEARANCE/CONSTRUCTION:**

Gray PVC with white helix.
Smooth wall and interior.

• **BENEFITS:**

- Excellent blend of economy and quality.
- Smooth interior prevents material blockage.

• **GENERAL APPLICATIONS:**

- General suction for water & light chemical solutions.

• **TEMPERATURE RANGE:**

-10°F to +130°F

• **STANDARD LENGTHS:**

3/4" thru 6" 100ft.



SPIRALITE® 113

PVC SPECIAL GREEN STANDARD SUCTION HOSE

NOMINAL SIZE	inch	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	5"	6"	8"
APPROX. O.D.	inch	1.00	1.25	1.51	1.81	2.34	2.88	3.42	4.49	5.58	6.80	8.94
RECOMMENDED W.P. AT 68°F	psi	100	90	70	70	60	60	50	45	45	45	40
VACUUM RATING AT 68°F	in/HG	28	28	28	28	28	28	28	28	28	28	28
RECOM. MIN. BEND RADIUS AT 68°F*	inch	2	3	4	5	6	8	9	13	21	24	40
APPROX. B.P. AT 68°F	psi	300	270	210	210	180	180	150	135	135	135	120
APPROX. WT.	lbs./ft.	.20	.26	.32	.45	.63	.90	1.16	1.82	3.00	4.56	7.05

* BEND RADIUS FOR CONTINUOUS SERVICE.

• **APPEARANCE/CONSTRUCTION:**

"Special" Green PVC tube with white PVC helix. Smooth wall and interior.

• **BENEFITS:**

- Excellent blend of economy and quality.
- Smooth interior prevents material blockage.

• **GENERAL APPLICATIONS:**

- General suction for water & light chemical solutions.

• **TEMPERATURE RANGE:**

-10°F to +130°F

• **STANDARD LENGTHS:**

3/4" thru 6" 100ft.
8" 20' 25' 30'