



SPIRALITE® 124-PS

PVC PIPE-SIZED CORRUGATED SUCTION HOSE

NOMINAL SIZE	inch	23/8"	31/2"	41/2"	65/8"	85/8"
APPROX. O.D.	inch	2.85	4.15	5.26	7.60	9.80
RECOMMENDED W.P. AT 68°F	psi	40	35	30	30	30
VACUUM RATING AT 68°F	in/HG	28	28	28	28	28
RECOM. MIN. BEND RADIUS AT 68°F*	inch	4	7	9	17	22
APPROX. BP AT 68°F*	psi	120	95	90	90	90
APPROX. WT.	lbs./ft.	.72	1.19	1.85	4.41	6.67

* BEND RADIUS FOR CONTINUOUS SERVICE.

- **APPEARANCE/CONSTRUCTION:**
Clear PVC with white helix.
Corrugated cover, smooth interior.
- **BENEFITS:**
 - Specially sized to fit over pipe.
 - Smooth interior prevents material blockage.
 - Clear wall allows easy inspection of material flow.
- **GENERAL APPLICATIONS:**
 - Landfill gas recovery.
 - Water/light chemical suction and transfer.
- **TEMPERATURE RANGE:**
-10°F to +130°F
- **STANDARD LENGTHS:**

2-3/8" thru 6-5/8"	100ft.
8-5/8"	20' 25' 30'



SPIRALITE® 125

PVC CLEAR CORRUGATED SUCTION HOSE

NOMINAL SIZE	inch	3/4"	1"	11/4"	11/2"	2"	21/2"	3"	4"	5"	6"	8"	10"	12"
APPROX. O.D.	inch	.99	1.26	1.61	1.86	2.44	2.98	3.54	4.65	5.73	6.98	9.14	11.30	13.27
RECOMMENDED W.P. AT 68°F	psi	50	35	50	50	40	40	35	35	30	35	35	30	25
VACUUM RATING AT 68°F	in/HG	28	28	28	28	28	28	28	28	28	28	28	21	15
RECOM. MIN. BEND RADIUS AT 68°F*	inch	1	2	3	3	4	5	6	8	11	15	18	28	36
APPROX. B.P. AT 68°F	psi	150	105	150	150	120	120	105	105	90	105	105	90	75
APPROX. WT.	lbs./ft.	.11	.14	.31	.37	.57	.77	1.04	1.65	2.34	4.08	6.34	9.10	10.14

* BEND RADIUS FOR CONTINUOUS SERVICE.

- **APPEARANCE/CONSTRUCTION:**
Clear PVC with white helix.
Corrugated cover, smooth interior.
- **BENEFITS:**
 - Good combination of durability and flexibility.
 - Smooth interior prevents material blockage.
 - Clear wall allows easy inspection of material flow.
- **GENERAL APPLICATIONS:**
 - General suction for water & light chemical solutions.
- **TEMPERATURE RANGE:**
-10°F to +130°F
- **STANDARD LENGTHS:**

3/4" thru 6"	100ft.
8" thru 12"	20' 25' 30'
8" also in	50'