



## SPIRALITE® 2400

### EPDM RUBBER DUCT HOSE

- **APPEARANCE/CONSTRUCTION:**

Black EPDM rubber tube with natural poly-ethylene helix.  
Corrugated wall, smooth interior.

- **BENEFITS:**

- Excellent flexibility and durability.
- Good chemical resistance (see chemical resistance chart).

- **GENERAL APPLICATIONS:**

- Air and corrosive atmosphere.
- Water/light chemical suction and transfer.

- **TEMPERATURE RANGE:**

-30°F to +140°F

- **STANDARD LENGTHS:**

1-1/2" thru 6" 100ft.

NOMINAL SIZE	inch	1 1/2"	2"	2 1/2"	3"	4"	6"
APPROX. O.D.	inch	1.83	2.42	3.00	3.59	4.68	6.88
RECOMMENDED W.P. AT 68°F	psi	33	27	25	24	22	20
RECOM. MIN. BEND RADIUS AT 68°F*	inch	3	4	5	6	7	10
APPROX. B.P. AT 68°F	psi	100	80	75	72	66	60
APPROX. WT.	lbs./ft.	.30	.45	.65	.89	1.27	2.43

\* BEND RADIUS FOR CONTINUOUS SERVICE.



## SPIRALITE® 2700

### BRAIDED EPDM RUBBER SUCTION / DISCHARGE HOSE

- **APPEARANCE/CONSTRUCTION:**

Black EPDM rubber tube and wall with polyester braid reinforcement; black poly-ethylene helix.  
Corrugated wall, smooth interior.

- **BENEFITS:**

- Excellent flexibility and durability.
- Higher working pressure than standard EPDM.
- Good chemical resistance (see chemical resistance chart).

- **GENERAL APPLICATIONS:**

- Suction / Discharge service for industry and agriculture.
- Applications requiring the chemical resistance of EPDM rubber at higher working pressures.

- **TEMPERATURE RANGE:**

-30°F to +140°F

- **STANDARD LENGTHS:**

2" thru 4" 100ft.

NOMINAL SIZE	inch	2"	3"	4"
APPROX. O.D.	inch	2.66	3.86	4.87
RECOMMENDED W.P. AT 68°F	psi	100	85	70
VACUUM RATING AT 68°F	in/HG	28	28	28
RECOM. MIN. BEND RADIUS AT 68°F	inch	4	6	8
APPROX. B.P. AT 65°F	psi	310	260	210
APPROX. WT.	lbs./ft.	.88	1.61	2.30