


Brass Shutoff V201F

Flare to Flare

Temperature Range: -40° to +250° F

PART NO.	TUBE SIZE	L	M	FLOW DIA. D
V201F-6-6	3/8	1.88	2.13	.250
V201F-8-8	1/2	1.98	2.30	.203




Ground Plug Shutoff V203F

Flare to Flare

Temperature Range: +32° to +125° F

PART NO.	TUBE SIZE	L	M	FLOW DIA. D
V203F-6-6	3/8	2.26	2.14	.220
V203F-8-8	1/2	2.26	2.42	.281




Ground Plug Shutoff V204F

Flare to Male Pipe

Temperature Range: +32° to +125° F

PART NO.	TUBE SIZE	PIPE THREAD	L	M	FLOW DIA. D
V204F-4-2	1/4	1/8	1.88	2.08	.180
V204F-6-4	3/8	1/4	2.27	2.05	.218





Ground Plug Shutoff V303C / V303CA

Compression to Compression

Temperature Range: +32° to +125° F

PART NO.	TUBE SIZE	L	M	FLOW DIA. D
V303C-4-4	1/4	1.88	2.33	.188
V303CA-4-4	1/4	1.90	1.75	.188
V303C-6-6	3/8	2.26	2.45	.218
V303CA-6-6	3/8	1.76	1.60	.218





Ground Plug Shutoff V304C / V304CA

Compression to Male Pipe

Temperature Range: +32° to +125° F

PART NO.	TUBE SIZE	PIPE THREAD	L	M	FLOW DIA. D
V304C-4-2	1/4	1/8	1.90	2.29	.188
V304CA-4-2	1/4	1/8	1.88	2.00	.188
V304C-4-4	1/4	1/4	1.90	2.15	.188
V304CA-4-4	1/4	1/4	1.86	2.08	.188
V304C-6-4	3/8	1/4	1.83	2.24	.218
V304CA-6-4	3/8	1/4	1.83	2.11	.218




Ground Plug Shutoff V401P

Male Pipe to Male Pipe

Temperature Range: +32° to +125° F

PART NO.	PIPE THREAD	L	M	FLOW DIA. D
V401P-2-2	1/8	1.90	2.25	.188
V401P-4-4	1/4	1.90	1.98	.188



J