

# PAGE-flex™ Hose Specifications

## SHVW - (Natural) & SHVB - (Conductive)

Part Number		Order ID	Hose OD	Working Pressure	Minimum Burst Pressure	Vacuum Rating	Minimum Bend Radius	Weight
Natural	Conductive	Inch (MM)	Inch (MM)	PSI @ 72°F (Bars @ 22°C)	PSI @ 72°F (Bars @ 22°C)	In. Hg. @ 72°F (Kg/Sq.CM @ 22°C)	Inch (MM)	Lbs./Ft. (Kgs/M)
08-SHVW-FS	08-SHVB-FS	0.500 (12.7)	0.72 (18.3)	500 (34.5)	2000 (138.0)	29.9 (1.0)	2.00 (50.8)	0.173 (0.257)
12-SHVW-FS	12-SHVB-FS	0.750 (19.0)	1.040 (26.4)	425 (29.3)	1700 (117.2)	29.9 (1.0)	2.75 (69.8)	0.330 (0.491)
16-SHVW-FS	16-SHVB-FS	1.000 (25.4)	1.250 (31.7)	350 (24.0)	1400 (96.5)	29.9 (1.0)	4.00 (101.6)	0.368 (0.548)
20-SHVW-FS	20-SHVB-FS	1.250 (31.7)	1.660 (42.2)	325 (22.4)	1300 (89.6)	29.9 (1.0)	5.50 (139.7)	0.560 (0.833)
24-SHVW-FS	24-SHVB-FS	1.500 (38.1)	1.920 (48.8)	300 (20.7)	1200 (82.7)	29.9 (1.0)	7.00 (177.8)	0.641 (0.954)
32-SHVW-FS	32-SHVB-FS	2.000 (50.8)	2.490 (63.2)	250 (17.2)	1000 (69.0)	29.9 (1.0)	8.50 (215.9)	0.835 (1.243)
40-SHVW-FS	40-SHVB-FS	2.500 (63.5)	3.250 (82.5)	200 (13.8)	800 (55.2)	29.9 (1.0)	12.00 (304.8)	1.520 (2.262)
48-SHVW-FS	48-SHVB-FS	3.000 (76.2)	3.800 (96.5)	175 (12.0)	700 (48.2)	29.9 (1.0)	14.00 (355.6)	1.820 (2.709)
64-SHVW-FS	64-SHVB-FS	4.000 (101.6)	4.760 (120.6)	150 (10.3)	600 (41.4)	29.9 (1.0)	16.00 (406.4)	2.100 (3.125)

**NOTE:** Temperature Range: -100°F to +500°F (-73°C to +260°C)

### TYPICAL APPLICATIONS

- Food
- Beverage
- Pharm / Bio Pharm
- Semicon
- High Purity Water
- Cosmetics / Soaps
- Chemical Processing
- General Industrial



PAGE-flex™ allows for increased live-length of the hose, providing a more flexible hose in shorter hose assemblies.

All ratings based on 72°F (22°C) - All dimensions nominal - Working pressures and vacuum ratings may vary depending upon end connections and process and temperature parameters.

Smoothbore PTFE Hose

Convuluted PTFE Hose

Flare Seal Hose

Silicone Hose

Specialty Hoses

Fittings

Accessories

Technical Help

Warranty



Parker Hannifin, Parflex Division