

HEATER & COOLANT HOSES

6723 X-treme Heavy-Wall Heater Hose

Extruded heavy-duty heater hose that meets or exceeds SAEJ20R3 Class A specifications. This product is utilized as standard equipment on trucks, cars and buses. Since this silicone hose is extruded it can be offered in long lengths, which saves money by reducing scrap. These hoses are resistant to coolant solutions, cracking, ozone, cold leaks, peeling and aging.

TUBE COLOR: Brick Red

REINFORCEMENT: High-temperature-resistant plies

COVER: Blue

BRANDING: PARKER SILICONE SERIES 6723 -65° to +350°F (DATE CODE) MADE IN MEXICO

TEMP. RANGE: -65° to +350°F

APPLICATIONS: Heater hose for cars, trucks and buses

SPECIFICATIONS: SAEJ20R3, SAEJ2387

MAX. WORKING PRESSURE: 1/3 of the Burst Pressure



| PART NUMBER | SIZE INCH | INSIDE DIAMETER | | OUTSIDE DIAMETER | | LENGTH FT | BURST PRESSURE PSI | WEIGHT LBS/100FT | BEND RADIUS | |
|--------------|--------------|-----------------|----|------------------|----|--------------|--------------------------|---------------------|-------------|-----|
| | | INCH | MM | INCH | MM | | | | INCH | MM |
| 6723-0250500 | 1/4 | 0.250 | 6 | 0.640 | 16 | 500 | 250 | 11.37 | 0.4 | 10 |
| 6723-0375500 | 3/8 | 0.375 | 10 | 0.765 | 19 | 500 | 250 | 15.09 | 0.6 | 16 |
| 6723-0500025 | 1/2 | 0.500 | 13 | 0.890 | 23 | 25 | 250 | 18.76 | 1.3 | 32 |
| 6723-0500050 | 1/2 | 0.500 | 13 | 0.890 | 23 | 50 | 250 | 18.76 | 1.3 | 32 |
| 6723-0500100 | 1/2 | 0.500 | 13 | 0.890 | 23 | 100 | 250 | 18.76 | 1.3 | 32 |
| 6723-0500500 | 1/2 | 0.500 | 13 | 0.890 | 23 | 500 | 250 | 18.76 | 1.3 | 32 |
| 6723-0625025 | 5/8 | 0.625 | 16 | 1.015 | 26 | 25 | 250 | 26.64 | 1.5 | 38 |
| 6723-0625050 | 5/8 | 0.625 | 16 | 1.015 | 26 | 50 | 250 | 26.64 | 1.5 | 38 |
| 6723-0625100 | 5/8 | 0.625 | 16 | 1.015 | 26 | 100 | 250 | 26.64 | 1.5 | 38 |
| 6723-0750025 | 3/4 | 0.750 | 19 | 1.140 | 29 | 25 | 200 | 28.73 | 2.4 | 60 |
| 6723-0750050 | 3/4 | 0.750 | 19 | 1.140 | 29 | 50 | 200 | 28.73 | 2.4 | 60 |
| 6723-0750100 | 3/4 | 0.750 | 19 | 1.140 | 29 | 100 | 200 | 28.73 | 2.4 | 60 |
| 6723-1000025 | 1 | 1.000 | 25 | 1.390 | 35 | 25 | 175 | 38.85 | 4.0 | 102 |
| 6723-1000050 | 1 | 1.000 | 25 | 1.390 | 35 | 50 | 175 | 38.85 | 4.0 | 102 |
| 6723-1000100 | 1 | 1.000 | 25 | 1.390 | 35 | 100 | 175 | 38.85 | 4.0 | 102 |