

## HEATER & COOLANT HOSES

# 6620 X-treme Plus SW Series

A softwall coolant/heater hose that is mandrel made in continuous lengths up to 130 feet, which is the longest length available in the industry. This hose is resistant to coolant solutions, cracking, ozone, cold leaks, peeling and aging. This X-treme Plus product is made for the connection between the radiator and any engine on heavy-duty equipment, buses, trucks, etc. Meets or exceeds SAEJ20R1 specifications.

**TUBE COLOR:** Black

**REINFORCEMENT:** High-temperature-resistant plies

**COVER COLOR:** Red

**BRANDING:** PARKER SILICONE SERIES 6620 -76° to +392°F (DATE CODE) MADE IN ITALY

**TEMP. RANGE:** -76° to +392°F

**APPLICATIONS:** Coolant and heater lines

**SPECIFICATIONS:** Meets or exceeds performance criteria of SAEJ20R1 Class A, ISO 1307-1997, TMC RP303B

**MAX. WORKING PRESSURE:** 1/3 of the Burst Pressure



PART NUMBER	SIZE INCH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH FT	BURST PRESSURE PSI	WEIGHT LBS/100FT
		INCH	MM	INCH	MM			
6620-0375130	3/8	0.394	10	0.709	18	130	900	12
6620-0500130	1/2	0.512	13	0.827	21	130	855	13
6620-0625130	5/8	0.630	16	0.945	24	130	750	15
6620-0688130	11/16	0.709	18	1.102	28	130	600	25
6620-0750130	3/4	0.748	19	1.142	29	130	600	26
6620-0813130	13/16	0.787	20	1.181	30	130	570	27
6620-0875130	7/8	0.866	22	1.260	32	130	525	29
6620-1000025	1	0.984	25	1.378	35	25	480	33
6620-1000130	1	0.984	25	1.378	35	130	480	33
6620-1188130	1-3/16	1.181	30	1.575	40	130	405	38
6620-1250130	1-1/4	1.260	32	1.654	42	130	390	40
6620-1375025	1-3/8	1.378	35	1.772	45	25	360	44
6620-1375130	1-3/8	1.378	35	1.772	45	130	360	44
6620-1500130	1-1/2	1.496	38	1.890	48	130	330	47
6620-1563130	1-9/16	1.575	40	1.969	50	130	315	49
6620-1625025	1-5/8	1.654	42	2.047	52	25	300	52
6620-1625130	1-5/8	1.654	42	2.047	52	130	300	52
6620-1750130	1-3/4	1.772	45	2.165	55	130	285	54
6620-1875130	1 7/8	1.890	48	2.283	58	130	270	58
6620-2000025	2	2.008	51	2.402	61	25	255	61
6620-2000130	2	2.008	51	2.402	61	130	255	61
6620-2188130	2-3/16	2.165	55	2.559	65	130	240	68
6620-2250130	2-1/4	2.283	58	2.677	68	130	225	70
6620-2370130	2-3/8	2.362	60	2.756	70	130	225	71
6620-2500130	2-1/2	2.500	64	2.894	73.5	130	210	77
6620-2563130	2-5/8	2.559	65	2.953	75	130	210	79
6620-2750130	2-3/4	2.756	70	3.150	80	130	195	84
6620-3000130	3	2.992	76	3.386	86	130	180	92
6620-3125130	3-1/8	3.150	80	3.543	90	130	165	93
6620-3375130	3-3/8	3.346	85	3.740	95	130	150	98
6620-3563130	3-9/16	3.543	90	3.937	100	130	150	104
6620-4000130	4	4.016	102	4.409	112	130	150	117