


## HOW TO ORDER

Part No.	S	V	H	C	4-4	F	OPTIONS			
<b>Material</b> No letter Steel, plated <b>A</b> Aluminum clear anodized <b>B</b> Brass <b>S</b> Stainless Steel 316	<b>Body Type</b> <b>V</b> Valve <b>P</b> Plain (without valve)	<b>Series</b> <b>H</b> <b>PH<sup>1</sup></b> <b>IH<sup>2</sup></b>	<b>Coupling Half</b> <b>C</b> Coupler <b>N</b> Nipple	<b>Coupling Size</b> 4 = 1/4" 6 = 3/8" 8 = 1/2" 12 = 3/4" 16 = 1" 20 = 1-1/4" 24 = 1-1/2" 32 = 2" 40 = 2-1/2" 48 = 3" 64 = 4"	<b>End Fitting Size</b> 2 = 1/8" 4 = 1/4" 6 = 3/8" 8 = 1/2" 10 = 5/8" 12 = 3/4" 16 = 1" 20 = 1-1/4" 24 = 1-1/2" 32 = 2" 40 = 2-1/2" 48 = 3" 64 = 4"	<b>End Fitting Type</b> (see page 5) <b>M</b> Male NPT <b>F</b> Female NPTF <sup>3</sup> <b>EF</b> Female SAE <b>EM</b> Male SAE 37° Flare <b>EB</b> Bulkhead SAE <b>RP</b> Female British Parallel BS2779 <b>49</b> MS33649 Female <b>56</b> MS33656 37° Male Flare <b>57</b> MS33657 Bulkhead <b>14</b> MS33514 Male <b>15</b> MS33515 Bulkhead	<b>Optional Seal</b> <b>-9</b> O-ring and Teflon back- up ring for steel & stainless steel units only. For others consult factory.	<b>Seal Material</b> No letter for Buna N (Code A) -40° to 200°F -40° to 93°C <b>JF</b> Military variation of Buna N for hydrocarbon fuels -65° to 160°F -54° to 71°C <b>M</b> Military variation of Buna N for MIL-H-5606 fluids -65° to 275°F -54° to 135°C <b>V</b> Viton® (DuPont) -20° to 375°F -29° to 190°C <b>E</b> Ethylene pro- pylene rubber -65° to 300°F -54° to 149°C	<b>Sleeve Lock</b> <b>SL</b> Aids in preventing accidental disconnection. To disconnect, align the pin in the body with the slot in the sleeve.	

<sup>1</sup> PH Valve option recommended on one side, not both. Available in steel only.

<sup>2</sup> IH available in steel only.

<sup>3</sup> For sizes up to 1" NPTF threads in steel.  
 For sizes up to 1" NPSF threads in stainless steel.  
 For sizes over 1" NPT threads.



## SPARE PARTS

Snap-tite Quick Disconnect Couplings are designed for long, trouble-free life. Upon occasion, certain parts may get damaged and need to be ordered.

**Valve Kits** (Includes valve, valve spring and stop. Valve seal is included in sizes 3/8" thru 1" in steel, brass and aluminum only).

Part Number – Use the base part number followed by SPK     **Example:** VHC4-SPK  
 VIHC6-SPK

**Valve Seals** (1/4" valve seal is staked in the coupler and nipple bodies in all materials and is not considered field repairable. 3/8" and above are available for repair).

Part Number – "H (size)-55"     **Example:** H6-55  
 H8-55V

**Nipple Seals** (U packer for "H" couplers; O-ring and back up ring for "-9" option).

Part Number – "H (size)-56"     **Example:** H4-56  
 H6-56-9

For other available spare parts, consult factory.