

★ Snap-tite ——— Agricultural Couplings

Featuring...Snap-tite quality and experience in the most economical package with a range that varies from the simplest to the most sophisticated couplings.

61DC8-8 Coupler



This is a dependable and economical 1/2" ISO 7241-1 Series A coupler which has a dual-acting sleeve. The sleeve, which has snap ring grooves that allow it to fit most industry standard brackets, permits one-hand connect or disconnect operation. This coupler is not designed for connection under pressure.

The coupler is made from high strength steel with zinc yellow dichromate plating for maximum corrosion resistance. The coupler is available with the following end fittings:

61DC8-8F	1/2" Female NPSF
61DC8-8RP	1/2" Female BSP
61DC8-8EF	1/2" Female SAE
Metric threads available on request	

When used in a bracket, body movement during connection or disconnection requires the use of a flexible connection. A plastic plug (61PDP-8) is available to prevent contamination from dust and dirt.

68C8-8 Coupler

This is a reliable, economical and versatile 1/2" ISO 7241-1 Series A coupler with a dual-acting sleeve and connect/disconnect under pressure capability. The sleeve, which has snap ring grooves that allow it to fit all industry standard brackets, permits one-hand connect or disconnect operation.

A stackable bracket (68B-8) is available. This durable bracket holds two couplers and is equipped with a drain line to carry away the small spillage that occurs on disconnection. The bracket is designed to be stacked allowing compact installation of many couplers. When stacked, the drain lines interconnect thus requiring only one drain connection. The brackets can be equipped with automatic dust caps (68BC-8) which prevent damage and contamination from dust and dirt. This coupler allows connection with pressure in either or both the tip (nipple) and coupler. After connecting pressurized components, operation of the vehicle's hydraulic control valve will open the coupling valves allowing fluid to flow. The coupler is available with the following fittings:

68C8-8F	1/2" Female NPSF
68C8-8RP	1/2" Female BSP
68C8-8EF	1/2" Female SAE
Metric threads available on request	

When used in a bracket, body movement during connection or disconnection requires the use of a flexible connection.



Stackable Brackets 68B-8

This durable bracket set holds two 68C8-8 couplers. Optional automatic dust caps 68BC-8 for use with the bracket set are shown below.



Dust Plug for 61DC8-8 & 68C8-8	61PDP-8
Dust Cap for 63N8-8	PDC-12