






AIR/MULTIPURPOSE

BLACK MAX® M.R.O.

This premium quality, non-conductive hose is high in oil resistance throughout. Its fuel line quality will convey oil, fuel oil, diesel, kerosene and other petroleum derived products. Its tough, black cover resists oils and solvents as well as weathering, ozone and abrasion. Hose is tested to have a minimum of 1,000,000 ohms per inch resistance when tested with a 1,000 volt D.C. meggar.

Note: Not recommended for a variety of unleaded gasoline.



Resistance:	   
Branding:	Thermoid Versicon/Black Max MRO Non-conductive Size WP Made In USA

Cover Color: Black
Oil Resistance: High
Construction: Non-conductive
Tube: NBR, RMA Class A
Cover: NBR/PVC RMA Class A
Reinforcement: Spiral polyester yarn
Temperature Range: -20°F to +180°F
 -29°C to +82°C
Packaging: Reels


Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
00447604400▲	1/4	6.35	0.63	15.88	4	300	2.07	1.50	38.10	0.16	0.24
00447606400▲	3/8	9.53	0.72	18.26	4	300	2.07	2.25	57.15	0.18	0.27
00447608400▲	1/2	12.70	0.91	23.02	4	300	2.07	3.00	76.20	0.25	0.37
00447612400▲	3/4	19.05	0.88	22.23	4	300	2.07	4.50	114.30	0.42	0.62
00447616400▲	1	25.40	1.43	36.20	4	300	2.07	7.00	177.80	0.60	0.89




▲ = Make To Order (MTO)

GOLDENAIR®

Goldenair is an excellent general purpose hose for air, petroleum products and nitrogen service. Designed for the harsh conditions found in steel mills, shipyards, foundries, auto plants and construction sites, Goldenair resists weathering, ozone and abrasion. Goldenair provides a constant working pressure to 350 psi in 3/4" size and is kink resistant. This premium quality hose is non-conductive. It has a tough, durable cover that resists oils and other solvents. Its 4-spiral polyester yarn reinforcement provides added strength and flexibility even in the most extreme conditions.

Note: Not recommended for a variety of unleaded gasoline.



Resistance:	  
Branding:	Thermoid Versicon/Goldenair Non-conductive Size PSI WP Made In USA (For Nitrogen Use)

Cover Color: Yellow
Oil Resistance: High
Construction: Non-conductive
Tube: NBR, RMA Class A
Cover: NBR/PVC RMA Class A
Reinforcement: Spiral polyester yarn
Temperature Range: -20°F to +180°F
 -29°C to +82°C
Packaging: Reels

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
00447312600	3/4	19.05	1.16	29.37	4	350	2.41	4.50	114.30	0.38	0.57
00447316400	1	25.40	1.43	36.20	4	300	2.07	7.00	177.80	0.61	0.91