

## AIR POWER™ JACKHAMMER

Thermoid Air Power Jackhammer is a hose as tough as its name. A rugged 4-spiral construction in either 200 or 300 psi, Air Power can tackle the job that only a jackhammer can dish out. The EPDM tube and cover handles heat, ozone and weather cracking better than other compounds. The OEM factory assemblies have domestic or foreign manufactured couplings with either 1 or 2 bands per end. Durability is built-in and this hose is ready for hard work.



**Resistance:**



**Branding:**

Thermoid Air Power 3/4"  
Made In USA

- Cover Color:** Red (also available in yellow)
- Oil Resistance:** Limited
- Construction:**
  - Tube:** EPDM
  - Cover:** EPDM
  - Reinforcement:** Spiral polyester yarn
- Temperature Range:** -40°F to +212°F  
-40°C to +100°C
- Packaging:** 50 ft. lengths – 5 per carton

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
00114581451	3/4	19.05	1.16	29.37	4	200	1.38	4.50	114.30	0.38	0.57
00114581452	3/4	19.05	1.16	29.37	4	200	1.38	4.50	114.30	0.38	0.57
00114580407	3/4	19.05	1.16	29.37	4	300	2.07	4.50	114.30	0.41	0.61

## RED AIR TOOL COUPLED

This tough, versatile factory coupled air hose is specifically designed to stand up to the harsh working conditions found on most project construction sites and industrial environments. Available in either 200 or 300 psi working pressures, this air hose features an EPDM tube and cover with a 4-spiral polyester reinforcement that provides excellent flexibility. This hose will resist kinking, abrasions, heat and ozone. This hose is cut to lengths and is coupled with Male x Male fittings with 1/4" or 3/8" threads per customer requirements.



**Resistance:**



**Branding:**

Thermoid Air Power Size WP 4 SP  
Made In USA

- Cover Color:** Red
- Oil Resistance:** Limited
- Construction:**
  - Tube:** EPDM
  - Cover:** EPDM
  - Reinforcement:** Spiral polyester yarn
- Temperature Range:** -40°F to +212°F  
-40°C to +100°C
- Packaging:** See Chart

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Lengths	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(feet)	(meters)
00114586454▲	1/4	6.35	0.59	15.08	4	200	1.38	50	15.25
00114587454▲	1/4	6.35	0.63	15.88	4	300	2.07	50	15.25
00114586624▲	3/8	9.53	0.72	18.26	4	200	1.38	25	7.62
00114587624▲	3/8	9.53	0.72	18.26	4	300	2.07	25	7.62
00114587628▲	3/8	9.53	0.72	18.26	4	300	2.07	25	7.62
00114586654▲	3/8	9.53	0.72	18.26	4	200	1.38	50	15.25
00114586658▲	3/8	9.53	0.72	18.26	4	200	1.38	50	15.25
00114587654	3/8	9.53	0.72	18.26	4	300	2.07	50	15.25
00114587658▲	3/8	9.53	0.72	18.26	4	300	2.07	50	15.25

▲ = Make To Order (MTO)