


1158 SOFTWALL AROMATIC FUEL SAE 30R2 TYPE 2

This hose is an excellent multipurpose hose which is designed for use in fuel transfer applications, such as, filler neck, where aromatic fuel resistance is required. This hose features a neoprene cover that is oil, heat, and ozone resistant.



- Cover Color:** Black
- Oil Resistance:** High
- Construction:**
 - Tube:** NBR
 - Cover:** CR
 - Reinforcement:** Tire cord
- Temperature Range:** -40°F to +212°F
-40°C to +100°C
- Packaging:** Make to Order (MTO)
Contact Salisbury for details
6 ft., 12 ft and 60 ft. lengths available
1/2" and 5/8" I.D. – 25 ft. maximum
Other lengths – 5% cutting charge

Product Number 6 Feet	Product Number 12 Feet	Product Number 60 Feet	Nominal I.D. (inches) (mm)	Nominal O.D. (inches) (mm)	Plies	Working Pressure (psi) (Mpa)	Min. Bend Radius (inches) (mm)	Weight (lb/ft) (Kg/m)
16115805006▲	16115805012▲	16115805025▲	1/2 12.70	1.00 25.40	2	175 1.21	n/a n/a	0.36 0.54
16115806206▲	16115806212▲	16115806225▲	5/8 15.88	1.13 28.58	2	125 0.86	n/a n/a	0.41 0.61
16115807506▲	16115807512▲	16115807560▲	3/4 19.05	1.25 31.75	2	125 0.86	n/a n/a	0.46 0.68
16115808706	16115808712	16115808760	7/8 22.23	1.38 34.93	2	125 0.86	n/a n/a	0.52 0.77
16115810006	16115810012	16115810060	1 25.40	1.50 38.10	2	125 0.86	n/a n/a	0.59 0.88
16115811206▲	16115811212▲	16115811260▲	1-1/8 28.58	1.63 41.28	2	100 0.69	n/a n/a	0.62 0.92
16115812506	16115812512	16115812560	1-1/4 31.75	1.75 44.45	2	100 0.69	n/a n/a	0.68 1.01
16115813706▲	16115813712▲	16115813760▲	1-3/8 34.93	1.88 47.63	2	100 0.69	n/a n/a	0.73 1.09
16115815006	16115815012	16115815060	1-1/2 38.10	2.00 50.80	2	100 0.69	n/a n/a	0.79 1.18
16115816206▲	16115816212	16115816260	1-5/8 41.28	2.13 53.98	2	62 0.43	n/a n/a	0.84 1.25
16115817506	16115817512	16115817560	1-3/4 44.45	2.25 57.15	2	62 0.43	n/a n/a	0.90 1.34
16115818706	16115818712	16115818760	1-7/8 47.63	2.38 60.33	2	62 0.43	n/a n/a	0.95 1.41
16115820006	16115820012	16115820060	2 50.80	2.50 63.50	2	62 0.43	n/a n/a	1.00 1.49
16115821206▲	16115821212▲	16115821260▲	2-1/8 53.98	2.63 66.68	2	62 0.43	n/a n/a	1.06 1.58
16115822506	16115822512	16115822560	2-1/4 57.15	2.75 69.85	2	50 0.34	n/a n/a	1.11 1.65
16115823706	16115823712	16115823760	2-3/8 60.33	2.88 73.03	2	50 0.34	n/a n/a	1.17 1.74
16115825006	16115825012	16115825060	2-1/2 63.50	3.00 76.20	2	50 0.34	n/a n/a	1.22 1.82
16115826206▲	16115826212▲	16115826260▲	2-5/8 66.68	3.13 79.38	2	50 0.34	n/a n/a	1.27 1.89
16115827506▲	16115827512▲	16115827560▲	2-3/4 69.85	3.25 82.55	2	50 0.34	n/a n/a	1.33 1.98
16115828706	16115828712	16115828760	2-7/8 73.03	3.38 85.73	2	50 0.34	n/a n/a	1.39 2.07
16115830006	16115830012	16115830060	3 76.20	3.50 88.90	2	50 0.34	n/a n/a	1.44 2.14
16115831206▲	16115831212▲	16115831260▲	3-1/8 79.38	3.63 92.08	2	37 0.25	n/a n/a	1.49 2.22
16115832506▲	16115832512▲	16115832560▲	3-1/4 82.55	3.75 95.25	2	37 0.25	n/a n/a	1.55 2.31
16115835006	16115835012	16115835060	3-1/2 88.90	4.00 101.60	2	37 0.25	n/a n/a	1.66 2.47
16115837506▲	16115837512▲	16115837560▲	3-3/4 95.25	4.25 107.95	2	37 0.25	n/a n/a	1.76 2.62
16115840006▲	16115840012▲	16115840060▲	4 101.60	4.50 114.30	2	37 0.25	n/a n/a	1.87 2.78
16115842506▲	16115842512▲	16115842560▲	4-1/4 107.95	4.75 120.65	2	25 0.17	n/a n/a	1.98 2.95
16115845006▲	16115845012▲	16115845060▲	4-1/2 114.30	5.00 127.00	2	25 0.17	n/a n/a	2.09 3.11
16115850006▲	16115850012▲	16115850060▲	5 127.00	5.50 139.70	2	12 0.08	n/a n/a	2.31 3.44
16115855006▲	16115855012▲	16115855060▲	5-1/2 139.70	6.00 152.40	2	12 0.08	n/a n/a	2.52 3.75
16115860006▲	16115860012▲	16115860060▲	6 152.40	6.50 165.10	2	10 0.07	n/a n/a	2.74 4.08

▲ = Make To Order (MTO)
n/a = Not Applicable

AUTOMOTIVE/MARINE COOLANT Automotive – Air Brake, Fuel, Heater & Coolant