

Hose information is subject to change. For full details, visit our website or contact Customer Service.



HI-VAC™ WHIP

Hi-Vac Whip hose's primary application is the "breakaway" connection from the pump to the primary hose assembly. This hose is used in conjunction with the Hi-Vac™ Co-Ax® hose assembly.

Note: Do not use reusable couplings with this product.

Coupling: Chrome plated brass metric thread (M34)



Resistance:
 
Branding:
Manufacturer's Identification, Product name UL Listed

- Cover Color:** Black
- Construction:**
 - Inner Hose Tube:** NBR/PVC
 - Outer Hose Tube:** NBR/PVC, RMA Class A
 - Inner Hose Cover:** NBR/PVC
 - Outer Hose Cover:** CSM, RMA Class B
 - Reinforcement:** Braided steel wire
- Temperature Range:** -40°F to +180°F
-40°C to +82°C
- Packaging:** Depends on the order quantity

Hi-Vac Whip Product Number	Nominal I.D.		Length	
	(inches)	(mm)	(inches)	(mm)
22471111031	3/4	19.05	10	254.00
22471111011	3/4	19.05	12	304.80
22473222021	7/8	22.23	10	254.00
22473222011	7/8	22.23	12	304.80

TRANSPORTER® EBONITE™ CORRUGATED TANK TRUCK

The Transporter Ebonite Corrugated Tank Truck hose is recommended for hydrocarbons with aromatic content up to 55% maximum, fats, greases, animal oil, vegetable oil, hydraulic fluid and a wide range of chemicals. This hose features a flat corrugated NBR/PVC cover which is ideal for those applications where flexibility is an issue. The reinforcement of two plies of polyester cord with a dual wire helix enables this hose to be rated at **full vacuum**. Also, this construction allows each size to have a constant working pressure of 150 psi.



Resistance:
   
Branding:
Thermoid HBD Industries Inc. Ebonite™ 150 PSI WP Made In USA

- Cover Color:** Black
- Oil Resistance:** High
- Construction:**
 - Tube:** NBR, RMA Class A
 - Cover:** NBR/PVC corrugated, RMA Class B
 - Reinforcement:** 2 plies of polyester cord with a dual wire helix(es) between plies
- Temperature Range:** -30°F to +200°F
-34°C to +93°C
- Packaging:** 100 ft. maximum

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
17813045002▲	1	25.40	1.53	38.89	2	150	1.03	2.00	50.80	0.60	0.89
17813046002▲	1-1/4	31.75	1.78	45.24	2	150	1.03	2.50	63.50	0.70	1.04
17813047002	1-1/2	38.10	2.06	52.39	2	150	1.03	3.00	76.20	0.90	1.34
17813048002	2	50.80	2.56	65.09	2	150	1.03	4.50	114.30	1.20	1.79
17813050002	3	76.20	3.56	90.49	2	150	1.03	6.00	152.40	1.80	2.68
17813055002	4	101.60	4.66	118.27	2	150	1.03	8.00	203.20	2.70	4.02

▲ = Make To Order (MTO)