

Hose information is subject to change. For full details, visit our website or contact Customer Service.

BLAST-FLEX™ SAND BLAST

Blast-Flex Sand Blast hose has been engineered to handle the cleaning, cutting or finishing stone, glass and metal surfaces. This hose will conduct sand, steel, shot or other sharp abrasives at high velocity. Blast-Flex features a 1/4" thick, SBR/NR tube that resists abrasion in sandblast service. The static-conducting properties of this hose prevent the build-up of electrical charges. The black SBR/EPDM cover resists abrasions, cuts and snags. The reinforcement of four spiral plies of heavy fabric resists collapsing and kinking when the hose is bent. The larger sizes of Blast-Flex are reinforced with heavier weight fabric for added strength.



Resistance:
Branding:
HBD Industries Sand Blast Made In USA

Cover Color: Black
Oil Resistance: Limited
Construction:
Tube: SBR/NR, 1/4" thick
Cover: SBR/EPDM
Reinforcement: Multiple plies of heavy fabric
Temperature Range: -40°F to +160°F
 -40°C to +71°C
Packaging: 50 ft. maximum, all lengths
 Minimum order is 500 ft. per size

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
17776010502	3/4	19.05	1.50	38.10	4	150	1.03	n/a	n/a	0.70	1.04
17776015502	1	25.40	1.88	47.63	4	150	1.03	n/a	n/a	1.00	1.49
17776025502▲	1-1/4	31.75	2.16	54.77	4	150	1.03	n/a	n/a	1.20	1.79
17776035502	1-1/2	38.10	2.38	60.33	4	150	1.03	n/a	n/a	1.30	1.93
17776040502▲	2	50.80	2.88	73.03	4	100	0.69	n/a	n/a	1.70	2.53
17776045502▲	2-1/2	63.50	3.41	86.52	4	100	0.69	n/a	n/a	2.00	2.98
17776050502	3	76.20	3.91	99.22	4	100	0.69	n/a	n/a	2.40	3.57

▲ = Make To Order (MTO)
 n/a = Not Applicable

WRAPPED SAND BLAST

Wrapped Sand Blast hose has been engineered to handle the cleaning, cutting or finishing stone, glass and metal surfaces. This hose will conduct sand, steel, shot or other sharp abrasives at high velocity. Wrapped Sand Blast features a 1/4" thick, SBR/NR tube that resists abrasion in sandblast service. The static-conducting properties of this hose prevent the build-up of electrical charges. The black SBR/EPDM cover resists abrasions, cuts and snags. The reinforcement of four spiral plies of heavy fabric resists collapsing and kinking when the hose is bent. The larger sizes of Wrapped Sand Blast are reinforced with heavier weight fabric for added strength.



Resistance:
Branding:
Thermoid HBD Industries Sand Blast Hose WP Made In USA

Cover Color: Black
Oil Resistance: Limited
Construction:
Tube: SBR/NR, 1/4" thick
Cover: SBR/EPDM
Reinforcement: Multiple plies of heavy fabric
Packaging: 50 ft. maximum, all lengths
 Minimum order is 500 ft. per size

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
21224407502	1/2	12.70	1.19	30.16	4	150	1.03	n/a	n/a	0.50	0.74
21224400502	3/4	19.05	1.50	38.10	4	150	1.03	n/a	n/a	0.70	1.04
21224401502	1	25.40	1.88	47.63	4	150	1.03	n/a	n/a	1.00	1.49
21224402502	1-1/4	31.75	2.16	54.77	4	150	1.03	n/a	n/a	1.20	1.79
21224403502▲	1-1/2	38.10	2.38	60.33	4	150	1.03	n/a	n/a	1.30	1.93
21224404502▲	2	50.80	2.88	73.03	4	100	0.69	n/a	n/a	1.70	2.53

▲ = Make To Order (MTO)
 n/a = Not Applicable