

Hose information is subject to change. For full details, visit our website or contact Customer Service.

PILE DRIVER STEAM

Pile Driver Steam hose is recommended for those applications where there is saturated steam service to +388°F on driving systems. This hose features an EPDM tube that is specifically compounded to resist permeation and prevent premature failure. The multiple plies of tire cord with plated steel cable reinforcement enable this hose to maintain a working pressure of 200 psi regardless which size hose you are using.

▲ See Steam Hose Warning, pages 8-9.



- Cover Color:** Black
- Oil Resistance:** Limited
- Construction:**
 - Tube:** EPDM, also available in CR for oil resistance
 - Cover:** EPDM, also available in CR for oil resistance
 - Reinforcement:** Multiple plies of tire cord and plated steel cable
- Temperature Range:** Saturated steam service to +388°F (+198°C)
- Packaging:** 100 ft. maximum
Minimum order 300 ft.

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
34854634002▲	2	50.80	3.13	79.38	4	200	1.38	20.00	508.00	4.10	6.10
34854636002▲	2-1/2	63.50	3.38	85.73	4	200	1.38	25.00	635.00	5.40	8.04
34854638002▲	3	76.20	4.50	114.30	4	200	1.38	30.00	762.00	6.40	9.52
34854640002▲	4	101.60	5.63	142.88	4	200	1.38	40.00	1016.00	9.30	13.84
34854642002▲	6	152.40	7.81	198.44	6	200	1.38	60.00	1524.00	18.60	27.68

▲ = Make To Order (MTO)