

BLACK HEAVY-DUTY WATER – Coupled

Suitable for water pressure up to 150 psi. Coupled with Male x Female octagonal nut spun brass garden hose couplings with brass ferrules.



Resistance:
Branding:
None

- Cover Color:** Black
- Oil Resistance:** Limited
- Construction:**
 - Tube:** EPDM
 - Cover:** EPDM
 - Reinforcement:** Spiral polyester yarn
- Temperature Range:** -40°F to +180°F
-40°C to +82°C
- Packaging:** 50 ft. lengths – 5 per carton

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
00512281249▲	5/8	15.88	0.94	23.81	2	150	1.03	3.75	95.25	0.23	0.34
00512281255▲	3/4	19.05	1.06	26.98	2	150	1.03	4.50	114.30	0.27	0.40

▲ = Make To Order (MTO)

BLACK HEAVY-DUTY CONTRACTORS WATER – Coupled

Contractors Water hose has a 150 psi working pressure constant through all sizes. This hose is coupled (Male x Female) with crush resistant octagonal nut rod brass garden hose couplings and brass ferrules. It features an EPDM tube and cover with multi-spiral reinforcement that is heat, ozone and sunlight resistant. Designed for professional grade contractor use, this heavy-duty water hose is engineered to stay flexible even in extreme temperatures. This hose is virtually kink-proof.



Resistance:
Branding:
None

- Cover Color:** Black
- Oil Resistance:** Limited
- Construction:**
 - Tube:** EPDM
 - Cover:** EPDM
 - Reinforcement:** Spiral polyester yarn
- Temperature Range:** -40°F to +180°F
-40°C to +82°C
- Packaging:** 50 ft. lengths – 5 per carton

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
00512180769	5/8	15.88	0.94	23.81	2	150	1.03	3.75	95.25	0.23	0.34
00512180771	3/4	19.05	1.06	26.98	2	150	1.03	4.50	114.30	0.27	0.40