

SS141 OXYGEN CHARGING HOSE

- Specially designed for steel mill lancing and scarfing applications.
- Premium grade Neoprene cover offers protection against sparks and abrasion.

Tube: Extruded Neoprene.
Reinforcement: Textile.
Cover: Green Neoprene.
Temperature: -40° to +200°F.

I.D.	O.D.	REINFORCEMENT	WORKING PRESSURE PSI	WEIGHT LB/FT
1"	1 ¹¹ / ₁₆ "	2 plies	500	.84
1 ¹ / ₄ "	1 ¹⁵ / ₁₆ "	2 plies	500	1.01
1 ¹ / ₂ "	2 ³ / ₁₆ "	4 plies	500	1.13
2"	2 ³ / ₄ "	4 plies	500	1.56
3"	4"	6 plies	500	3.10
4"	5"	6 plies	500	4.00

Hoses are cleaned and capped prior to shipping.



SS147 DRY MATERIAL DISCHARGE HOSE - 3/16" SBR TUBE

- Handles dry abrasive materials and for dry bulk transfer.
- Lightweight construction provides excellent flexibility for handling ease.
- High grade cover resists cuts, gouges and scuffs.

Tube: 3/16" Extruded SBR.
Reinforcement: Textile.
Cover: SBR.
Temperature: -40° to +180°F.

I.D.	O.D.	REINFORCEMENT	WORKING PRESSURE PSI	WEIGHT LB/FT
4"	4 ⁵ / ₈ "	2 plies	60	1.96

Static conductive tube.



SS236 MATERIAL HANDLING HOSE - 1/4" NATURAL RUBBER TUBE

- Rugged, ultra-durable, slurry discharge hose designed to handle highly abrasive wet and dry materials.
- Durable cover resists cuts, scuffs, gouges, and ozone attack.

Tube: 1/4" Extruded Natural Rubber.
Reinforcement: Textile.
Cover: SBR.
Temperature: -40° to +150°F.

I.D.	O.D.	REINFORCEMENT	WORKING PRESSURE PSI	WEIGHT LB/FT
1 ¹ / ₂ "	2 ⁵ / ₁₆ "	2 plies	150	1.21
2"	2 ¹³ / ₁₆ "	2 plies	150	1.56
2 ¹ / ₂ "	3 ⁵ / ₁₆ "	2 plies	150	1.90
3"	3 ¹³ / ₁₆ "	2 plies	150	2.20
4"	4 ¹³ / ₁₆ "	2 plies	100	2.85
4 ¹ / ₂ "	5 ⁵ / ₁₆ "	2 plies	100	3.23
5"	5 ¹³ / ₁₆ "	2 plies	100	3.54
6"	6 ¹³ / ₁₆ "	2 plies	85	4.15

