

**SS247 HEAVY DUTY DRY CEMENT HOSE - 1/4" SBR TUBE**

Static conductive tube.

Higher working pressures available upon request.



- Specially designed to handle dry abrasive materials such as sand or pebble lime.
- Lightweight construction provides excellent flexibility for handling ease.
- High grade cover resists cuts, gouges and scuffs.

**Tube:** 1/4" Extruded SBR.  
**Reinforcement:** Textile.  
**Cover:** SBR.  
**Temperature:** -40° to +180°F.

I.D.	O.D.	REINFORCEMENT	WORKING PRESSURE PSI	WEIGHT LB/FT
4"	4 <sup>3</sup> / <sub>4</sub> "	2 plies	75	2.50
4 <sup>1</sup> / <sub>2</sub> "	5 <sup>1</sup> / <sub>4</sub> "	2 plies	75	2.79
5"	5 <sup>3</sup> / <sub>4</sub> "	2 plies	75	3.11
6"	6 <sup>3</sup> / <sub>4</sub> "	2 plies	70	3.69
8"	8 <sup>3</sup> / <sub>4</sub> "	2 plies	60	4.88

**SW336 MATERIAL HANDLING HOSE - 1/4" NATURAL RUBBER TUBE**

Corrugated construction available upon request.

Refer to EW336 (page 43) for additional sizes.



- Durable, all-weather material suction and discharge hose designed to handle highly abrasive materials.
- Dual wire reinforcement provides full vacuum capabilities.

**Tube:** 1/4" Extruded Natural Rubber.  
**Reinforcement:** Textile with dual wire helix.  
**Cover:** SBR.  
**Temperature:** -40° to +150°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
3"	3 <sup>15</sup> / <sub>16</sub> "	12"	125	2.69	Full
4"	5"	18"	125	3.94	Full
5"	6"	25"	110	5.25	Full
6"	7 <sup>1</sup> / <sub>16</sub> "	30"	110	7.09	Full

**SW360 HOT AIR BLOWER HOSE**

Refer to EW360 (page 44) for additional sizes and working pressures.



- High temperature, ultra-durable hose for transferring hot air between the tractor and trailer during product unloading.
- Superior grade tube will withstand temperatures up to 350°F.
- Heavy duty cover is heat and ozone resistant.

**Tube:** Extruded heat resistant EPDM.  
**Reinforcement:** Textile with dual wire helix.  
**Cover:** Heat resistant EPDM.  
**Temperature:** -40° to +350°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
2"	2 <sup>1</sup> / <sub>2</sub> "	6"	200	.97	Full
3"	3 <sup>9</sup> / <sub>16</sub> "	12"	200	1.75	Full
4"	4 <sup>9</sup> / <sub>16</sub> "	16"	125	2.41	Full
6"	6 <sup>13</sup> / <sub>16</sub> "	24"	100	4.93	Full