

SW353 HEAVY DUTY TANK TRUCK HOSE

- Heavy duty petroleum suction and discharge hose designed for tank truck service.
- Suitable for 50% aromatics.

Tube: Nitrile.
Reinforcement: Textile with dual wire helix.
Cover: Specially compounded Nitrile.
Temperature: -40° to +180°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1 1/4"	1 3/4"	5"	200	.64	Full
1 1/2"	2 1/16"	6"	200	.78	Full
2"	2 9/16"	8"	200	1.07	Full
2 1/2"	3 1/8"	10"	200	1.49	Full
3"	3 9/16"	12"	200	2.07	Full
4"	4 9/16"	18"	200	2.86	Full
5"	5 5/8"	25"	150	3.70	Full
6"	6 3/4"	30"	150	4.83	Full
8"	9 1/4"	42"	150	12.08	Full



EW353 HEAVY DUTY TANK TRUCK HOSE

Custom Made Hose Product

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
10"	11"	60"	75	13.00	Full
12"	13 1/4"	72"	65	18.00	Full

SW355 PETROLEUM / OIL SERVICE HOSE - 300 PSI

- High pressure petroleum suction and discharge hose suitable for 60% aromatics.
- Lightweight construction provides excellent flexibility.
- Heavy duty cover protects against oils, chemicals, cuts, abrasions, and ozone attack.

Tube: Extruded Nitrile.
Reinforcement: Textile with dual wire helix.
Cover: Specially compounded Nitrile.
Temperature: -40° to +180°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
3"	4"	12"	300	2.84	Full
4"	5"	16"	300	3.84	Full
6"	7"	36"	300	7.38	Full

