



VAN GORP® CONVEYOR ROLLERS ARE DESIGNED TO MEET THE DEMANDS FOR ALL TYPES OF PACKAGE HANDLING CONVEYOR SERVICE INCLUDING MAIL HANDLING, BAG HANDLING AND VARIOUS WAREHOUSING REQUIREMENTS.

These conveyor rollers are constructed of steel tubing mechanically expanded to insure a true crown, with end disc continuously welded to rims to exclude foreign material. Straight face pulleys are also available. Crown face will be supplied unless specified otherwise.

Table No. 31 — Standard Sizes & Weights

Pulley Dia.	Bore Range	Face Width - Average Weight in Pounds								
		10	12	14	16	18	20	22	24	26
4	1/2-1 7/16	7	8	9	9	10	10	11	11	12
5	1/2-1 7/16	13	14	15	16	17	18	19	20	21
6	1/2-1 15/16	17	18	20	21	22	23	25	26	27
8	1/2-1 15/16	29	31	33	35	37	39	41	42	44

Pulley Dia.	Bore Range	Face Width - Average Weight in Pounds								
		28	30	32	34	36	38	40	42	44
4	1/2-1 7/16	13	13	14	14	15	15	16	17	17
5	1/2-1 7/16	22	23	24	25	26	27	28	29	30
6	1/2-1 15/16	28	30	31	32	34	35	36	37	38
8	1/2-1 15/16	46	48	50	52	54	56	58	59	61

Rollers with ER Bearings

VAN GORP also offers rollers built to your specifications or designed by our engineers to meet your application needs. Standard rollers are available in diameters of 2 1/8", 2 3/4", 3 1/2" and 4 1/2" with face widths 18" to 60".

