

Quick,

Easy Assembly

## Flange Ball Valves/Fittings

- Quick and easy assembly. No pipe tape or sealant necessary.
- Positive seals.
- Easy on/off hose connections.
- 360° orientation.
- Valves and fittings are manufacture from glass reinforced polypropylene for strength and durability. Will not rust or corrode.



### Valves

- Self-aligning ball rotates freely against Teflon® seats.
- Unique body-to-flange design allows for low torque on/off operations.
- Viton O-ring stem seal and EPDM O-ring body seal.
- Pressure rated at 125 psi @ 70°F
- All valves tested by air pressure under water.



DESCRIPTION	PART NO.	LIST PRICE
1" Full Port Flange x Flange	63028	30.80
2" Full Port Compact Flange x Flange	63123	48.35
3" Full Port Flange x Flange	63125	128.20

Recommended operating pressure  
100 psi @ 0°F • 125 psi @ 70°F • 70 psi @ 150°F

### Stainless Steel Worm Screw Hose Clamps for Flange Fittings



DESCRIPTION	PART NO.	LIST PRICE
1"	62932	6.08
2"	62933	7.56
3"	62934	10.58

### EPDM Flange Gasket for Flange Fittings



DESCRIPTION	PART NO.	LIST PRICE
1"	62935	.88
2"	61574	.98
3"	61575	1.02

