



**COOL**  **CLIP**  
Air Conditioning  
Fittings Catalog



**1**  
one source  
one system  
one solution



# TABLE OF CONTENTS

## Hose

Galaxy 4826 .....	4
Galaxy 4867 .....	4
Galaxy 4890 .....	4

## Fitting

Nomenclature .....	5
--------------------	---

## A/C Crimp Fittings

Compressor O-Ring Tube, Female, 45 Elbow .....	6
Compressor O-Ring Tube, Female, 90 Elbow .....	6
Compressor O-Ring Tube, Female, 90 Block Elbow .....	6
Compressor O-Ring Tube, Female, R134a Valve, 90 Block Elbow .....	6
Flareless Tube, Male. ....	7
Flareless Tube, Male, 90 Block Elbow .....	7
Flareless Tube, Male, Metric. ....	7
O-Ring Insert Male .....	7
O-Ring Insert Male, 45 Elbow. ....	8
O-Ring Insert Male, 90 Elbow. ....	8
O-Ring Insert Male, Bulkhead. ....	8
O-Ring Insert Male, Bulkhead, 90 Elbow .....	8
O-Ring Insert Male, R134a Valve .....	9
O-Ring Insert Male, R134a Valve, 90 Elbow .....	9
O-Ring Tube, Female, Swivel. ....	9
O-Ring Tube, Female, Swivel, 45 Elbow .....	9
O-Ring Tube, Female, Swivel, 90 Elbow .....	10
O-Ring Tube, Female, Swivel, 90 Block Elbow .....	10
O-Ring Tube, Female, Swivel, 180 Elbow .....	10
O-Ring Tube, Female, Swivel, Metric .....	10
O-Ring Tube, Female, Swivel, Metric, 45 Elbow. ....	11
O-Ring Tube, Female, Swivel, Metric, 90 Elbow. ....	11
O-Ring Tube, Female, Swivel, R12 Valve .....	11
O-Ring Tube, Female, Swivel, R12 Valve, 90 Elbow .....	11
O-Ring Tube, Female, Swivel, R134a Valve. ....	12
O-Ring Tube, Female, Swivel, R134a Valve, 45 Elbow .....	12
O-Ring Tube, Female, Swivel, R134a Valve, 90 Elbow .....	12
O-Ring Tube, Male, Swivel .....	12
O-Ring Tube, Male, Swivel, 45 Elbow .....	13
O-Ring Tube, Male, Swivel, 90 Elbow .....	13
O-Ring Tube, Male, Swivel, Long Pilot .....	13
O-Ring Tube, Male, Swivel, R134a Valve .....	13
O-Ring Tube, Male, Swivel, R134a Valve, 90 Elbow .....	14
SAE 45 Flare, Female, Swivel .....	14
SAE 45 Flare, Female, Swivel, 45 Elbow .....	14
SAE 45 Flare, Female, Swivel, 90 Elbow .....	14
SAE 45 Flare, Male. ....	15
SAE 45 Flare, Male, 45 Elbow .....	15
SAE 45 Flare, Male, 90 Elbow .....	15



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# TABLE OF CONTENTS

## GC Cool Clip™ Fittings

Compressor Pad Block, R12 Valve/Switch, 90 Block Elbow . . . . .	16
Compressor Pad Block, R12 Valve/Switch Reversed,90 Elbow . . . . .	16
Compressor O-Ring Tube, Female, 45 Elbow . . . . .	16
Compressor O-Ring Tube, Female, 90 Elbow . . . . .	16
Compressor O-Ring Tube, Female, 90 Block Elbow . . . . .	16
Compressor O-Ring Tube, Female, R134a Valve, 90 Block Elbow . . . . .	17
Flareless Tube, Braze-On . . . . .	17
Flareless Tube, Male . . . . .	17
Flareless Tube, Male, 90 Block Elbow . . . . .	17
Flareless Tube, Male, Metric . . . . .	18
Ford Spring Lock, Female . . . . .	18
Ford Spring Lock, Female, 45 Elbow . . . . .	18
Ford Spring Lock, Female, 90 Elbow . . . . .	18
Ford Spring Lock, Male . . . . .	19
Ford Spring Lock, Male, 45 Elbow . . . . .	19
Ford Spring Lock, Male, 90 Elbow . . . . .	19
Hose Mender . . . . .	19
Hose Mender, 90 Elbow . . . . .	20
Hose Mender, 180 Elbow . . . . .	20
Hose Mender, R12 Valve . . . . .	20
Hose Mender, R134a Valve . . . . .	20
Hose Mender, with Sight Glass . . . . .	20
Hose Mender, Tee . . . . .	21
O-Ring Face Seal, Female, Swivel . . . . .	21
O-Ring Face Seal, Female, Swivel, 90 Elbow . . . . .	21
O-Ring Insert Male . . . . .	21
O-Ring Insert Male, 45 Elbow . . . . .	22
O-Ring Insert Male, 90 Elbow . . . . .	22
O-Ring Insert Male, Bulkhead . . . . .	22
O-Ring Insert Male, Bulkhead, 90 Elbow . . . . .	22
O-Ring Insert Male, R134a Valve . . . . .	23
O-Ring Insert Male, R134a Valve, 90 Elbow . . . . .	23
O-Ring Tube, Female, Swivel . . . . .	23
O-Ring Tube, Female, Swivel, 45 Elbow . . . . .	23
O-Ring Tube, Female, Swivel, 90 Elbow . . . . .	24
O-Ring Tube, Female, Swivel, 90 Block Elbow . . . . .	24
O-Ring Tube, Female, Swivel, 180 Elbow . . . . .	24
O-Ring Tube, Female, Swivel, R12 Valve . . . . .	24
O-Ring Tube, Female, Swivel, R12 Valve, 90 Elbow . . . . .	25
O-Ring Tube, Female, Swivel, R134a Valve . . . . .	25
O-Ring Tube, Female, Swivel, R134a Valve, 45 Elbow . . . . .	25
O-Ring Tube, Female, Swivel, R134a Valve, 90 Elbow . . . . .	25
O-Ring Tube, Male, Swivel . . . . .	26
O-Ring Tube, Male, Swivel, 45 Elbow . . . . .	26
O-Ring Tube, Male, Swivel, 90 Elbow . . . . .	26
O-Ring Tube, Male, Swivel, Long Pilot . . . . .	26
O-Ring Tube , Male, Swivel, R134a Valve . . . . .	27
O-Ring Tube, Male, Swivel, R134a Valve, 90 Elbow . . . . .	27



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# TABLE OF CONTENTS

SAE 45 Flare, Female, Swivel . . . . .	27
SAE 45 Flare, Female, Swivel, 45 Elbow . . . . .	27
SAE 45 Flare, Female, Swivel, 90 Elbow . . . . .	28
SAE 45 Flare, Male . . . . .	28
SAE 45 Flare, Male, 45 Elbow . . . . .	28
SAE 45 Flare, Male, 90 Elbow . . . . .	28

## Adapters

O-Ring Tube Compressor Female to O-Ring Insert Male, 90 Elb, w/R134a Valve . . . . .	29
O-Ring Tube Female to O-Ring Insert Male w/R12 Valve . . . . .	29
O-Ring Tube Female to O-Ring Insert Male, 90 Elbow w/R12 Valve . . . . .	29
O-Ring Tube Female to O-Ring Insert Male w/R134a Valve . . . . .	30
O-Ring Tube Female to O-Ring Insert Male, 90 Elbow w/R134a Valve . . . . .	30

## Fitting Accessories & Assembly Tools

Flareless Tube Nuts . . . . .	31
Flareless Tube Sleeves . . . . .	31
Flareless Tube Sleeves, Metric . . . . .	31
Inline Orifice Tubes . . . . .	31
O-Ring, for Ford Spring Lock . . . . .	31
O-Ring, for Switch . . . . .	32
O-Ring, for Tube Fittings . . . . .	32
Sealing Washers . . . . .	32
Valve Adapters . . . . .	32
Valve Caps . . . . .	32
Valve Core . . . . .	33
Metal Clip . . . . .	33
Plastic Clip Holder . . . . .	33
Clip Pliers . . . . .	33
Hose Cutting Tool & Replacement Blades . . . . .	33



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# Galaxy® Air Conditioning Hose

## GALAXY 4826 Hose

SAE J2064 / Type C / Class II / Low Pressure

For use with Goodyear "AC" Crimp Fittings



Part Number	Hose Size I.D.		Hose O.D.		Max. Working Pressure		Min. Bend Radius		Min. Burst Pressure		Weight (lbs/foot)
	INCH	MM	INCH	MM	PSI	MPA	INCH	MM	PSI	MPA	
G4826-06	5/16	7.9	0.75	19.1	500	3.4	.6	16	2000	13.8	0.20
G4826-08	13/32	10.3	0.91	23.0	500	3.4	1.0	25	2000	13.8	0.28
G4826-10	1/2	12.7	1.00	25.4	500	3.4	1.3	32	2000	13.8	0.33
G4826-12	5/8	15.9	1.13	28.6	350	2.4	2.0	50	1750	12.1	0.38

Continuous Brand Layline Example

GALAXY by GOODYEAR SAE J2064 Type C ClassII 1/2 in (13mm) 4826 - Size 10 Made in USA

## GALAXY 4867 Hose

SAE J2064 / Type C / Class I / Low Pressure

For use with Goodyear "AC" Crimp Fittings



Part Number	Hose Size I.D.		Hose O.D.		Max. Working Pressure		Min. Bend Radius		Min. Burst Pressure		Weight (lbs/foot)
	INCH	MM	INCH	MM	PSI	MPA	INCH	MM	PSI	MPA	
G4867-14	3/4	19.1	1.13	28.6	350	2.4	6.3	160	1750	12.1	0.26

Continuous Brand Layline Example

GOODYEAR GALAXY A/C Hose 3/4 IN (19mm) 4867

## GALAXY 4890 Hose

SAE J2064 / Type C / Class I / Low Pressure

For use with Goodyear COOL CLIP™ Fittings



Part Number	Hose Size I.D.		Hose O.D.		Max. Working Pressure		Min. Bend Radius		Min. Burst Pressure		Weight (lbs/foot)
	INCH	MM	INCH	MM	PSI	MPA	INCH	MM	PSI	MPA	
G4890-06	5/16	7.9	.56	14.7	500	3.4	1.0	25	2000	13.8	0.09
G4890-08	13/32	10.3	.69	17.3	500	3.4	1.5	38	2000	13.8	0.12
G4890-10	1/2	12.7	.75	19.4	500	3.4	2.5	63	2000	13.8	0.13
G4890-12	5/8	15.9	.94	23.6	350	2.4	4.0	104	1750	12.1	0.20

Continuous Brand Layline Example

GALAXY SLE 4890 A/C Hose 13/32 in (10mm) GOODYEAR R134a



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

## GOODYEAR A/C Fitting Nomenclature


Fitting Style	Family	Fitting Family Description	Gender	Swivel	Valve (V)	Attribute
CB12VS	CB	Compressor Pad Block			R12	S=Single
CB12VSR	CB				R12	SR=Single Reversed
COTF	COT	Compressor O-Ring Tube	F	Yes		
COTF134V	COT		F	Yes	R134a	
FTBO	FT	Flareless Tube				BO=Braze On
FTM	FT		M			
FTMM	FT		M			M=Metric
FTN	FT					N=Nut
FTS	FT					S=Sleeve
FTSM	FT					S=Sleeve, M=Metric
FSLF	FSL	Ford Spring Lock	F			
FSLM	FSL		M			
HM	HM	Hose Mender				
HM12V	HM				R12	
HM134V	HM				R134a	
HMSG	HM					SG=Sight Glass
HMT	HM					T=Tee
ILOTORA	ILOT	Inline Orifice Tube				ORA=Orange
ILOTRED	ILOT					RED=Red
ILOTBLU	ILOT					BLU=Blue
ILOTBLK	ILOT					BLK=Black
ILOTWHI	ILOT					WHI=White
OFFX	OF	O-Ring Face Seal (SAE J1453 ORS/ORFS)	F	X		
OIM	OI	O-Ring Insert	M			
OIMB	OI		M			B=Bulkhead
OIM134V	OI		M		134a	
OTF	OT	O-Ring Tube	F	Yes		
OTF12V	OT		F	Yes	R12	
OTF134V	OT		F	Yes	R134a	
OTF134VHS	OT		F	Yes	R134a	HS=High Pressure Side
OTM	OT		M	Yes		
OTMLP	OT		M	Yes		LP=Long Pilot
OTM134V	OT		M	Yes	R134a	
SFFX	SF	SAE 45° J512 Flare	F	X		
SFM	SF		M			
SWA	SW	Sealing Washer				A=Accumulator
SWCN	SW					CN=Compressor Narrow
SWCW	SW					CW=Compressor Wide
VC12V	VC	Valve Cap			R12	
VC134VHS	VC				R134a	HS=High Pressure Side
VC134VLS	VC				R134a	LS=Low Pressure Side

Additional Prefix & Suffix
AC=Crimp Fitting
GC=Cool Clip Fitting
45=45° Elbow
45B=45° Block Elbow
90=90° Elbow
90B=90° Block Elbow
180=180° Elbow
A=Aluminum

**PN GC-OTF134V45**

134V=R134a Valve

45 = 45° Elbow



OTF= O-Ring Tube Female



One Source, One System, One Solution.


[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# 'AC' (Crimp) FITTINGS

For use with GALAXY G4826 (5/16"-5/8") & G4867 (3/4") Hose

## Compressor O-Ring Tube, Female, 45 Elbow




DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-COTF45-0810	50133-0810	13/32	10.30	1-14	1.10	28	2.01	51		
AC-COTF45-1010	50133-1010	1/2	12.70	1-14	1.26	32	1.38	35		
AC-COTF45-1210	50133-1210	5/8	15.90	1-14	0.67	17	1.26	32		

## Compressor O-Ring Tube, Female, 90 Elbow

Picture Not Available


DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-COTF90-0810	50135-0810	13/32	10.30	1-14	1.93	49	1.77	45		
AC-COTF90-1010	50135-1010	1/2	12.70	1-14	2.20	56	1.77	45		
AC-COTF90-1210	50135-1210	5/8	15.90	1-14	2.72	69	2.36	60		

## Compressor O-Ring Tube, Female, 90 Block Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-COTF90B-0810	50137-0810	13/32	10.30	1-14	0.83	21	0.94	24		
AC-COTF90B-1010	50137-1010	1/2	12.70	1-14	0.83	21	0.94	24		
AC-COTF90B-1210	50137-1210	5/8	15.90	1-14	0.83	21	1.06	27		

## Compressor O-Ring Tube, Female, R134a Valve, 90 Block Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-COTF134V90B-0810	50145-0810	13/32	10.30	1-14	0.83	21	0.94	24	0.63	16
AC-COTF134V90B-1010	50145-1010	1/2	12.70	1-14	0.83	21	0.94	24	0.51	13
AC-COTF134V90B-1210	50145-1210	5/8	15.90	1-14	0.83	21	1.06	27	0.51	13



# 'AC' (Crimp) FITTINGS

## For use with GALAXY G4826 (5/16"-5/8") & G4867 (3/4") Hose

### Flareless Tube, Male

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-FTM-0606	50230-0606	5/16	7.90	5/8-18			1.46	37		
AC-FTM-0608	50230-0608	5/16	7.90	3/4-16			1.61	41		
AC-FTM-0806	50230-0806	13/32	10.30	5/8-18			1.61	41		
AC-FTM-0808	50230-0808	13/32	10.30	3/4-16			1.61	41		
AC-FTM-0810	50230-0810	13/32	10.30	7/8-14			2.13	54		
AC-FTM-1008	50230-1008	1/2	12.70	3/4-16			2.13	54		
AC-FTM-1010	50230-1010	1/2	12.70	7/8-14			2.13	54		
AC-FTM-1210	50230-1210	5/8	15.90	7/8-14			2.36	60		
AC-FTM-1212	50230-1212	5/8	15.90	1 1/16-14			2.36	60		

### Flareless Tube, Male, 90 Block Elbow

Picture Not Available


DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-FTM90B-0606	50235-0606	5/16	7.90	5/8-18	1.50	38	1.06	27		
AC-FTM90B-0808	50235-0808	13/32	10.30	3/4-16	1.73	44	1.26	32		
AC-FTM90B-0810	50235-0810	13/32	10.30	7/8-14	2.01	51	1.50	38		
AC-FTM90B-1008	50235-1008	1/2	12.70	3/4-16	2.01	51	1.50	38		
AC-FTM90B-1010	50235-1010	1/2	12.70	7/8-14	2.01	51	1.50	38		
AC-FTM90B-1210	50235-1210	5/8	15.90	7/8-14	2.36	60	2.36	60		
AC-FTM90B-1212	50235-1212	5/8	15.90	1 1/16-14	2.36	60	2.36	60		

### Flareless Tube, Male, Metric

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-FTMM-0608	50240-0608	5/16	7.90	5/8-18			1.61	41		
AC-FTMM-0812	50240-0812	13/32	10.30	3/4-16			2.13	54		
AC-FTMM-1015	50240-1015	1/2	12.70	7/8-14			2.36	60		

### O-Ring Insert Male



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OIM-0606	50500-0606	5/16	7.90	5/8-18			1.46	37		
AC-OIM-0808	50500-0808	13/32	10.30	3/4-16			1.61	41		
AC-OIM-1010	50500-1010	1/2	12.70	7/8-14			2.13	54		
AC-OIM-1210	50500-1210	5/8	15.90	7/8-14			1.69	43		
AC-OIM-1212	50500-1212	5/8	15.90	1 1/16-14			2.36	60		
AC-OIM-1412	50500-1412	3/4	19.05	1 1/16-14			2.36	60		



One Source, One System, One Solution.


[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# 'AC' (Crimp) FITTINGS


For use with GALAXY G4826 (5/16"-5/8") & G4867 (3/4") Hose

## O-Ring Insert Male, 45 Elbow




DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OIM45-0606	50503-0606	5/16	7.90	5/8-18	0.75	19	0.83	21		
AC-OIM45-0808	50503-0808	13/32	10.30	3/4-16	0.98	25	0.94	24		
AC-OIM45-1010	50503-1010	1/2	12.70	7/8-14	1.26	32	1.26	32		
AC-OIM45-1212	50503-1212	5/8	15.90	1 1/16-14	1.38	35	1.50	38		
AC-OIM45-1412	50503-1412	3/4	19.05	1 1/16-14	1.38	35	1.50	38		

## O-Ring Insert Male, 90 Elbow




DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OIM90-0606	50505-0606	5/16	7.90	5/8-18	1.50	38	1.06	27		
AC-OIM90-0808	50505-0808	13/32	10.30	3/4-16	1.73	44	1.26	32		
AC-OIM90-1010	50505-1010	1/2	12.70	7/8-14	2.01	51	1.50	38		
AC-OIM90-1210	50505-1210	5/8	15.90	7/8-14	2.17	55	1.97	50		
AC-OIM90-1212	50505-1212	5/8	15.90	1 1/16-14	2.52	64	2.36	60		
AC-OIM90-1412	50505-1412	3/4	19.05	1 1/16-14	2.52	64	2.36	60		

## O-Ring Insert Male, Bulkhead



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OIMB-0606	50515-0606	5/16	7.90	5/8-18			2.52	64		
AC-OIMB-0808	50515-0808	13/32	10.30	3/4-16			2.76	70		
AC-OIMB-1010	50515-1010	1/2	12.70	7/8-14			2.95	75		

## O-Ring Insert Male, Bulkhead, 90 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OIMB90-0606	50520-0606	5/16	7.90	5/8-18	2.13	54	1.61	41		
AC-OIMB90-0808	50520-0808	13/32	10.30	3/4-16	2.44	62	1.73	44		
AC-OIMB90-1010	50520-1010	5/8	15.90	7/8-14	2.52	64	2.01	51		



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# 'AC' (Crimp) FITTINGS

For use with GALAXY G4826 (5/16"-5/8") & G4867 (3/4") Hose

## O-Ring Insert Male, R134a Valve

Picture Not Available


DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OIM134V-0606	50530-0606	5/16	7.90	5/8-18			2.44	62	0.63	16
AC-OIM134V-0808	50530-0808	13/32	10.30	3/4-16			2.56	65	0.63	16
AC-OIM134V-1010	50530-1010	1/2	12.70	7/8-14			1.77	45	0.51	13
AC-OIM134V-1212	50530-1212	5/8	15.90	1 1/16-14			2.95	75	0.51	13

## O-Ring Insert Male, R134a Valve, 90 Elbow

Picture Not Available


DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OIM134V90-0606	50535-0606	5/16	7.90	5/8-18	1.61	41	2.13	54	0.63	16
AC-OIM134V90-0808	50535-0808	13/32	10.30	3/4-16	1.89	48	2.13	54	0.63	16
AC-OIM134V90-1010	50535-1010	1/2	12.70	7/8-14	2.13	54	2.36	60	0.51	13

## O-Ring Tube, Female, Swivel



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OTF-0605	50600-0605	5/16	7.90	9/16-18			1.30	33		
AC-OTF-0606	50600-0606	5/16	7.90	5/8-18			1.38	35		
AC-OTF-0608	50600-0608	5/16	7.90	3/4-16			1.50	38		
AC-OTF-0806	50600-0806	13/32	10.30	5/8-18			1.50	38		
AC-OTF-0808	50600-0808	13/32	10.30	3/4-16			1.50	38		
AC-OTF-1008	50600-1008	1/2	12.70	3/4-16			1.69	43		
AC-OTF-1010	50600-1010	1/2	12.70	7/8-14			1.69	43		
AC-OTF-1012	50600-1012	1/2	12.70	1 1/16-14			1.81	46		
AC-OTF-1210	50600-1210	5/8	15.90	7/8-14			1.81	46		
AC-OTF-1212	50600-1212	5/8	15.90	1 1/16-14			1.81	46		
AC-OTF-1412	50600-1412	3/4	19.05	1 1/16-14			1.81	46		

## O-Ring Tube, Female, Swivel, 45 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OTF45-0606	50603-0606	5/16	7.90	5/8-18	0.55	14	0.83	21		
AC-OTF45-0806	50603-0806	13/32	10.30	5/8-18	0.63	16	0.94	24		
AC-OTF45-0808	50603-0808	13/32	10.30	3/4-16	0.63	16	0.94	24		
AC-OTF45-1010	50603-1010	1/2	12.70	7/8-14	0.87	22	1.26	32		
AC-OTF45-1210	50603-1210	5/8	15.90	7/8-14	0.94	24	1.50	38		
AC-OTF45-1212	50603-1212	5/8	15.90	1 1/16-14	0.94	24	1.50	38		
AC-OTF45-1412	50603-1412	3/4	19.05	1 1/16-14	0.94	24	1.50	38		



One Source, One System, One Solution.


[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# 'AC' (Crimp) FITTINGS


For use with GALAXY G4826 (5/16"-5/8") & G4867 (3/4") Hose

## O-Ring Tube, Female, Swivel, 90 Elbow




DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OTF90-0605	50605-0605	5/16	7.90	9/16-18	1.10	28	1.26	32		
AC-OTF90-0606	50605-0606	5/16	7.90	5/8-18	1.10	28	1.06	27		
AC-OTF90-0608	50605-0608	5/16	7.90	3/4-16	1.30	33	1.26	32		
AC-OTF90-0806	50605-0806	13/32	10.30	5/8-18	1.30	33	1.26	32		
AC-OTF90-0808	50605-0808	13/32	10.30	3/4-16	1.30	33	1.26	32		
AC-OTF90-1008	50605-1008	1/2	12.70	3/4-16	1.50	38	1.50	38		
AC-OTF90-1010	50605-1010	1/2	12.70	7/8-14	1.50	38	1.50	38		
AC-OTF90-1012	50605-1012	1/2	12.70	1 1/16-14	1.77	45	1.77	45		
AC-OTF90-1210	50605-1210	5/8	15.90	7/8-14	1.77	45	1.77	45		
AC-OTF90-1212	50605-1212	5/8	15.90	1 1/16-14	1.77	45	1.77	45		
AC-OTF90-1412	50605-1412	3/4	19.05	1 1/16-14	1.77	45	1.77	45		

## O-Ring Tube, Female, Swivel, 90 Block Elbow




DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM		
AC-OTF90B-0808	50610-0808	13/32	10.30	3/4-16	0.75	19	0.94	24		
AC-OTF90B-1010	50610-1010	1/2	12.70	7/8-14	0.75	19	0.98	25		
AC-OTF90B-1210	50610-1210	5/8	15.90	7/8-14	0.75	19	0.98	25		

## O-Ring Tube, Female, Swivel, 180 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM		
AC-OTF180-0606	50615-0606	5/16	7.90	5/8-18	1.61	41	2.01	51		
AC-OTF180-0808	50615-0808	13/32	10.30	3/4-16	1.73	44	2.01	51		
AC-OTF180-1212	50615-1212	5/8	15.90	1 1/16-14	2.13	54	2.99	76		

## O-Ring Tube, Female, Swivel, Metric



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM		
AC-OTFM-0616	50630-0616	5/16	7.90	16x1.5			1.54	39		
AC-OTFM-0618	50630-0618	5/16	7.90	18x1.5			1.54	39		
AC-OTFM-0620	50630-0620	5/16	7.90	20x1.5			1.54	39		
AC-OTFM-0820	50630-0820	13/32	10.30	20x1.5			1.69	43		
AC-OTFM-1022	50630-1022	1/2	12.70	22x1.5			1.69	43		
AC-OTFM-1024	50630-1024	1/2	12.70	24x2.0			1.69	43		
AC-OTFM-1227	50630-1227	5/8	15.90	27x2.0			1.81	46		



One Source, One System, One Solution.


[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# 'AC' (Crimp) FITTINGS


For use with GALAXY G4826 (5/16"-5/8") & G4867 (3/4") Hose

## O-Ring Tube, Female, Swivel, Metric, 45 Elbow




DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD	DROP		LENGTH		VALVE	
		INCH	MM	SIZE	INCH	MM	INCH	MM	INCH	MM
AC-OTFM45-0614	50633-0614	5/16	7.90	14x1.5	0.55	14	0.98	25		
AC-OTFM45-0616	50633-0616	5/16	7.90	16x1.5	0.55	14	0.98	25		
AC-OTFM45-0618	50633-0618	5/16	7.90	18x1.5	0.55	14	0.98	25		
AC-OTFM45-0620	50633-0620	5/16	7.90	20x1.5	0.55	14	0.98	25		
AC-OTFM45-0820	50633-0820	13/32	10.30	20x1.5	0.63	16	0.98	25		
AC-OTFM45-1022	50633-1022	1/2	12.70	22x1.5	0.87	22	1.26	32		
AC-OTFM45-1024	50633-1024	1/2	12.70	24x2.0	0.87	22	1.26	32		
AC-OTFM45-1227	50633-1227	5/8	15.90	27x2.0	0.94	24	1.50	38		

## O-Ring Tube, Female, Swivel, Metric, 90 Elbow




DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD	DROP		LENGTH		VALVE	
		INCH	MM	SIZE	INCH	MM	INCH	MM	INCH	MM
AC-OTFM90-0616	50635-0616	5/16	7.90	16x1.5	1.10	28	1.06	27		
AC-OTFM90-0618	50635-0618	5/16	7.90	18x1.5	1.10	28	1.06	27		
AC-OTFM90-0620	50635-0620	5/16	7.90	20x1.5	1.10	28	1.06	27		
AC-OTFM90-0820	50635-0820	13/32	10.30	20x1.5	1.30	33	1.26	32		
AC-OTFM90-1022	50635-1022	1/2	12.70	22x1.5	1.50	38	1.50	38		
AC-OTFM90-1024	50635-1024	1/2	12.70	24x2.0	1.50	38	1.50	38		
AC-OTFM90-1227	50635-1227	5/8	15.90	27x2.0	1.77	45	1.77	45		

## O-Ring Tube, Female, Swivel, R12 Valve



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD	DROP		LENGTH		VALVE	
		INCH	MM	SIZE	INCH	MM	INCH	MM	INCH	MM
AC-OTF12V-0606	50650-0606	5/16	7.90	5/8-18			1.89	48	1/4	6.35
AC-OTF12V-0808	50650-0808	13/32	10.30	3/4-16			1.89	48	1/4	6.35
AC-OTF12V-1010	50650-1010	1/2	12.70	7/8-14			2.13	54	1/4	6.35

## O-Ring Tube, Female, Swivel, R12 Valve, 90 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD	DROP		LENGTH		VALVE	
		INCH	MM	SIZE	INCH	MM	INCH	MM	INCH	MM
AC-OTF12V90-0606	50655-0606	5/16	7.90	5/8-18	1.10	28	2.13	54	1/4	6.35
AC-OTF12V90-0808	50655-0808	13/32	10.30	3/4-16	1.30	33	2.13	54	1/4	6.35
AC-OTF12V90-1010	50655-1010	1/2	12.70	7/8-14	1.50	38	2.36	60	1/4	6.35
AC-OTF12V90-1210	50655-1210	5/8	15.90	7/8-14	1.73	44	2.68	68	1/4	6.35



One Source, One System, One Solution.


[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# 'AC' (Crimp) FITTINGS


For use with GALAXY G4826 (5/16"-5/8") & G4867 (3/4") Hose

## O-Ring Tube, Female, Swivel, R134a Valve




DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OTF134V-0606	50660-0606	5/16	7.90	5/8-18			1.89	48	0.63	16
AC-OTF134V-0808	50660-0808	13/32	10.30	3/4-16			1.89	48	0.63	16
AC-OTF134V-1010	50660-1010	1/2	12.70	7/8-14			2.13	54	0.51	13
AC-OTF134V-1210	50660-1210	5/8	15.90	7/8-14			2.24	57	0.51	13
AC-OTF134V-1212	50660-1212	5/8	15.90	1 1/16-14			2.24	57	0.51	13
AC-OTF134V-1412	50660-1412	3/4	19.05	1 1/16-14			2.24	57	0.51	13
AC-OTF134VHS-1010	50675-1010	1/2	12.70	7/8-14			2.13	54	0.63	16

## O-Ring Tube, Female, Swivel, R134a Valve, 45 Elbow




DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OTF134V45-0606	50663-0606	5/16	7.90	5/8-18	0.55	14	1.61	41	0.63	16
AC-OTF134V45-0808	50663-0808	13/32	10.30	3/4-16	0.63	16	1.61	41	0.63	16
AC-OTF134V45-1010	50663-1010	1/2	12.70	7/8-14	0.87	22	1.73	44	0.51	13
AC-OTF134V45-1210	50663-1210	5/8	15.90	7/8-14	0.94	24	1.89	48	0.51	13
AC-OTF134V45-1212	50663-1212	5/8	15.90	1 1/16-14	0.94	24	1.89	48	0.51	13
AC-OTF134V45-1412	50663-1412	3/4	19.05	1 1/16-14	0.94	24	1.89	48	0.51	13

## O-Ring Tube, Female, Swivel, R134a Valve, 90 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OTF134V90-0606	50665-0606	5/16	7.90	5/8-18	1.10	28	2.13	54	0.63	16
AC-OTF134V90-0806	50665-0806	13/32	10.30	5/8-18	1.30	33	2.13	54	0.63	16
AC-OTF134V90-0808	50665-0808	13/32	10.30	3/4-16	1.30	33	2.13	54	0.63	16
AC-OTF134V90-1010	50665-1010	1/2	12.70	7/8-14	1.50	38	2.36	60	0.51	13
AC-OTF134V90-1210	50665-1210	5/8	15.90	7/8-14	1.73	44	2.68	68	0.51	13
AC-OTF134V90-1212	50665-1212	5/8	15.90	1 1/16-14	1.73	44	2.68	68	0.51	13
AC-OTF134V90-1412	50665-1412	3/4	19.05	1 1/16-14	1.73	44	2.68	68	0.51	13

## O-Ring Tube, Male, Swivel



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OTM-0606	50700-0606	5/16	7.90	5/8-18			1.69	43		
AC-OTM-0607	50700-0607	5/16	7.90	1 1/16-16			1.69	43		
AC-OTM-0608	50700-0608	5/16	7.90	3/4-18			1.77	45		
AC-OTM-0808	50700-0808	13/32	10.30	3/4-18			1.77	45		
AC-OTM-1010	50700-1010	1/2	12.70	7/8-18			1.89	48		
AC-OTM-1012	50700-1012	1/2	12.70	1 1/16-16			2.36	60		
AC-OTM-1210	50700-1210	5/8	15.90	7/8-18			2.36	60		
AC-OTM-1212	50700-1212	5/8	15.90	1 1/16-16			2.36	60		



One Source, One System, One Solution.


[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# 'AC' (Crimp) FITTINGS


For use with GALAXY G4826 (5/16"-5/8") & G4867 (3/4") Hose

## O-Ring Tube, Male, Swivel, 45 Elbow




DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD	DROP		LENGTH		VALVE	
		INCH	MM	SIZE	INCH	MM	INCH	MM	INCH	MM
AC-OTM45-0606	50703-0606	5/16	7.90	5/8-18	0.87	22	0.83	21		
AC-OTM45-0808	50703-0808	13/32	10.30	3/4-18	0.98	25	0.94	24		
AC-OTM45-1010	50703-1010	1/2	12.70	7/8-18	1.06	27	1.26	32		
AC-OTM45-1210	50703-1210	5/8	15.90	7/8-18	1.18	30	1.50	38		
AC-OTM45-1212	50703-1212	5/8	15.90	1 1/16-16	1.18	30	1.50	38		

## O-Ring Tube, Male, Swivel, 90 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD	DROP		LENGTH		VALVE	
		INCH	MM	SIZE	INCH	MM	INCH	MM	INCH	MM
AC-OTM90-0606	50705-0606	5/16	7.90	5/8-18	1.61	41	1.06	27		
AC-OTM90-0608	50705-0608	5/16	7.90	3/4-18	1.89	48	1.26	32		
AC-OTM90-0806	50705-0806	13/32	10.30	5/8-18	1.89	48	1.26	32		
AC-OTM90-0808	50705-0808	13/32	10.30	3/4-18	1.89	48	1.26	32		
AC-OTM90-1010	50705-1010	1/2	12.70	7/8-18	2.13	54	1.50	38		
AC-OTM90-1012	50705-1012	1/2	12.70	1 1/16-16	2.24	57	1.77	45		
AC-OTM90-1210	50705-1210	5/8	15.90	7/8-18	2.24	57	1.77	45		
AC-OTM90-1212	50705-1212	5/8	15.90	1 1/16-16	2.24	57	1.77	45		

## O-Ring Tube, Male, Swivel, Long Pilot



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD	DROP		LENGTH		VALVE	
		INCH	MM	SIZE	INCH	MM	INCH	MM	INCH	MM
AC-OTMLP-0606	50720-0606	5/16	7.90	5/8-18	1.61	41	1.06	27		
AC-OTMLP-0808	50720-0808	13/32	10.30	3/4-18	1.89	48	1.26	32		
AC-OTMLP-1010	50720-1010	1/2	12.70	7/8-18	2.13	54	1.50	38		
AC-OTMLP-1210	50720-1210	5/8	15.90	7/8-18	2.24	57	1.77	45		

## O-Ring Tube , Male, Swivel, R134a Valve

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD	DROP		LENGTH		VALVE	
		INCH	MM	SIZE	INCH	MM	INCH	MM	INCH	MM
AC-OTM134V-0606	50730-0606	5/16	7.90	5/8-18			1.69	43	0.63	16
AC-OTM134V-0808	50730-0808	13/32	10.30	3/4-18			1.77	45	0.63	16
AC-OTM134V-1010	50730-1010	1/2	12.70	7/8-18			2.36	60	0.51	13
AC-OTM134V-1210	50730-1210	5/8	15.90	7/8-18			2.36	60	0.51	13
AC-OTM134V-1212	50730-1212	5/8	15.90	1 1/16-16			2.52	64	0.51	13



One Source, One System, One Solution.


[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# 'AC' (Crimp) FITTINGS


For use with GALAXY G4826 (5/16"-5/8") & G4867 (3/4") Hose

## O-Ring Tube, Male, Swivel, R134a Valve, 90 Elbow




DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-OTM134V90-1010	50735-1010	1/2	12.70	7/8-18	2.13	54	2.36	60	0.51	13
AC-OTM134V90-1210	50735-1210	5/8	15.90	7/8-18	2.13	54	2.36	60	0.51	13

## SAE 45 Flare, Female, Swivel




DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-SFFX-0606	50760-0606	5/16	7.90	5/8-18			1.38	35		
AC-SFFX-0608	50760-0608	5/16	7.90	3/4-16			1.18	30		
AC-SFFX-0806	50760-0806	13/32	10.30	5/8-18			1.18	30		
AC-SFFX-0808	50760-0808	13/32	10.30	3/4-16			1.18	30		
AC-SFFX-1008	50760-1008	1/2	12.70	3/4-16			1.50	38		
AC-SFFX-1010	50760-1010	1/2	12.70	7/8-14			1.50	38		
AC-SFFX-1210	50760-1210	5/8	15.90	7/8-14			1.73	44		
AC-SFFX-1212	50760-1212	5/8	15.90	1 1/16-14			1.73	44		

## SAE 45 Flare, Female, Swivel, 45 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-SFFX45-0606	50763-0606	5/16	7.90	5/8-18	0.55	14	0.83	21		
AC-SFFX45-0608	50763-0608	5/16	7.90	3/4-16	0.63	16	0.94	24		
AC-SFFX45-0806	50763-0806	13/32	10.30	5/8-18	0.63	16	0.94	24		
AC-SFFX45-0808	50763-0808	13/32	10.30	3/4-16	0.63	16	0.94	24		
AC-SFFX45-1008	50763-1008	1/2	12.70	3/4-16	0.87	22	1.26	32		
AC-SFFX45-1010	50763-1010	1/2	12.70	7/8-14	0.87	22	1.26	32		
AC-SFFX45-1210	50763-1210	5/8	15.90	7/8-14	0.98	25	1.50	38		
AC-SFFX45-1212	50763-1212	5/8	15.90	1 1/16-14	0.98	25	1.50	38		

## SAE 45 Flare, Female, Swivel, 90 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-SFFX90-0606	50765-0606	5/16	7.90	5/8-18	1.06	27	1.06	27		
AC-SFFX90-0608	50765-0608	5/16	7.90	3/4-16	1.26	32	1.26	32		
AC-SFFX90-0806	50765-0806	13/32	10.30	5/8-18	1.26	32	1.26	32		
AC-SFFX90-0808	50765-0808	13/32	10.30	3/4-16	1.26	32	1.26	32		
AC-SFFX90-1008	50765-1008	1/2	12.70	3/4-16	1.50	38	1.50	38		
AC-SFFX90-1010	50765-1010	1/2	12.70	7/8-14	1.50	38	1.50	38		
AC-SFFX90-1210	50765-1210	5/8	15.90	7/8-14	1.50	38	1.73	44		
AC-SFFX90-1212	50765-1212	5/8	15.90	1 1/16-14	1.50	38	1.73	44		



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)


Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.



# 'AC' (Crimp) FITTINGS

For use with GALAXY G4826 (5/16"-5/8") & G4867 (3/4") Hose

## SAE 45 Flare, Male



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-SFM-0606A	50780-0606A	5/16	7.90	5/8-18			1.89	48		
AC-SFM-0808A	50780-0808A	13/32	10.30	3/4-16			2.01	51		
AC-SFM-1010A	50780-1010A	1/2	12.70	7/8-14			2.32	59		
AC-SFM-1212A	50780-1212A	5/8	15.90	1 1/16-14			2.52	64		

## SAE 45 Flare, Male, 45 Elbow

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-SFM45-0606A	50783-0606A	5/16	7.90	5/8-18	1.50	38	1.06	27		
AC-SFM45-0808A	50783-0808A	13/32	10.30	3/4-16	1.73	44	1.26	32		
AC-SFM45-1010A	50783-1010A	1/2	12.70	7/8-14	2.01	51	1.50	38		
AC-SFM45-1212A	50783-1212A	5/8	15.90	1 1/16-14	2.52	64	2.36	60		

## SAE 45 Flare, Male, 90 Elbow

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
AC-SFM90-0606A	50785-0606A	5/16	7.90	5/8-18	0.75	19	0.83	21		
AC-SFM90-0808A	50785-0808A	13/32	10.30	3/4-16	0.98	25	0.94	24		
AC-SFM90-1010A	50785-1010A	1/2	12.70	7/8-14	1.26	32	1.26	32		
AC-SFM90-1212A	50785-1212A	5/8	15.90	1 1/16-14	1.38	35	1.50	38		



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# COOL CLIP™ FITTINGS

## For use with GALAXY® G4890 Hose

### Compressor Pad Block, R12 Valve/Switch, 90 Block Elbow

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-CB12VSR90-0808	54110-0808	13/32	10.30							
GC-CB12VSR90-1008	54110-1008	1/2	12.70							
GC-CB12VSR90-1208	54110-1208	5/8	15.90							

### Compressor Pad Block, R12 Valve/Switch Reversed, 90 Elbow

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-CB12VSR90-0808	54112-0808	13/32	10.30							
GC-CB12VSR90-1008	54112-1008	1/2	12.70							
GC-CB12VSR90-1208	54112-1208	5/8	15.90							

### Compressor O-Ring Tube, Female, 45 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-COTF45-0810	54133-0810	13/32	10.30	1-14	0.39	10	1.65	42		
GC-COTF45-1010	54133-1010	1/2	12.70	1-14	0.39	10	1.65	42		
GC-COTF45-1210	54133-1210	5/8	15.90	1-14	0.39	10	1.65	42		

### Compressor O-Ring Tube, Female, 90 Elbow

Similar to GC-COTF90B  
except bent tube, not block

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-COTF90-0810	54135-0810	13/32	10.30	1-14	0.91	23	1.77	45		
GC-COTF90-1010	54135-1010	1/2	12.70	1-14	0.91	23	1.77	45		
GC-COTF90-1210	54135-1210	5/8	15.90	1-14	0.91	23	1.77	45		

### Compressor O-Ring Tube, Female, 90 Block Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-COTF90B-0810	54137-0810	13/32	10.30	1-14	0.91	23	1.97	50		
GC-COTF90B-1010	54137-1010	1/2	12.70	1-14	0.91	23	1.97	50		
GC-COTF90B-1210	54137-1210	5/8	15.90	1-14	0.91	23	1.97	50		



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# COOL CLIP™ FITTINGS

## For use with GALAXY® G4890 Hose

### Compressor O-Ring Tube, Female, R134a Valve, 90 Block Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-COTF134V90B-0810	54145-0810	13/32	10.30	1-14	.91	23	1.97	50	.63	16
GC-COTF134V90B-1010	54145-1010	1/2	12.70	1-14	.91	23	1.97	50	.51	13
GC-COTF134V90B-1210	54145-1210	5/8	15.90	1-14	.91	23	1.97	50	.51	13

### Flareless Tube, Braze-On



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-FTBO-0606	54210-0606	5/16	7.90	3/8 Fitting			1.46	37		
GC-FTBO-0808	54210-0808	13/32	10.30	1/2 Fitting			1.46	37		
GC-FTBO-1010	54210-1010	1/2	12.70	5/8 Fitting			1.46	37		
GC-FTBO-1210	54210-1210	5/8	15.90	5/8 Fitting			1.46	37		
GC-FTBO-1212	54210-1212	5/8	15.90	3/4 Fitting			1.46	37		

### Flareless Tube, Male

Picture Not Available

DESCRIPTIVE #	PRODUCT #	INCH	MM	SIZE	INCH	MM	INCH	MM	INCH	MM
GC-FTM-0606	54230-0606	5/16	7.90	5/8-18			2.44	62		
GC-FTM-0608	54230-0608	5/16	7.90	3/4-16			2.44	62		
GC-FTM-0806	54230-0806	13/32	10.30	5/8-18			2.44	62		
GC-FTM-0808	54230-0808	13/32	10.30	3/4-16			2.56	65		
GC-FTM-0810	54230-0810	13/32	10.30	7/8-14			2.56	65		
GC-FTM-1008	54230-1008	1/2	12.70	3/4-16			2.80	71		
GC-FTM-1010	54230-1010	1/2	12.70	7/8-14			2.80	71		
GC-FTM-1210	54230-1210	5/8	15.90	7/8-14			3.31	84		
GC-FTM-1212	54230-1212	5/8	15.90	1 1/16-14			3.31	84		

### Flareless Tube, Male, 90 Block Elbow

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-FTM90B-0606	54235-0606	5/16	7.90	5/8-18	1.22	31	1.06	27		
GC-FTM90B-0608	54235-0608	5/16	7.90	3/4-16	1.22	31	1.06	27		
GC-FTM90B-0806	54235-0806	13/32	10.30	5/8-18	1.22	31	1.06	27		
GC-FTM90B-0808	54235-0808	13/32	10.30	3/4-16	1.73	44	1.26	32		
GC-FTM90B-0810	54235-0810	13/32	10.30	7/8-14	1.73	44	1.26	32		
GC-FTM90B-1008	54235-1008	1/2	12.70	3/4-16	1.73	44	1.26	32		
GC-FTM90B-1010	54235-1010	1/2	12.70	7/8-14	2.09	53	1.57	40		
GC-FTM90B-1210	54235-1210	5/8	15.90	7/8-14	2.52	64	2.28	58		
GC-FTM90B-1212	54235-1212	5/8	15.90	1 1/16-14	2.52	64	2.28	58		



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# COOL CLIP™ FITTINGS

## For use with GALAXY® G4890 Hose

### Flareless Tube, Male, Metric

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-FTMM-0608	54240-0608	5/16	7.90	5/8-18			2.44	62		
GC-FTMM-0812	54240-0812	13/32	10.30	3/4-16			2.56	65		
GC-FTMM-1015	54240-1015	1/2	12.70	7/8-14			3.31	84		

### Ford Spring Lock, Female

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-FSLF-0606A	54300-0606A	5/16	7.90	FSL-06			2.52	64		
GC-FSLF-0608A	54300-0608A	5/16	7.90	FSL-08			2.52	64		
GC-FSLF-0808A	54300-0808A	13/32	10.30	FSL-08			2.76	70		
GC-FSLF-1010A	54300-1010A	1/2	12.70	FSL-10			2.95	75		
GC-FSLF-1210A	54300-1210A	5/8	15.90	FSL-10			2.95	75		
GC-FSLF-1212A	54300-1212A	5/8	15.90	FSL-12			2.95	75		

### Ford Spring Lock, Female, 45 Elbow

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-FSLF45-0606A	54303-0606A	5/16	7.90	FSL-06	1.30	33	1.50	38		
GC-FSLF45-0608A	54303-0608A	5/16	7.90	FSL-08	1.30	33	1.50	38		
GC-FSLF45-0808A	54303-0808A	13/32	10.30	FSL-08	1.30	33	0.94	24		
GC-FSLF45-1010A	54303-1010A	1/2	12.70	FSL-10	1.42	36	1.26	32		
GC-FSLF45-1210A	54303-1210A	5/8	15.90	FSL-10	1.42	36	1.26	32		
GC-FSLF45-1212A	54303-1212A	5/8	15.90	FSL-12	1.42	36	1.26	32		

### Ford Spring Lock, Female, 90 Elbow

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-FSLF90-0606A	54305-0606A	5/16	7.90	FSL-06	2.13	54	1.61	41		
GC-FSLF90-0608A	54305-0608A	5/16	7.90	FSL-08	2.13	54	1.61	41		
GC-FSLF90-0808A	54305-0808A	13/32	10.30	FSL-08	2.44	62	1.73	44		
GC-FSLF90-1010A	54305-1010A	1/2	12.70	FSL-10	2.52	64	2.01	51		
GC-FSLF90-1210A	54305-1210A	5/8	15.90	FSL-10	2.52	64	2.01	51		
GC-FSLF90-1212A	54305-1212A	5/8	15.90	FSL-12	2.52	64	2.01	51		



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# COOL CLIP™ FITTINGS

## For use with GALAXY® G4890 Hose

### Ford Spring Lock, Male

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-FSLM-0606A	54330-0606A	5/16	7.90	FSL-06			2.36	60		
GC-FSLM-0608A	54330-0608A	5/16	7.90	FSL-08			2.36	60		
GC-FSLM-0808A	54330-0808A	13/32	10.30	FSL-08			2.36	60		
GC-FSLM-1010A	54330-1010A	1/2	12.70	FSL-10			2.64	67		
GC-FSLM-1210A	54330-1210A	5/8	15.90	FSL-10			2.64	67		
GC-FSLM-1212A	54330-1212A	5/8	15.90	FSL-12			2.76	70		

### Ford Spring Lock, Male, 45 Elbow

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-FSLM45-0606A	54333-0606A	5/16	7.90	FSL-06	1.30	33	1.50	38		
GC-FSLM45-0608A	54333-0608A	5/16	7.90	FSL-08	1.30	33	1.50	38		
GC-FSLM45-0808A	54333-0808A	13/32	10.30	FSL-08	1.26	32	0.94	24		
GC-FSLM45-1010A	54333-1010A	1/2	12.70	FSL-10	1.42	36	1.26	32		
GC-FSLM45-1210A	54333-1210A	5/8	15.90	FSL-10	1.42	36	1.26	32		
GC-FSLM45-1212A	54333-1212A	5/8	15.90	FSL-12	1.42	36	1.26	32		

### Ford Spring Lock, Male, 90 Elbow

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-FSLM90-0606A	54335-0606A	5/16	7.90	FSL-06	2.13	54	1.61	41		
GC-FSLM90-0608A	54335-0608A	5/16	7.90	FSL-08	2.13	54	1.61	41		
GC-FSLM90-0808A	54335-0808A	13/32	10.30	FSL-08	2.44	62	1.73	44		
GC-FSLM90-1010A	54335-1010A	1/2	12.70	FSL-10	2.52	64	2.01	51		
GC-FSLM90-1210A	54335-1210A	5/8	15.90	FSL-10	2.52	64	2.01	51		
GC-FSLM90-1212A	54335-1212A	5/8	15.90	FSL-12	2.52	64	2.01	51		

### Hose Mender



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-HM-0606	54350-0606	5/16	7.90				1.46	37		
GC-HM-0608	54350-0608	5/16	7.90				1.46	37		
GC-HM-0808	54350-0808	13/32	10.30				1.46	37		
GC-HM-0810	54350-0810	13/32	10.30				1.46	37		
GC-HM-1010	54350-1010	1/2	12.70				1.46	37		
GC-HM-1210	54350-1210	5/8	15.90				1.46	37		
GC-HM-1212	54350-1212	5/8	15.90				1.46	37		



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# COOL CLIP™ FITTINGS

## For use with GALAXY® G4890 Hose

### Hose Mender, 90 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-HM90-0606	54355-0606	5/16	7.90		.59	15	.59	15		
GC-HM90-0808	54355-0808	13/32	10.30		.79	20	.79	20		
GC-HM90-1010	54355-1010	1/2	12.70		.98	25	.98	25		
GC-HM90-1212	54355-1212	5/8	15.90		1.18	30	1.18	30		

### Hose Mender, 180 Elbow

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-HM180-0606	54360-0606	5/16	7.90		1.97	50	2.13	54		
GC-HM180-0808	54360-0808	13/32	10.30		2.36	60	2.13	54		
GC-HM180-1010	54360-1010	1/2	12.70		2.76	70	2.48	63		
GC-HM180-1212	54360-1212	5/8	15.90		3.15	80	3.15	80		

### Hose Mender, R12 Valve

Same as GC-HM134V  
except with R12 Valve

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-HM12V-0606	54365-0606	5/16	7.90				1.46	37	1/4	6.35
GC-HM12V-0808	54365-0808	13/32	10.30				1.46	37	1/4	6.35
GC-HM12V-1010	54365-1010	1/2	12.70				1.46	37	1/4	6.35
GC-HM12V-1212	54365-1212	5/8	15.90				1.46	37	1/4	6.35

### Hose Mender, R134a Valve



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-HM134V-0606	54370-0606	5/16	7.90				1.46	37	0.63	16
GC-HM134V-0808	54370-0808	13/32	10.30				1.46	37	0.63	16
GC-HM134V-1010	54370-1010	1/2	12.70				1.46	37	0.51	13
GC-HM134V-1212	54370-1212	5/8	15.90				1.46	37	0.51	13

### Hose Mender, with Sight Glass

Same as GC-HM with sight glass

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-HMSG-0606	54375-0606	5/16	7.90				1.77	45		



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# COOL CLIP™ FITTINGS

## For use with GALAXY® G4890 Hose

### Hose Mender, Tee



DESCRIPTIVE #	PRODUCT #	HOSE ID 1&2		HOSE ID 3		DROP		LENGTH		VALVE	
		INCH	MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM
GC-HMT-0606	54380-0606	5/16	7.90	5/16	7.90	0.87	22	1.73	44		
GC-HMT-0808	54380-0808	13/32	10.30	13/32	10.30	0.94	24	1.89	48		
GC-HMT-1010	54380-1010	1/2	12.70	1/2	12.70	1.38	35	2.01	51		
GC-HMT-1210	54380-1210	5/8	15.90	1/2	12.70	1.38	35	2.01	51		
GC-HMT-1212	54380-1212	5/8	15.90	5/8	15.90	1.38	35	2.24	57		

### O-Ring Face Seal, Female, Swivel



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OFFX-0606	54430-0606	5/16	7.90	11/16-16			1.42	36		
GC-OFFX-0808	54430-0808	13/32	10.30	13/16-16			1.61	41		
GC-OFFX-1010	54430-1010	1/2	12.70	1-14			2.13	54		
GC-OFFX-1212	54430-1212	5/8	15.90	1 3/16-12			2.36	60		

### O-Ring Face Seal, Female, Swivel, 90 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OFFX90-0606	54435-0606	5/16	7.90	11/16-16	1.14	29	0.59	15		
GC-OFFX90-0808	54435-0808	13/32	10.30	13/16-16	1.34	34	0.79	20		
GC-OFFX90-1010	54435-1010	1/2	12.70	1-14	1.57	40	0.98	25		
GC-OFFX90-1212	54435-1212	5/8	15.90	1 3/16-12	1.81	46	1.18	30		

### O-Ring Insert Male



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OIM-0606	54500-0606	5/16	7.90	5/8-18			2.44	62		
GC-OIM-0808	54500-0808	13/32	10.30	3/4-16			2.56	65		
GC-OIM-1010	54500-1010	1/2	12.70	7/8-14			1.77	45		
GC-OIM-1210	54500-1210	5/8	15.90	7/8-14			1.77	45		
GC-OIM-1212	54500-1212	5/8	15.90	1 1/16-14			2.95	75		



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# COOL CLIP™ FITTINGS

## For use with GALAXY® G4890 Hose

### O-Ring Insert Male, 45 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OIM45-0606	54503-0606	5/16	7.90	5/8-18	0.75	19	0.83	21		
GC-OIM45-0808	54503-0808	13/32	10.30	3/4-16	0.94	24	0.94	24		
GC-OIM45-1010	54503-1010	1/2	12.70	7/8-14	1.26	32	1.26	32		
GC-OIM45-1212	54503-1212	5/8	15.90	1 1/16-14	1.38	35	1.42	36		

### O-Ring Insert Male, 90 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OIM90-0606	54505-0606	5/16	7.90	5/8-18	1.38	35	1.77	45		
GC-OIM90-0808	54505-0808	13/32	10.30	3/4-16	1.73	44	1.26	32		
GC-OIM90-1010	54505-1010	1/2	12.70	7/8-14	2.17	55	1.97	50		
GC-OIM90-1210	54505-1210	5/8	15.90	7/8-14	2.17	55	1.97	50		
GC-OIM90-1212	54505-1212	5/8	15.90	1 1/16-14	2.76	70	1.97	50		

### O-Ring Insert Male, Bulkhead



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OIMB-0606	54515-0606	5/16	7.90	5/8-18			2.80	71		
GC-OIMB-0808	54515-0808	13/32	10.30	3/4-16			2.80	71		
GC-OIMB-1010	54515-1010	1/2	12.70	7/8-14			2.80	71		

### O-Ring Insert Male, Bulkhead, 90 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OIMB90-0606	54520-0606	5/16	7.90	5/8-18	2.13	54	1.61	41		
GC-OIMB90-0808	54520-0808	13/32	10.30	3/4-16	2.44	62	1.73	44		
GC-OIMB90-1010	54520-1010	5/8	15.90	7/8-14	2.52	64	2.01	51		



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.



# COOL CLIP™ FITTINGS

## For use with GALAXY® G4890 Hose

### O-Ring Insert Male, R134a Valve

Same as GC-OIM with  
134a Valve

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OIM134V-0606	54530-0606	5/16	7.90	5/8-18			2.44	62	0.63	16
GC-OIM134V-0808	54530-0808	13/32	10.30	3/4-16			2.56	65	0.63	16
GC-OIM134V-1010	54530-1010	1/2	12.70	7/8-14			1.77	45	0.51	13
GC-OIM134V-1212	54530-1212	5/8	15.90	1 1/16-14			2.95	75	0.51	13

### O-Ring Insert Male, R134a Valve, 90 Elbow

Same as GC-OIM90 with  
134a Valve

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OIM134V90-0606	54535-0606	5/16	7.90	5/8-18	1.38	35	1.77	45	0.63	16
GC-OIM134V90-0808	54535-0808	13/32	10.30	3/4-16	1.73	44	1.26	32	0.63	16
GC-OIM134V90-1010	54535-1010	1/2	12.70	7/8-14	2.17	55	1.97	50	0.51	13

### O-Ring Tube, Female, Swivel



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OTF-0605	54600-0605	5/16	7.90	9/16-18			1.06	27		
GC-OTF-0606	54600-0606	5/16	7.90	5/8-18			1.06	27		
GC-OTF-0608	54600-0608	5/16	7.90	3/4-16			1.22	31		
GC-OTF-0806	54600-0806	13/32	10.30	5/8-18			1.22	31		
GC-OTF-0808	54600-0808	13/32	10.30	3/4-16			1.22	31		
GC-OTF-1008	54600-1008	1/2	12.70	3/4-16			1.22	31		
GC-OTF-1010	54600-1010	1/2	12.70	7/8-14			1.61	41		
GC-OTF-1012	54600-1012	1/2	12.70	1 1/16-14			1.73	44		
GC-OTF-1210	54600-1210	5/8	15.90	7/8-14			1.61	41		
GC-OTF-1212	54600-1212	5/8	15.90	1 1/16-14			1.73	44		

### O-Ring Tube, Female, Swivel, 45 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OTF45-0606	54603-0606	5/16	7.90	5/8-18	0.55	14	0.67	17		
GC-OTF45-0806	54603-0806	13/32	10.30	5/8-18	0.55	14	0.67	17		
GC-OTF45-0808	54603-0808	13/32	10.30	3/4-16	0.59	15	1.77	45		
GC-OTF45-1008	54603-1008	1/2	12.70	3/4-16	0.59	15	1.77	45		
GC-OTF45-1010	54603-1010	1/2	12.70	7/8-14	0.67	17	1.77	45		
GC-OTF45-1210	54603-1210	5/8	15.90	7/8-14	0.67	17	1.77	45		
GC-OTF45-1212	54603-1212	5/8	15.90	1 1/16-14	1.18	30	1.77	45		



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# COOL CLIP™ FITTINGS

## For use with GALAXY® G4890 Hose

### O-Ring Tube, Female, Swivel, 90 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD	DROP		LENGTH		VALVE	
		INCH	MM	SIZE	INCH	MM	INCH	MM	INCH	MM
GC-OTF90-0605	54605-0605	5/16	7.90	9/16-18	1.26	32	1.10	28		
GC-OTF90-0606	54605-0606	5/16	7.90	5/8-18	1.26	32	1.10	28		
GC-OTF90-0608	54605-0608	5/16	7.90	3/4-16	1.42	36	1.42	36		
GC-OTF90-0806	54605-0806	13/32	10.30	5/8-18	1.65	42	1.81	46		
GC-OTF90-0808	54605-0808	13/32	10.30	3/4-16	1.42	36	1.42	36		
GC-OTF90-1008	54605-1008	1/2	12.70	3/4-16	1.42	36	1.42	36		
GC-OTF90-1010	54605-1010	1/2	12.70	7/8-14	1.65	42	1.81	46		
GC-OTF90-1012	54605-1012	1/2	12.70	1 1/16-14	1.77	45	2.05	52		
GC-OTF90-1210	54605-1210	5/8	15.90	7/8-14	1.65	42	1.81	46		
GC-OTF90-1212	54605-1212	5/8	15.90	1 1/16-14	1.77	45	2.05	52		

### O-Ring Tube, Female, Swivel, 90 Block Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD	DROP		LENGTH		VALVE	
		INCH	MM	SIZE	INCH	MM	INCH	MM	INCH	MM
GC-OTF90B-0808	54610-0808	13/32	10.30	3/4-16	0.91	23	1.97	50		
GC-OTF90B-1010	54610-1010	1/2	12.70	7/8-14	0.94	24	1.97	50		
GC-OTF90B-1210	54610-1210	5/8	15.90	7/8-14	0.94	24	1.97	50		

### O-Ring Tube, Female, Swivel, 180 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD	DROP		LENGTH		VALVE	
		INCH	MM	SIZE	INCH	MM	INCH	MM	INCH	MM
GC-OTF180-0606	54615-0606	5/16	7.90	5/8-18	1.97	50	2.13	54		
GC-OTF180-0808	54615-0808	13/32	10.30	3/4-16	2.36	60	2.13	54		
GC-OTF180-1212	54615-1212	5/8	15.90	1 1/16-14	3.15	80	3.15	80		

### O-Ring Tube, Female, Swivel, R12 Valve

Same as GC-OTF with  
R12 Valve

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD	DROP		LENGTH		VALVE	
		INCH	MM	SIZE	INCH	MM	INCH	MM	INCH	MM
GC-OTF12V-0606	54650-0606	5/16	7.90	5/8-18			1.06	27	1/4	6.35
GC-OTF12V-0808	54650-0808	13/32	10.30	3/4-16			1.22	31	1/4	6.35
GC-OTF12V-1010	54650-1010	1/2	12.70	7/8-14			1.61	41	1/4	6.35



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# COOL CLIP™ FITTINGS

## For use with GALAXY® G4890 Hose

### O-Ring Tube, Female, Swivel, R12 Valve, 90 Elbow

Same as GC-OTF 90  
with R12 Valve

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OTF12V90-0606	54655-0606	5/16	7.90	5/8-18	1.26	32	1.10	28	1/4	6.35
GC-OTF12V90-0808	54655-0808	13/32	10.30	3/4-16	1.42	36	1.42	36	1/4	6.35
GC-OTF12V90-1010	54655-1010	1/2	12.70	7/8-14	1.65	42	1.81	46	1/4	6.35
GC-OTF12V90-1210	54655-1210	5/8	15.90	7/8-14	1.50	38	1.50	38	1/4	6.35

### O-Ring Tube, Female, Swivel, R134a Valve



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OTF134V-0606	54660-0606	5/16	7.90	5/8-18			1.06	27	0.63	16
GC-OTF134V-0808	54660-0808	13/32	10.30	3/4-16			1.22	31	0.63	16
GC-OTF134V-1010	54660-1010	1/2	12.70	7/8-14			1.61	41	0.51	13
GC-OTF134V-1210	54660-1210	5/8	15.90	7/8-14			1.61	41	0.51	13
GC-OTF134V-1212	54660-1212	5/8	15.90	1 1/16-14			1.73	44	0.51	13
GC-OTF134VHS-1010	54675-1010	5/8	15.90	7/8-14			1.61	41	0.63	16

### O-Ring Tube, Female, Swivel, R134a Valve, 45 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OTF134V45-0606	54663-0606	5/16	7.90	5/8-18	0.55	14	0.98	25	0.63	16
GC-OTF134V45-0808	54663-0808	13/32	10.30	3/4-16	0.59	15	1.02	26	0.63	16
GC-OTF134V45-1010	54663-1010	1/2	12.70	7/8-14	0.67	17	1.06	27	0.51	13
GC-OTF134V45-1210	54663-1210	5/8	15.90	7/8-14	0.67	17	1.06	27	0.51	13
GC-OTF134V45-1212	54663-1212	5/8	15.90	1 1/16-14	0.94	24	1.77	45	0.51	13

### O-Ring Tube, Female, Swivel, R134a Valve, 90 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OTF134V90-0606	54665-0606	5/16	7.90	5/8-18	1.26	32	1.10	28	0.63	16
GC-OTF134V90-0806	54665-0806	13/32	10.30	5/8-18	1.26	32	1.10	28	0.63	16
GC-OTF134V90-0808	54665-0808	13/32	10.30	3/4-16	1.42	36	1.42	36	0.63	16
GC-OTF134V90-1010	54665-1010	1/2	12.70	7/8-14	1.65	42	1.81	46	0.51	13
GC-OTF134V90-1210	54665-1210	5/8	15.90	7/8-14	1.65	42	1.81	46	0.51	13
GC-OTF134V90-1212	54665-1212	5/8	15.90	1 1/16-14	1.77	45	2.05	52	0.51	13



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# COOL CLIP™ FITTINGS

## For use with GALAXY® G4890 Hose

### O-Ring Tube, Male, Swivel



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OTM-0606	54700-0606	5/16	7.90	5/8-18			1.14	29		
GC-OTM-0607	54700-0607	5/16	7.90	1 1/16-16			1.14	29		
GC-OTM-0608	54700-0608	5/16	7.90	3/4-18			1.18	30		
GC-OTM-0806	54700-0806	13/32	10.30	5/8-18			1.18	30		
GC-OTM-0808	54700-0808	13/32	10.30	3/4-18			1.73	44		
GC-OTM-1010	54700-1010	1/2	12.70	7/8-18			1.81	46		
GC-OTM-1012	54700-1012	1/2	12.70	1 1/16-16			1.81	46		
GC-OTM-1210	54700-1210	5/8	15.90	7/8-18			1.81	46		
GC-OTM-1212	54700-1212	5/8	15.90	1 1/16-16			2.05	52		

### O-Ring Tube, Male, Swivel, 45 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OTM45-0606	54703-0606	5/16	7.90	5/8-18	0.87	22	0.79	20		
GC-OTM45-0608	54703-0608	5/16	7.90	3/4-18	0.87	22	0.79	20		
GC-OTM45-0806	54703-0806	13/32	10.30	5/8-18	0.87	22	0.79	20		
GC-OTM45-0808	54703-0808	13/32	10.30	3/4-18	0.98	25	1.06	27		
GC-OTM45-1010	54703-1010	1/2	12.70	7/8-18	1.06	27	1.30	33		
GC-OTM45-1210	54703-1210	5/8	15.90	7/8-18	1.18	30	1.46	37		
GC-OTM45-1212	54703-1212	5/8	15.90	1 1/16-16	1.18	30	1.46	37		

### O-Ring Tube, Male, Swivel, 90 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OTM90-0606	54705-0606	5/16	7.90	5/8-18	1.46	37	1.02	26		
GC-OTM90-0608	54705-0608	5/16	7.90	3/4-18	1.46	37	1.02	26		
GC-OTM90-0806	54705-0806	13/32	10.30	5/8-18	1.46	37	1.02	26		
GC-OTM90-0808	54705-0808	13/32	10.30	3/4-18	1.77	45	1.34	34		
GC-OTM90-1010	54705-1010	1/2	12.70	7/8-18	2.05	52	1.65	42		
GC-OTM90-1012	54705-1012	1/2	12.70	1 1/16-16	2.05	52	1.65	42		
GC-OTM90-1210	54705-1210	5/8	15.90	7/8-18	2.05	52	1.65	42		
GC-OTM90-1212	54705-1212	5/8	15.90	1 1/16-16	2.36	60	1.89	48		

### O-Ring Tube, Male, Swivel, Long Pilot



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OTMLP-0606	54720-0606	5/16	7.90	5/8-18			1.14	29		
GC-OTMLP-0808	54720-0808	13/32	10.30	3/4-18			1.73	44		
GC-OTMLP-1010	54720-1010	1/2	12.70	7/8-18			1.81	46		
GC-OTMLP-1210	54720-1210	5/8	15.90	7/8-18			1.81	46		



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# COOL CLIP™ FITTINGS

## For use with GALAXY® G4890 Hose

### O-Ring Tube , Male, Swivel, R134a Valve

Same as GC-OTM with  
134a Valve

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OTM134V-0606	54730-0606	5/16	7.90	5/8-18			1.06	27	0.63	16
GC-OTM134V-0808	54730-0808	13/32	10.30	3/4-18			1.22	31	0.63	16
GC-OTM134V-1010	54730-1010	1/2	12.70	7/8-18			1.61	41	0.51	13
GC-OTM134V-1210	54730-1210	5/8	15.90	7/8-18			1.73	44	0.51	13
GC-OTM134V-1212	54730-1212	5/8	15.90	1 1/16-16			1.73	44	0.51	13

### O-Ring Tube, Male, Swivel, R134a Valve, 90 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-OTM134V90-1010	54735-1010	1/2	12.70	7/8-18	2.05	52	1.65	42	0.51	13
GC-OTM134V90-1210	54735-1210	5/8	15.90	7/8-18	2.05	52	1.65	42	0.51	13

### SAE 45 Flare, Female, Swivel



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-SFFX-0606	54760-0606	5/16	7.90	5/8-18			1.38	35		
GC-SFFX-0608	54760-0608	5/16	7.90	3/4-16			1.38	35		
GC-SFFX-0806	54760-0806	13/32	10.30	5/8-18			1.77	45		
GC-SFFX-0808	54760-0808	13/32	10.30	3/4-16			1.77	45		
GC-SFFX-1008	54760-1008	1/2	12.70	3/4-16			1.77	45		
GC-SFFX-1010	54760-1010	1/2	12.70	7/8-14			1.97	50		
GC-SFFX-1210	54760-1210	5/8	15.90	7/8-14			1.97	50		
GC-SFFX-1212	54760-1212	5/8	15.90	1 1/16-14			2.17	55		

### SAE 45 Flare, Female, Swivel, 45 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-SFFX45-0606	54763-0606	5/16	7.90	5/8-18	0.79	20	2.17	55		
GC-SFFX45-0608	54763-0608	5/16	7.90	3/4-16	0.79	20	2.17	55		
GC-SFFX45-0806	54763-0806	13/32	10.30	5/8-18	0.79	20	2.17	55		
GC-SFFX45-0808	54763-0808	13/32	10.30	3/4-16	0.79	20	2.36	60		
GC-SFFX45-1008	54763-1008	1/2	12.70	3/4-16	0.79	20	2.36	60		
GC-SFFX45-1010	54763-1010	1/2	12.70	7/8-14	0.87	22	2.36	60		
GC-SFFX45-1210	54763-1210	5/8	15.90	7/8-14	0.87	22	2.36	60		
GC-SFFX45-1212	54763-1212	5/8	15.90	1 1/16-14	0.87	22	2.36	60		



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# COOL CLIP™ FITTINGS

## For use with GALAXY® G4890 Hose

### SAE 45 Flare, Female, Swivel, 90 Elbow



DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-SFFX90-0606	54765-0606	5/16	7.90	5/8-18	1.18	30	1.38	35		
GC-SFFX90-0608	54765-0608	5/16	7.90	3/4-16	1.18	30	1.38	35		
GC-SFFX90-0806	54765-0806	13/32	10.30	5/8-18	1.18	30	1.38	35		
GC-SFFX90-0808	54765-0808	13/32	10.30	3/4-16	1.77	45	1.38	35		
GC-SFFX90-1008	54765-1008	1/2	12.70	3/4-16	1.77	45	1.38	35		
GC-SFFX90-1010	54765-1010	1/2	12.70	7/8-14	1.77	45	1.77	45		
GC-SFFX90-1210	54765-1210	5/8	15.90	7/8-14	1.77	45	1.77	45		
GC-SFFX90-1212	54765-1212	5/8	15.90	1 1/16-14	1.77	45	1.77	45		

### SAE 45 Flare, Male

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-SFM-0606A	54780-0606A	5/16	7.90	5/8-18			1.38	35		
GC-SFM-0808A	54780-0808A	13/32	10.30	3/4-16			1.38	35		
GC-SFM-1010A	54780-1010A	1/2	12.70	7/8-14			1.50	38		
GC-SFM-1212A	54780-1212A	5/8	15.90	1 1/16-14			1.73	44		

### SAE 45 Flare, Male, 45 Elbow

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-SFM45-0606A	54783-0606A	5/16	7.90	5/8-18	0.75	19	1.38	35		
GC-SFM45-0808A	54783-0808A	13/32	10.30	3/4-16	0.94	24	1.38	35		
GC-SFM45-1010A	54783-1010A	1/2	12.70	7/8-14	1.26	32	1.77	45		
GC-SFM45-1212A	54783-1212A	5/8	15.90	1 1/16-14	1.38	35	1.77	45		

### SAE 45 Flare, Male, 90 Elbow

Picture Not Available

DESCRIPTIVE #	PRODUCT #	HOSE ID		THREAD SIZE	DROP		LENGTH		VALVE	
		INCH	MM		INCH	MM	INCH	MM	INCH	MM
GC-SFM90-0606A	54785-0606A	5/16	7.90	5/8-18	1.18	30	1.38	35		
GC-SFM90-0808A	54785-0808A	13/32	10.30	3/4-16	1.77	45	1.38	35		
GC-SFM90-1010A	54785-1010A	1/2	12.70	7/8-14	1.77	45	1.77	45		
GC-SFM90-1212A	54785-1212A	5/8	15.90	1 1/16-14	1.77	45	1.77	45		




One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# A/C ADAPTERS

## O-Ring Tube Compressor Female to O-Ring Insert Male, 90 Elbow, w/R134a Valve



Descriptive #	Product #	Thread Size OTCF	Thread Size OIM
AC-OTCF10-OIM08-90-134V	50900-1008	1-14	3/4-16
AC-OTCF10-OIM10-90-134V	50900-1010	1-14	7/8-14

## O-Ring Tube Female to O-Ring Insert Male w/R12 Valve

Same as AC-OTF-OIM-134V  
except with R12 Valve

Descriptive #	Product #	Thread Size OTF	Thread Size OIM
AC-OTF06-OIM06-12V	50910-0606	5/8-18	5/8-18
AC-OTF08-OIM08-12V	50910-0808	3/4-16	3/4-16
AC-OTF10-OIM10-12V	50910-1010	7/8-14	7/8-14
AC-OTF12-OIM12-12V	50910-1212	1 1/16-14	1 1/16-14

## O-Ring Tube Female to O-Ring Insert Male, 90 Elbow w/R12 Valve

Picture Not Available

Descriptive #	Product #	Thread Size OTF	Thread Size OIM
AC-OTF06-OIM06-90-12V	50915-0606	5/8-18	5/8-18
AC-OTF08-OIM08-90-12V	50915-0808	3/4-16	3/4-16
AC-OTF10-OIM10-90-12V	50915-1010	7/8-14	7/8-14
AC-OTF12-OIM12-90-12V	50915-1212	1 1/16-14	1 1/16-14




One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# A/C ADAPTERS

## O-Ring Tube Female to O-Ring Insert Male w/R134a Valve



Descriptive #	Product #	Thread Size OTF	Thread Size OIM
AC-OTF06-OIM06-134V	50920-0606	5/8-18	5/8-18
AC-OTF08-OIM08-134V	50920-0808	3/4-16	3/4-16
AC-OTF10-OIM10-134V	50920-1010	7/8-14	7/8-14
AC-OTF12-OIM12-134V	50920-1212	1 1/16-14	1 1/16-14

## O-Ring Tube Female to O-Ring Insert Male, 90 Elbow w/R134a Valve

Picture Not Available

Descriptive #	Product #	Thread Size OTF	Thread Size OIM
AC-OTF06-OIM06-90-134V	50925-0606	5/8-18	5/8-18
AC-OTF08-OIM08-90-134V	50925-0808	3/4-16	3/4-16
AC-OTF10-OIM10-90-134V	50925-1010	7/8-14	7/8-14
AC-OTF12-OIM12-90-134V	50925-1212	1 1/16-14	1 1/16-14



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.



# A/C CLIP FITTING ACCESSORIES

## Flareless Tube Nuts

Descriptive #	Product #	Thread Size	Tube O.D.	
			INCH	
AC-FTN-0006	50250-0006	5/8-18	3/8	
AC-FTN-0008	50250-0008	3/4-16	1/2	
AC-FTN-0010	50250-0010	7/8-14	5/8	
AC-FTN-0012	50250-0012	1 1/16-14	3/4	

## Flareless Tube Sleeves

Descriptive #	Product #	Thread Size	Tube O.D.	
			INCH	
AC-FTS-0006	50255-0006		3/8	
AC-FTS-0008	50255-0008		1/2	
AC-FTS-0010	50255-0010		5/8	
AC-FTS-0012	50255-0012		3/4	

## Flareless Tube Sleeves, Metric

Descriptive #	Product #	Thread Size	Tube O.D.	
			MM	
AC-FTSM-0008	50260-0008		8	
AC-FTSM-0012	50260-0012		12	
AC-FTSM-0015	50260-0015		14.5	

## Inline Orifice Tubes

Descriptive #	Product #	Orifice Tube O.D.		Orifice Tube Length		Description
		INCH	MM	INCH	MM	
AC-ILOTORA-0057	50401-0057	.057	1.4	3.50	88.9	Inline Orifice Tube, Ford, Orange
AC-ILOTRED-0062	50401-0062	.062	1.6	3.50	88.9	Inline Orifice Tube, Ford, Red
AC-ILOTBLU-0072	50401-0072	.072	1.8	3.50	88.9	Inline Orifice Tube, Ford, Blue
AC-ILOTBLK-0072	50402-0072	.072	1.8	3.50	88.9	Inline Orifice Tube, GM, Black
AC-ILOTWHI-0072	50403-0072	.072	1.8	3.50	88.9	Inline Orifice Tube, GM, White

## O-Ring, for Ford Spring Lock

Descriptive #	Product #	O-RING ID				
		INCH	MM			
GC-OFSL-0006	54450-0006	3/8	9.5			
GC-OFSL-0008	54450-0008	1/2	12.7			
GC-OFSL-0010	54450-0010	5/8	15.9			
GC-OFSL-0012	54450-0012	3/4	19.1			



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)


Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# A/C FITTING ACCESSORIES

## O-Ring, for Switch

Descriptive #	Product #	O-RING ID	
		INCH	MM
GC-OSWCH-0006	54455-0006	3/8	9.5

## O-Ring, for Tube Fittings




Descriptive #	Product #	O-RING ID		O-RING Thickness	
		INCH	MM	INCH	MM
AC-OTUBE-0006	50460-0006	.30	7.6	0.07	1.8
AC-OTUBE-0008	50460-0008	.43	10.9	0.07	1.8
AC-OTUBE-0010	50460-0010	.55	14.0	0.07	1.8
AC-OTUBE-0012	50460-0012	.68	17.3	0.07	1.8

## Sealing Washers


Descriptive #	Product #	I. D.	Product Description
		INCH	
AC-SWA-0012	50800-0012	3/4	Sealing Washer, Accumulator
AC-SWCN-0010	50803-0010	5/8	Sealing Washer, Compressor, Narrow
AC-SWCN-0012	50803-0012	3/4	Sealing Washer, Compressor, Narrow
AC-SWCW-0010	50805-0010	5/8	Sealing Washer, Compressor, Wide

## Valve Adapters



Descriptive #	Product #	R12	R134a	Product Description
		Thread Size	MM	
AC-VA12V3/16-134V16	50820-0001	3/8-24	16mm	Converts R12 to R134a valve
AC-VA12V1/4-134V13	50820-0002	7/16-20	13mm	Converts R12 to R134a valve
AC-VA12V1/4-134V16	50820-0003	7/16-20	16mm	Converts R12 to R134a valve

## Valve Caps



Descriptive #	Product #	Valve	Valve
		Style	Size
AC-VC12V-0001	50830-0001	R12	1/4 in
AC-VC134VHS-0002	50830-0002	R134a H.S.	16mm
AC-VC134VLS-0003	50830-0003	R134a L.S.	13mm

# A/C FITTING ACCESSORIES

## Valve Core



Descriptive #	Product #	Thread	
		Size	
AC-VCORE-0001	50835-0001	.210x36	

## Metal Clip



Descriptive #	Product #	HOSE ID	
		INCH	MM
GC-CLIP-0006	54850-0006	5/16	7.9
GC-CLIP-0008	54850-0008	13/32	10.3
GC-CLIP-0010	54850-0010	1/2	12.7
GC-CLIP-0012	54850-0012	5/8	15.9

## Plastic Clip Holder



Descriptive #	Product #	HOSE ID	
		INCH	MM
GC-CLIPHLDR-0006	54855-0006	5/16	7.9
GC-CLIPHLDR-0008	54855-0008	13/32	10.3
GC-CLIPHLDR-0010	54855-0010	1/2	12.7
GC-CLIPHLDR-0012	54855-0012	5/8	15.9

## Clip Pliers



Descriptive #	Product #	Product Description
GC-PLIERS-0001	54860-0001	Clip Pliers for assembly of Cool Clip Fittings

## Hose Cutting Tool & Replacement Blades



Descriptive #	Product #	Product Description
65090 HCT	65090	Hose Cutting Tool for G4890 Hose
65091 HCTRB	65091	Hose Cutting Tool Replacement Blades - 2/Pkg



One Source, One System, One Solution.

[www.hydraulics.goodyear.com](http://www.hydraulics.goodyear.com)

Information in this catalog supersedes all previously printed material and is current as of April 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online.

# Notes

# Notes

# Notes

# Notes



U.S.A.

1-800-468-4046  
FAX 1-800-762-4017

CANADA

1-888-275-4397  
FAX 1-888-464-4397

GOODYEARINDUSTRIALPRODUCTS.COM



**Warning – Goodyear Hose and Fitting Compatibility**

Goodyear hose and Goodyear fittings have been engineered and designed as a complete hose assembly system. Each component of the hose assembly system is compatible with other parts of the system to which it relates. Component compatibility, along with the use of quality components, ensures the production of reliable hose assemblies, when assembled properly. The use or intermixing of fittings and hose not specifically engineered and designed for use with each other is not recommended and may result in the production of unsafe or unreliable hose assemblies. This can result in hose leakage, hose and fitting separation, or other failures, which can cause serious bodily injury or property damage from spraying fluids or flying projectiles. The Goodyear warranty is limited to apply only when Goodyear fittings and a compatible Goodyear hose are assembled with approved Goodyear Clip pliers, or Goodyear crimpers to Goodyear crimp specifications.

06GHYD010 - 06/06