Fuel Fill Hose/Marine Exhaust Hose

Application: Designed for use with gasoline, methanol, ethanol, and diesel fuel in marine applications such as fuel filler neck, fuel tank vent and exhaust hose.

Construction

Tube: Black Chemigum (Nitrile)
Reinforcement: 2-ply synthetic with helix wire
Cover: Black Chemivic (Nitrile/PVC) wrapped finish

Temperature Range F & C: -25˚F to +212˚F (-30˚C to +100˚C)
SAE Specifications: J1527 USCG Type A, Class 2, Style R2
USCG Specifications: CFR33 183 Subpart J, Fire resistance Type A
Goodyear Engineered Products Specifications: 543990 543991 543992
Length: See table below.
Brand Layline: Goodyear HI-MILER® Wire Inserted USCG Type A2 SAE J1527, P/N ID.
Installation: See selection of Goodyear EP clamps

Warning: Do not use hose reducers with this hose unless they meet the same fuel resistant specifications.

Part Number	ID(in.)	OD(in.)	Length(ft.)	Working Pressure(PSI)	Min Bend Radius(in.)	Vacuum HG(in.)	Weight (lbs./ft.)
59310	5/8	63/64	30	35	1.8	20	0.32
59312	3/4	1 7/64	30	35	2.3	20	0.37
59314	7/8	1 15/64	30	35	2.8	20	0.42
59316	1	1 11/64	30	35	3.0	20	0.47
59318	1 1/8	1 1/2	30	18	2.3	20	0.53
59320	1 1/4	1 39/64	30	18	2.8	20	0.58
58524	1 1/2	1 53/64	4	18	4.5	20	0.66
59324	1 1/2	1 27/64	30	18	4.5	20	0.69
59328	1 3/4	2 1/8	30	18	5.0	20	0.80
58530	1 7/8	2 1/4	4	18	5.5	20	0.85
59330	1 7/8	2 1/4	30	18	5.5	20	0.85
58532	2	2 3/8	4	18	6.0	20	0.90
59332	2	2 3/8	30	18	6.0	20	0.90
59034	2 1/8	2 1/2	10	18	6.3	20	0.95
58536	2 1/4	2 39/64	4	18	6.8	20	1.00
59036	2 1/4	2 39/64	10	18	6.8	20	1.00
59038	2 3/8	2 3/4	10	18	7.0	20	1.05
58540	2 1/2	2 57/64	4	18	7.5	20	1.22
59040	2 1/2	2 57/64	10	18	7.5	20	1.22
59048	3	3 7/16	10	18	9.0	20	1.61
59056	3 1/2	3 63/64	10	18	10.5	20	1.94
59072	4 1/2	5 1/32	10	18	13.5	20	2.88

For clamps see page 47.

GOODYEAR RUBBER PRODUCTS INC.
Call Toll Free: 1-866-711-4673
WebSales@GoodyearRubberProducts.com
We Ship World Wide