Hose Selector Guide - by application

| Series | Trademark | Hose Application / Construction / Selector Guide | | Tube | Cover | Size | Pressure | Temp | Page |
|--------|-----------------|--|------------------------------|----------------|------------------|---------------|----------------|-------------------|------|
| | | | | | | Range (in) | Range (psi) | Range (°F) | No. |
| SM382 | HARVEST PLUS+ | Non-fatty, non-oily foods | Crush resistant | Chlorobutyl | EPDM | 1-1/2 - 4 | 200-250 | -40/+225 | 109 |
| SP330 | LIGHT-N-BRIGHT™ | Non-fatty, non-oily foods | PVC external helix | Chlorobutyl | Synthetic rubber | 2 - 4 | 150 | -40/+200 | 110 |
| SP100 | | | PVC banding coil | n/a | n/a | 2 - 6 | n/a | n/a | 111 |
| XSP100 | | | PVC abrasion coil | n/a | n/a | 2 - 6 | n/a | n/a | 111 |
| SS200 | | Non-fatty, non-oily foods | Brewers hose, discharge only | Chlorobutyl | EPDM | 1-1/2 - 4 | 350 | -40/+180 | 112 |
| SS231 | | Dry foods | Abrasion resistant | Natural rubber | Natural rubber | 2 - 6 | 110-200 | -20/+180 | 114 |
| SS290 | | Fatty, oily foods | Discharge only | Nitrile | Natural rubber | 1-1/2 - 4 | 250 | -20/+225 | 106 |
| SW319 | | Dry foods | Hot air blower, high temp | EPDM | EPDM | 1-1/4 - 3 | 150-250 | -20/+325/ +350 | 115 |
| SW330 | | Non-fatty, non-oily foods | | Chlorobutyl | EPDM | 1 - 4 | 150 | -40/+225 | 107 |
| SW373 | | Non-fatty, non-oily foods | Premium tube | FEP | EPDM | 1/2 - 4 | 100-500 | -40/+300 | 118 |
| SW383 | EXACT-CHEM™ | Dry foods | | MXLPE | EPDM | 1 - 6 | 150-200 | -40/+180 | 116 |
| SW430 | | Fatty, oily foods | | Nitrile | Nitrile | 1-1/2 - 4 | 150 | -20/+225 | 103 |
| SW431 | | Dry foods | Abrasion resistant | Natural rubber | Natural rubber | 4 - 5 | 100 | -20/+180 | 113 |
| SW574 | TITANFLEX® | Non-fatty, non-oily foods | Premium tube | FEP | EPDM | 3/4 - 4 | 200-400 | -40/+300 | 120 |
| SW630 | | Non-fatty, non-oily foods | | Chlorobutyl | EPDM | 1-1/2 - 4 | 200 | -40/+225 | 108 |
| SW640 | | Fatty, oily foods | | Nitrile | Nitrile | 1-1/2 - 4 | 200-250 | -20/+225 | 102 |
| SWC430 | | Fatty, oily foods | Corrugated | Nitrile | Nitrile | 2 - 6 | 100-150 | -20/+225 | 104 |
| SWC432 | | Fatty, oily foods | Corrugated | Nitrile | Nitrile | 2 - 4 | 100-200 | -20/+225 | 105 |
| SWC693 | TITANFLEX® | Non-fatty, non-oily foods | High pressure, high temp | UHMWPE | EPDM | 1 - 4 | 200-250 | -40/+250 | 122 |

NOTE: This is a guide only. It is the responsibility of the end user to select and/or test the most appropriate product for the application. Refer to product pages for specific data. Contact Parker for additional information.

See the following page for Hose Selector Guide by industry standard.

See pages ii and iii for an index of all product series by series number and pages iv through xi for an index by application and by series name.

Due to continual product improvements, Parker reserves the right to alter specifications without prior notice.



Parker Industrial HoseCustomer Service866 810 HOSE (4673)800 242 HOSE (4673)Strongsville, OHSouth Gate, CAEastern USAWestern USA

www.safehose.com



