Municipal **Woven Fire Hose**





Polyester Double Jacket **Rubber Lined Fire Hose**

Angus Ultima is the ultimate in quality, municipal grade fire hose. This durable, double jacket hose is constructed of 100% high tensile strength polyester yarns, both warp and filler, and lined with a high-tech E.P.D.M. tube. Its engineered design guarantees minimum weight with maximum durability and flexibility. The standard color for Ultima Hose is white. Other colors available with our innovative ARMOUR JACKET abrasion resistant coatings are red, yellow, orange, blue, green and tan.

		Į.	Angus Ultima			
		Pressure			Weight*	Coil Diameter
Size	Service	Proof	Burst	Bowl Size	50' (15m)	50' (15m)
inch mm	psi kPa	psi kPa	psi kPa	inch mm	lbs. kg	inch mm
1-1/2 38	400 2800	800 5600	1200 8400	1-15/16 49	15 6.8	18 457
1-3/4 45	400 2800	800 5600	1200 8400	2-1/8 54	22 9.9	18 457
2-1/2 65	400 2800	800 5600	1200 8400	3 76	31 14.0	21 533
3 75	400 2800	800 5600	1200 8400	3-9/16 90	42 18.9	21 533



Polyester Double Jacket Urethane Lined Fire Hose

Angus Ultima Lite is a lightweight hose that utilizes a thin, high tensile thermoplastic lining to minimize weight. Both the inner and outer jackets are constructed of polyester warp yarns and filament polyester filler yarns. Ultima Lite's lining meets the NSF (National Sanitation Foundation) Standard 61 for potable water and has a tensile strength of over 5000 psi (35,000 kPa). Ultima Lite is U.L. Listed. The standard color for Ultima Lite Hose is white. Other colors available with our innovative ARMOUR JACKET abrasion resistant coatings are red, yellow, orange, blue, green and tan.

			gus Ultima Lite			
		Pressure			Weight*	Coil Diameter
Size	Service	Proof	Burst	Bowl Size	50' (15m)	50' (15m)
inch mm	psi kPa	psi kPa	psi kPa	inch mm	lbs. kg	inch mm
1-1/2 38	400 2800	800 5600	1200 8400	1-15/16 49	12 5.4	16 406
1-3/4 45	400 2800	800 5600	1200 8400	2-1/8 54	14 6.3	16 406
2-1/2 65	400 2800	800 5600	1200 8400	3 76	25 11.3	19 483
3 75	400 2800	800 5600	1200 8400	3-9/16 90	31 14.0	19 483
0 ,0	100 2000	000 0000	1200 0100	0 77.0 70	01 1110	17 100

Premier

Nylon Double Jacket Rubber **Lined Fire Hose**

Angus Premier is constructed of high strength, low stretch entangled filament polyamide/cordura fibers over a rubber, ozone proof, E.P.D.M. tube. Premier Hose is available with our innovative ARMOUR JACKET abrasion resistant coating. The standard colors are red, yellow, orange, blue, green and tan.

			ngus Premier			
		Pressure			Weight*	Coil Diameter
Size	Service	Proof	Burst	Bowl Size	50' (15m)	50' (15m)
inch mm	psi kPa	psi kPa	psi kPa	inch mm	lbs. kg	inch mm
1-1/2 38	400 2800	800 5600	1200 8400	1-15/16 49	14 6.3	18 457
1-3/4 45	400 2800	800 5600	1200 8400	2-1/8 54	18 8.1	18 457
2-1/2 65	400 2800	800 5600	1200 8400	3 76	25 11.3	20 508
3 75	400 2800	800 5600	1200 8400	3-9/16 90	35 15.8	21 533
4 100	300 2100	600 4200	900 6300	4-17/32 115	41 18.6	25 635