

Municipal Rubber Covered Fire Hose



Red Chief Lightweight Attack Hose

Angus Red Chief is a nitrile rubber through-the-weave construction fire hose that is ideally suited for municipal fire protection. Its synthetic jacket is completely protected and locked in by a rubber cover and lining for extra toughness and extra durability. The heavy rib construction makes the hose highly resistant to cuts, punctures, impact and abrasion. With a proof pressure of 600 psi (4200 kPa) and a tolerance for temperatures from 1200°F to -37°F (649°C to -38°C), Red Chief is clearly superior to all other conventional fire hose constructions. Its lightweight design is virtually non-kinking. U.L. labeling is available on 1-1/2" and 2-1/2" at 200 PSI. The standard color for Red Chief is red.

Angus Red Chief													
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*		Coil Diameter	
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	lbs.	kg	inch	mm
1-1/2	38	300	2100	600	4200	900	6300	1-13/16	46	17	7.7	16	406
1-3/4	45	300	2100	600	4200	900	6300	2-1/16	52	19	8.6	16	406
2	50	300	2100	600	4200	900	6300	2-5/16	59	21	9.5	17	432
2-1/2	65	300	2100	600	4200	900	6300	2-7/8	73	28	12.6	18	457
3	75	300	2100	600	4200	900	6300	3-13/32	87	35	15.8	18	457

Yellow Chief Lightweight Attack Hose


Angus Yellow Chief is a lightweight nitrile rubber through-the-weave construction fire hose. Its synthetic jacket is completely protected and locked in by a rubber cover and lining for extra toughness and durability. A heavy rib construction makes this hose resistant to cuts, punctures, impact and abrasion. Yellow Chief is a 600 psi (4200 kPa) fire hose that withstands temperatures from 1200°F to -37°F, (649°C to -38°C). Its light-weight design is virtually non-kinking and ideal for municipal fire protection. The standard color for Yellow Chief is yellow.

Angus Yellow Chief													
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*		Coil Diameter	
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	lbs.	kg	inch	mm
1	25	300	2100	600	4200	900	6300	1-1/4	32	8	3.6	15	381
1-1/2	38	300	2100	600	4200	900	6300	1-13/16	46	16	7.3	16	406
1-3/4	45	300	2100	600	4200	900	6300	2-1/16	52	18	8.2	16	406
2	50	300	2100	600	4200	900	6300	2-5/16	59	20	9.1	17	432
2-1/2	65	300	2100	600	4200	900	6300	2-7/8	73	27	12.2	18	457
3	75	300	2100	600	4200	900	6300	3-13/32	87	33	15.0	18	457

Hi-Power High Rise Fire Hose

Angus Hi-Power is an ultra-lightweight, maneuverable, nitrile rubber hose designed specifically for fighting fires in high rise buildings. The lightweight through-the-weave construction is heat and puncture resistant, kink resistant and has low friction loss. The rubber cover prevents water from penetrating the reinforcement thus minimizing the weight of the hose when in service. The standard color for Hi-Power is blue.

Angus Hi-Power													
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*		Coil Diameter	
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	lbs.	kg	inch	mm
1-1/2	38	300	2100	600	4200	900	6300	1-3/4	44	11	5.0	13	330
1-3/4	45	300	2100	600	4200	900	6300	2	51	14	6.3	14	356
2	50	300	2100	600	4200	900	6300	2-3/16	56	18	8.1	14	356
2-1/2	65	300	2100	600	4200	900	6300	2-3/4	70	20	9.0	15	381

 Factory Mutual Approved
* Weight is uncoupled