

Application Data

Hose Quick Reference Chart

MATERIAL HANDLING HOSES

Hose Name	Product #	Page	Tube	Cover	Rein.	WP (PSI)	Size	Color	Features
DRY BULK TRANSFER									
Lynx Softwall Dry Material	H0319	67	Natural Rubber/SBR Blend	SBR	Fiber Spiral	50	4"	Black	Natural Rubber tube is static dissipating. Abrasion, age, and weather resistance. Discharge only.
Lynx HD Softwall Dry Material	H0521	68	Natural Rubber/SBR Blend	SBR	Fiber Spiral	50	4" and 5"	Black	1/4" thick heavy wall tube for extended service life. Natural Rubber tube is static dissipating. Abrasion, age, and weather resistance. Discharge only.
Sabertooth Dry Material	H0347	69	Natural Rubber/SBR Blend	SBR	Fiber Spiral with Helical Wire	100	3" and 4"	Black	Natural rubber tube is static dissipating. Hard wall for higher pressures. Abrasion, age, and weather resistance. Suction or discharge service.
HOT AIR									
Wildcat Hot Air	H0349	70	EPDM	EPDM/ Pin Pricked	Fiber Spiral/ Ply with Helical Wire	100-150	3" and 4"	Brown	Hot air blower hose for hot, dry, oil-free applications. Heat resistance +300°F. Age and weather resistant. Poor resistance to petroleum.

SPECIALTY SERVICE HOSES

Hose Name	Product #	Page	Tube	Cover	Rein.	WP (PSI)	Size	Color	Features
Hot Tar Pumping	H9603	72	Nitrile	CPE/Pin Pricked	Wire Braid	250	1"	Black	Ozone and weather resistant. Handles intermittent temperatures of up to 400°F.
Chemforce	H1560, H1561 & H1562	73	PVC/ Polyurethane Blend	PVC	Fiber Spiral	250, 600, or 800	3/8" thru 3/4"	Green, Yellow, Blue	Compatible with hydrocarbon-based aromatic chemicals. Excellent for pest control and lawn service.
Hydrocarbon Drain	H9690	74	Nitrile	CPE/Pin Pricked	Wire Braid	250	3/4"	Blue	High temp (up to 350°F), oil, and abrasion resistant.
Nitrogen Service	H8811	75	Nitrile	Neoprene/ Pinpricked	Fiber Spiral	300	1/2" and 3/4"	Yellow, Blue	Pinpricked cover. Abrasion, age, and oil resistant.
Kelly Power	H0377	76	Neoprene	Neoprene	Wire Spiral	3000	2"	Black	Abrasion, oil, and weather resistant.
Nyall	H1941 & H1942	77	Nylon	Neoprene (Black), Vinyl Nitrile (Colors)	Fiber Braid	500-750	1/4" thru 1"	Black, Red	Excellent chemical compatibility. Easy to clean. Low coefficient of friction. Paint and adhesive transfer.
Black Cat Hot Tar	H0372 & H0616	78	Nitrile	Neoprene Ply	Fiber-glass Braids w/Helical Wire	200	2" thru 4"	Black	Heat and oil resistant. Light weight. Handles intermittent temperatures of hot tar up to +400°F. (corrugated also available)
Bulldog Fuel Oil Delivery	H901	80	Nitrile RMA Class A	Vinyl Nitrile	Fiber Braid	250	1-1/4" thru 1-1/2"	Red	RMA Class A nitrile tube. Smooth, non-marking cover. Lightweight/Flexible.
Black Line LPG	H900	81	Nitrile	Vinyl Nitrile/ Pinpricked	Fiber Braid, 1" Built with SS Static Wires	100/1 Natural Gas	1/4" thru 1"	Black	UL 21 approved for LP Gas transfer. Abrasion resistant.
Chemical Booster	82-5751 82-5752	82	Rubber	Rubber	Textile Braid	800	3/4" thru 1"	Red	Abrasion, ozone and weather resistant.