

# Hose

## Low Working Pressure

 Refer to warnings and safety information on pages 3-4 and page 38.

### Boston Performer II



**Tube:** Nitrile

**Reinforcement:** Fiber, 1 or 2 Braid

**Cover:** Vinyl Nitrile

**Color:** Red

**Temperature Range:** -40°F To +180°F

**Type Of Branding:** Ink Print

**Working Pressure:** 225-300 PSI

**Type Of Coupling:** 'U' Series, 430 'U', Barbed Inserts, Quick Acting, Long Shank, Series or Steel Nipple. Clamps—Interlocking, Bolt, Band or Wire.

#### Features:

- Vinyl nitrile cover
- Nitrile tube (RMA Class A)
- Continuous permanent brand
- Multi-purpose hose
- High working pressure
- Braided reinforcement

#### Advantages:

- Abrasion, oil, and weather resistant
- High oil resistance
- Easy identification
- For many applications
- Better coupling retention for impulse applications

#### Markets:

- Assembly/Manufacturers
- Construction Industry
- Forest Industry
- Metal Working
- Mining
- Ship Building
- Plastic Molding

#### Applications:

- Pneumatic tools on production line
- Provide power to air operated equipment
- Convey air and water

PRODUCT NUMBER	NOMINAL I.D. (IN.) (MM)		BRAID	NOMINAL O.D. (IN.) (MM)		APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	STANDARD REELS (FT)
H11604-550R	1/4	6.3	1	1/2	12.7	10	225	550
H11504	1/4	6.3	2	19/32	15.1	15	300	50
H11504-550R								550
H11605-550R	5/16	7.9	1	5/8	15.9	14	225	550
H11505	5/16	7.9	2	21/32	15.9	14	300	50
H11505-550R								550
H11606-550R	3/8	9.5	1	21/32	16.7	15	225	550
H11506	3/8	9.5	2	3/32	18.3	19	300	50
H11506-550R								550
H11608-550R	1/2	12.7	1	13/16	20.6	21	225	550
H11508	1/2	12.7	2	7/8	22.2	27	300	50
H11508-550R								550
H11512	3/4	19.1	2	1-5/32	29.4	41	300	50
H11512-550R								550
H11516	1	25.4	2	1-7/16	36.5	46	250	50
H11516-300R								300
H11520	1-1/4	31.8	2	1-3/4	44.5	65	225	50
H11520-300R								300
H11524	1-1/2	38.1	2	2	50.8	82	225	50
H11524-300R								300