


Hose

Specialty Service Hoses

 Refer to warnings and safety information on pages 3-4 and page 71.

Boston Chemforce



Tube: PVC/Polyurethane Blend

Reinforcement: Fiber, 2 or 4 Spiral

Cover: PVC

Color: Yellow (YW), Green (GN) or Blue (BU)

Temperature Range: +15°F to +160°F

Type Of Branding: Unbranded

Working Pressure: 250, 600, 800 PSI

Type Of Coupling: Barbed Inserts. Clamps—Brass Collar. **Do not use internal expanded couplings.**

Features:

- Polyurethane/PVC blend tube
- Durable non-marking PVC cover
- Light weight
- Color availability
- Non-conductive
- Factory tested to exceed minimum electrical resistivity of one megohm per inch at 1000 volts D.C.

Advantages:

- Compatible with hydrocarbon based aromatic chemicals for pest control
- Excellent abrasion resistance
- Good ozone resistance
- Easy to handle and store
- Easy identification for color coded applications

Markets:

- Agriculture
- Nursery
- Orchard
- Landscape
- Lawn Care Services

Applications:

- Weed and pest control spraying; suitable for use with aromatic based hydrocarbons

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	SPIRAL	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	MTO* MIN. ORDER QTY.	STANDARD COILS (FT)
H156006-300R	3/8	9.5	2	13/20	16.5	13	250	3,000	300(GN)
H156008-300R	1/2	12.7	2	21/25	21.3	17	250	3,000	300(GN)
H156012-300R	3/4	19.1	2	1-1/40	26.0	35	250	3,000	300(GN)
H156106-300R	3/8	9.5	4	13/20	16.5	13	600	—	300(YW)
H156108-300R	1/2	12.7	4	21/25	21.3	17	600	—	300(YW)
H156110-300R	5/8	15.9	4	39/40	24.8	27	600	3,000	300(YW)
H156112-300R	3/4	19.1	4	1-7/50	29.0	35	600	—	300(YW)
H156206-300R	3/8	9.5	4	13/20	16.5	14	800	3,000	300(BU)
H156208-300R	1/2	12.7	4	21/25	21.3	21	800	—	300(BU)
H156212-300R	3/4	19.1	4	1-7/50	29.0	36	800	3,000	300(BU)

Stated working pressures are tested at 70°F. Working pressure decreases as temperature increases. See chart on page 14 showing the relationship between working pressure and temperature for reinforced PVC hose.

* MTO - Made to Order