


# Hose

## Food Clean-Up

 Refer to warnings and safety information on pages 3-4 and page 83.

### Boston Washdown 1250®



**Tube:** Nitrile  
**Reinforcement:** Fiber, 1 and 2 Braid  
**Cover:** Vinyl Nitrile  
**Color:** Grey  
**Temperature Range:** -40°F to +180°F  
**Type Of Branding:** Ink Print  
**Working Pressure:** 1,250 PSI  
**Type Of Coupling:** 'U' Series, Steel Nipple or Interlocking. Clamps—Interlocking.

#### Features:

- Vinyl nitrile cover
- Smooth cover
- Nitrile tube
- Continuous permanent brand/grey cover
- Longer lengths

#### Advantages:

- Abrasion, animal fat, vegetable oil, and weather resistant
- Easy to clean
- Heat resistant
- Detergent resistant
- Easy identification
- Economical; less waste

#### Markets:

- Food Industry
- Poultry Processing
- Industrial Cleaning Markets
- Construction Industry

#### Applications:

- Washdown of food processing facilities and equipment
- Transfer of hot detergent type solutions for cleaning equipment, tanks, buildings, etc.; maximum temperature +180°F
- Convey air and water

PRODUCT NUMBER	NOMINAL I.D. (IN.) (MM)		BRAID	NOMINAL O.D. (IN.) (MM)		APPROX. LBS. WEIGHT PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	MTO* MIN. ORDER QTY.	STANDARD REELS** (FT)
H967306-350R	3/8	9.5	1	45/64	17.8	16	1,250	—	350
H967308-350R	1/2	12.7	2	55/64	22.9	23	1,250	—	350
H967312-350R	3/4	19.1	2	1-11/64	29.8	30	1,250	3,200	350

\*MTO - Made to Order \*\* Reels will vary from 300 to 400 feet with maximum of 3 pieces per reel, no piece less than 50 feet.