


Hose

Dry Bulk Transfer

 Refer to warnings and safety information on pages 3-4 and page 83.

Boston Dry Bulk Food Discharge



Tube: White Natural Rubber, FDA Approved Materials

Reinforcement: 2 Ply Fiber with Dual Stainless Steel Static Wires

Cover: Natural Rubber/SBR Blend

Color: Grey

Temperature Range: -20°F to +160°F

Type Of Branding: Impression

Discharge: Dry Bulk Food Discharge

Working Pressure: 50 PSI (Depending on coupling)

Type Of Coupling: Cam and Groove. Clamps—Band.

Features:

- Grey SBR/natural rubber cover
- 7/32" natural rubber tube (white)
- Continuous printed brand
- Longer lengths
- Minimum 4-to-1 safety factor
- Dual static wire

Advantages:

- Abrasion and weather resistant
- Abrasion resistant for dry bulk food; FDA approved materials
- Easy identification
- Economical; less waste
- Meets industry standards
- Ground to coupling for increased static dissipation

Markets:

- Food Industry
- Plastic Industry
- Tank Truck Industry

Applications:

- Transfer of dry bulk food products
- Transfer of plastic pellets
- Transfer of bulk sugar, flour, rice, corn starch, and plastic pellets.

PRODUCT NUMBER	NOMINAL I.D. (IN.)	NOMINAL I.D. (MM)	PLY	NOMINAL O.D. (IN.)	NOMINAL O.D. (MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	MINIMUM BEND RADIUS (IN.)	MINIMUM BEND RADIUS (MM)	STANDARD LENGTH (FT)
H041364-100	4	101.6	2	4-3/4	120.7	225	50	11	279.4	100