

Metric Push-In Fittings

button. silicone free.

neously

temperature


Gripping Ring Technology




Quick Connect and Disconnect: Simply push tubing in. To remove, press the release ring towards the

fitting and pull tubing out. No tools required.

Male Connectors (Tube to Male BSPT)





Vacuum Capability: vacuum of 28" Hg (99% vacuum)

Reusable: connect and disconnect numerous times Full Flow: fitting seals on outside diameter of tubing Working Pressure: fittings rated to 290 PSI at ambient

Materials: Nickel-plated brass construction. Black body is glass-filled nylon; Buna-N O-ring seal; polypropylene release

Positive Seal: sealing and holding is accomplished instanta-



Female Connectors (Tube to Female BSPP)

(1000 10 10 10 10 10 10 10 10 10 10 10 10					
Tube O.D.	Female BSPP	Part #	Price/E	Pkg Qty	
4 mm	1/8"	31140410	\$6.75	10	
4 mm	1/4"	31140413	9.10	10	
6 mm	1/8"	31140610	6.80	10	
6 mm	1/4"	31140613	7.70	10	
8 mm	1/8"	31140810	8.60	10	
8 mm	1/4"	31140813	8.20	10	



Male Swivel Elbows (Tube to Male BSPT)

Tube O.D.	BSPT	Part #	Price/E	Pkg Qty
4 mm	1/8"	31090410	\$5.10	10
4 mm	1/4"	31090413	7.85	10
6 mm	1/8"	31090610	5.40	10
6 mm	1/4"	31090613	5.50	10
8 mm	1/8"	31090810	8.10	10
8 mm	1/4"	31090813	8.10	10



Male Swivel Branch Tees (Tube to Male BSPT)

Tube O.D.	Male BSPT	Part #	Price/E	Pkg Qty
4 mm	1/8"	31080410	\$7.30	10
4 mm	1/4"	31080413	10.65	10
6 mm	1/8"	31080610	7.65	10
6 mm	1/4"	31080613	7.80	10
8 mm	1/8"	31080810	9.65	10
8 mm	1/4"	31080813	10.05	10

Metric Nylon Tubing Rolls

- Resistant to fungus, abrasion, moisture and UV radiation.
- Temperature range -60°F to 200°F (Higher temperatures lower working pressures)
- Translucent color

Size O.D. I.D.	Wall Thickness	Work. Press.	Length	Part #	Price/ Length
4 mm x 2.7 mm 6 mm x 4 mm 8 mm x 6 mm	.65 mm 1 mm 1 mm	275 280 210	25 m 25 m 25 m	1025P0400 1025P0600 1025P0800	\$27.70 50.00 75.00



Tubing cutters sold on page 271

DPL108 153





