

## **Chemical Booster Fire Hose**

Coupled with female and male NST (NH) thread, hole type, chromed brass couplings. The vertical braid construction and red ozone resistant outer cover is designed to withstand the weathering and abrasion associated with severe service. See page 396 for hole type spanner wrench.

Working pressure: 800 PSI

## Coupled with female and male NST (NH) thread, chromed brass hole type couplings

Size	Length	Part #	Price / Each
3/4"	50'	80B07-50HCF	\$1010.20
3/4"	100'	80B07-100HCF	1679.05
1"	50'	80B10-50HCF	1200.30
1"	100'	80B10-100HCF	2016.25




**Aluminum Hose Type Booster Hose Couplings** 

Special tooling is required to attach these couplings to hose. See installation kit below.

- Hardcoat finish
- Complete set
- Working pressure: 800 PSI

Hose Size	Thread Type	Bowl Size	Part #	Price / Each
3/4"	1" NPSH	1-3/16"	ABH08118	\$142.10
3/4"	1" NPSH	1-1/4"	ABH08125	142.10
1"	1" NH (NST)	1-7/16"	ABH10143F	150.45
1"	1" NH (NST)	1-9/16"	ABH10156F	150.45







## **Polished Chrome Plated Brass Hole Type Booster Hose Couplings**

Special tooling is required to attach these couplings to hose. See installation kit below.

- Complete set
- Working pressure: 800 PSI

Hose Size	Thread Type	Bowl Size	Part #	Price / Each
3/4"	3/4" NH (NST)	1-3/16"	BW07118F-PC	\$268.40
3/4"	3/4" NH (NST)	1-1/4"	BW07125F-PC	268.40
1"	1" NH (NST)	1-7/16"	BW10143F-PC	312.85
1"	1" NH (NST)	1-9/16"	BW10156F-PC	312.85

\* ¾" and 1" NST threads are the same size. Also known as Chemical Hose Thread (CHT) or Booster Hose Thread.



## **Booster Hose Installation Kit**

Set includes: clamp, key, wrench, and half pint tar lube

	• • • • • • • • • • • • • • • • • • • •	•
Part #	Description	Price / Each
BW75AT BW10AT	3/4" (with aluminum clamps) 1" (with aluminum clamps)	\$561.25 706.45



DPL108 385



We Ship

