
# Pipe and Welding Fittings



### **Gaskets**

- Check gasket color code to be certain it is recommended for the service intended
- · Use lubricant on gasket
- For services not listed contact Dixon for recommendations

#### **EPDM Gaskets**

Compound type: EPDM

Temperature range: -22°F to +230°F

Color code: Black

General service application:

 Water, dilute acids, alkalies, salts, and many chemical services not involving hydrocarbons, oils, or gases.
Excellent oxidation resistance.

Not for use with hydrocarbons



1½"   G150E   \$23.75     2"   G200E   7.40     2½"   G250E   8.85     3"   G300E   9.80     4"   G400E   14.30     5"   G500E   42.00     6"   G600E   25.85     8"   G800E   42.10	Size	Part #	Price / Each
2½" G250E 8.85 3" G300E 9.80 4" G400E 14.30 5" G500E 42.00 6" G600E 25.85	1½"	G150E	\$23.75
3" G300E 9.80 4" G400E 14.30 5" G500E 42.00 6" G600E 25.85	2"	G200E	7.40
4"	2½"	G250E	8.85
5" <b>G500E</b> 42.00 6" <b>G600E</b> 25.85	3"	G300E	9.80
6" <b>G600E</b> 25.85	4"	G400E	14.30
	5"	G500E	42.00
8" <b>G800E</b> 42.10	6"	G600E	25.85
	8"	G800E	42.10

#### **Buna-N Gaskets**

Compound type: Buna-N

Temperature range: -24°F to +176°F

Color code: Blue

General service application:

 Petroleum products, vegetable oils, mineral oils, and air contaminated with petroleum oils.

Not for use in hot water services



Size	Black with orange stripe Part #	Price / Each	White Part #	Price / Each
1½"	G150T	\$23.75		
2"	G200T	7.40		
2½"	G250T	8.85		
3"	G300T	9.80		
4"	G400T	14.30	G400N	\$23.50
5"	G500T	42.00		
6"	G600T	25.85		
8"	G800T	42.10		

## **Gruvlok Lubricant - Groove Lube**



- Water soluble
- Non-toxic
- Non-corrosive
- Non-flammable
- NSF approved for use with potable water

Should <u>not</u> be used with HDPE pipe.

SAFETY
ALERT

Container	Size	Part #	Price/E
Tube	4½ oz.	GROOVLUB4	\$25.50
Tub	1 qt.	GROOVLUB32	130.85

## **Nuts and Bolts**

Pipe & Welding

- The nuts are a heavy hexagon design
- Nuts and bolts are made of electroplated carbon steel and conform to ASTM A183
- The bolts are specifically designed for use with the couplings on pages 478-480.

Price/E	Part #	Torque, Ft. Lbs.	Bolt Length	Bolt Thread
\$4.75	BLT38200	30	2"	3/8"
9.85	BLT38225	30	21/4"	3/8"
4.75	BLT50212	50	21/2"	1/2"
6.50	BLT50234	50	23/4"	1/2"
4.25	BLT58314	75	31/4"	5/8"
14.00	BLT75414	75	41/4"	3/4"
20.00	BLT78600	100	6"	7/8"

484 DPL108



