Brass Female to Female Hex Nipples

· Cast brass

| R | Contraction of the | ASLEDICE | | 1 |
|---|--------------------|----------|-------|-----|
| T | 37/1 | | (ing) | |
| | | | | 200 |
| | | | | |

| Female | Female | Dixon | Powhatan |
|--------------|----------|-----------------|--------------|
| Thread | NH (NST) | Part # | Part # |
| 1½" NPT | 1½" | FFH1515F | 14-156-00053 |
| 2½" NPT | 2½" | FFH2525F | 14-156-00100 |
| 1½" NH (NST) | 1½" | FFH15F15F | 14-156-00059 |
| 2½" NH (NST) | 2½" | FFH25F25F | 14-156-00098 |
| Female | Female | Dixon | Powhatan |
| Thread | NYFD | Part # | Part # |
| 1½" NYFD | 1½" | FFH15NYFD15NYFD | |
| 1½" NPT | 1½" | FFH1515NYFD | 14-156-00057 |
| 2½" NYFD | 2½" | FFH25NYFD25NYFD | |
| 2½" NPT | 2½" | FFH2525NYFD | 14-156-00127 |

· Other configurations are also available. Consult the factory for pricing and availability.

Brass Male x Groove Adapters with Internal Lugs



· Allows the conversion of a female NPT valve inlet to connect to groove piping

| Male | Groove | Length | Dixon |
|------|--------|---------|---------|
| NPT | Size | | Part # |
| 2½" | 2½" | 2-3/64" | VMIL250 |
| 4" | 4" | 2-3/64" | VMIL400 |

Brass Male x Male Adapters with Internal Lugs



Allows the conversion of a female NPT valve inlet to connect to hose

| Male | Male | Length | Dixon |
|-------|----------|----------|-----------|
| NPT | NH (NST) | | Part # |
| 21⁄2" | 2½" | 1-29/64" | DMIL250F |
| 21⁄2" | 3" | 1-31/64" | DMIL2530F |

bSales@GoodyearRubberProducts.com

We Ship

World Wi

