

XLT



Size Range (In) stock 2" to 6"
 Standard Length (Ft) 25'
 Standard Colors black
 Temperature Range (°F) -40° to 275°



- Very light weight thermoplastic rubber hose reinforced with a spring steel wire helix
- Excellent compressibility & flexibility
- Most compressible thermoplastic rubber hose in product line
- Designed for applications with wide temperature ranges
- Easy to install in tight spaces
- Recommended for light duty, low pressure applications
- Great moisture & UV resistance
- Excellent chemical resistance
- Wall Thickness = .012"



LT



Size Range (In) stock 1½" to 16"
 Standard Length (Ft) 25', 50'
 Standard Colors black
 Temperature Range (°F) -40° to 275°



- Light weight thermoplastic rubber hose reinforced with a spring steel wire helix
- Excellent compressibility & flexibility
- Designed for applications with wide temperature ranges
- Great moisture & UV resistance
- Excellent chemical resistance
- Smooth interior assures minimal friction loss & efficient air flow
- Wall Thickness = .020"



HT



Size Range (In) stock 1½" to 16"
 Standard Length (Ft) 25', 50'
 Standard Colors black
 Temperature Range (°F) -40° to 275°



- Heavy weight thermoplastic rubber hose reinforced with a spring steel wire helix
- Suitable for more demanding positive & negative pressure applications
- Designed for applications with wide temperature ranges
- Great moisture & UV resistance
- Excellent chemical resistance
- Smooth interior assures minimal friction loss & efficient air flow
- Wall Thickness = .045"



HT-W



Size Range (In) stock 8" to 12"
 Standard Length (Ft) 25'
 Standard Colors black with yellow wearstrip
 Temperature Range (°F) -40° to 275°



- Heavy weight thermoplastic rubber hose reinforced with a spring steel wire helix & external polypropylene wearstrip
- Wearstrip offers additional external abrasion & drag resistance
- Suitable for more demanding positive & negative pressure applications including lawn & leaf collection
- Designed for applications with wide temperature ranges
- Great moisture & UV resistance
- Excellent chemical resistance
- Smooth interior assures minimal friction loss & efficient air flow
- Wall Thickness = .054"

