

Flexco® Bolt Hinged Fastener System

Extra Hinge Pins

For 375X and 550

Belt Width		Ordering Number							
		NC (1/4" dia.) Nylon Covered Steel Cable		NCS (1/4" dia.) Nylon Covered Stainless Cable*		SC (1/4" dia.) Bare Steel Cable		SSC (7/32" dia.) Bare Stainless Cable*	
in.	mm	Each (One Pin)	Package (Ten Pins)	Each (One Pin)	Package (Ten Pins)	Each (One Pin)	Package (Ten Pins)	Each (One Pin)	Package (Ten Pins)
18	450	NC-18-1	NC-18		NCS-18				
24	600	NC-24-1	NC-24	NCS-24-1	NCS-24	SC-24-1	SC-24	SSC-24-1	SSC-24
30	750	NC-30-1	NC-30	NCS-30-1	NCS-30	SC-30-1	SC-30	SSC-30-1	SSC-30
36	900	NC-36-1	NC-36	NCS-36-1	NCS-36	SC-36-1	SC-36	SSC-36-1	SSC-36
42	1050	NC-42-1	NC-42	NCS-42-1	NCS-42	SC-42-1	SC-42	SSC-42-1	SSC-42
48	1200	NC-48-1	NC-48	NCS-48-1	NCS-48	SC-48-1	SC-48	SSC-48-1	SSC-48
60	1500	NC-60-1	NC-60	NCS-60-1	NCS-60				

* 300 Series

NC – Nylon Covered Steel Cable

Nylon covering reduces corrosion and simplifies hinge pin insertion.

SC – Bare Steel Cable

Recommended for abrasive or gritty material conveyance.

NCS – Nylon Covered Stainless Steel Cable

For greater corrosion resistance.

SSC – Bare 300 Series Stainless Steel Cable

For conditions where corrosion attacks ordinary steel pins.

Extra piloted bolts and nuts

Replacement piloted bolts and nuts are packaged separately, 100 per box.



Extra Piloted Bolts

For Fastener Number	Ordering Number	
	Steel	Stainless – 300 Series
375X	20398	20400
550	20399	20400

Extra Nuts

For Fastener Number	Ordering Number	
	Steel	Stainless – 300 Series
375X	20380	20381*
550	20380	20381*

* Slotted Nuts

Plastic filler tubing reduces sifting

Flexco Plastic Filler Tubing is furnished in all “J” cartons, and keeps sifting of fine materials through the hinged joint to a minimum. It is included with every “J” carton and is sold by the 100-foot reel.

Filler Tubing

Description	Qty.	Ordering Number
375X / 550	100'/Pkg.	30894

